15-213

Machine-Level Programming III: Procedures
Feb. 8, 2000

Topics
- IA32 stack
- Stack-based languages
- Stack frames
- Register saving conventions
- Creating pointers to local variables

IA32 Stack

- Region of memory managed with stack discipline
- Register `%esp` indicates lowest allocated position in stack
  - i.e., address of top element

Pushing
- `pushl` *Src*
- Fetch operand at *Src*
- Decrement `%esp` by 4
- Write operand at address given by `%esp`

Popping
- `popl` *Dest*
- Read operand at address given by `%esp`
- Increment `%esp` by 4
- Write to *Dest*



Stack Operation Examples



Procedure Control Flow

Use stack to support procedure call and return

Procedure call:

`call label` Push return address on stack; Jump to *label*

Return address value
- Address of instruction beyond `call`
- Example from disassembly

```
804854e:    e8 3d 06 00 00    call   8048b90 <main>
8048553:    50                pushl  %eax
```

  - Return address = `0x8048553`

Procedure return:
- `ret` Pop address from stack; Jump to address

Procedure Call / Return Example

```
804854e:  e8 3d 06 00 00      call   8048b90 <main>
8048553:  50                  pushl  %eax
```



%eip is program counter

Stack-Based Languages

Languages that Support Recursion

- e.g., C, Pascal, Java
- Code must be "*Reentrant*"
  - Multiple simultaneous instantiations of single procedure
- Need some place to store state of each instantiation
  - Arguments
  - Local variables
  - Return pointer

Stack Discipline

- State for given procedure needed for limited time
  - From when called to when return
- Callee returns before caller does

Stack Allocated in *Frames*

- state for single procedure instantiation

Call Chain Example

Code Structure

```
yoo(…)
{
   •
   •
   who();
   •
   •
}
```

```
who(…)
{
   •
   •
   amI();
   •
   •
}
```

```
amI(…)
{
   •
   •
   amI();
   •
   •
}
```

Call Chain



- Procedure `amI` recursive

IA32 Stack Structure

Stack Growth

- Toward lower addresses

Stack Pointer

- Address of next available location in stack
- Use register `%esp`

Frame Pointer

- Start of current stack frame
- Use register `%ebp`



IA32/Linux Stack Frame

Callee Stack Frame ("Top" to Bottom)

- Parameters for called functions
- Local variables
  - If can't keep in registers
- Saved register context
- Old frame pointer

Caller Stack Frame

- Return address
  - Pushed by `call` instruction
- Arguments for this call



Revisiting `swap`

```
int zip1 = 15213;
int zip2 = 91125;

void call_swap()
{
  swap(&zip1, &zip2);
}
```

```
void swap(int *xp, int *yp)
{
  int t0 = *xp;
  int t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```

```
call_swap:
    • • •
    pushl $zip2
    pushl $zip1
    call swap
    • • •
```



Revisiting `swap`

```
void swap(int *xp, int *yp)
{
  int t0 = *xp;
  int t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```

```
swap:
    pushl %ebp
    movl %esp,%ebp
    pushl %ebx

    movl 12(%ebp),%ecx
    movl 8(%ebp),%edx
    movl (%ecx),%eax
    movl (%edx),%ebx
    movl %eax,(%edx)
    movl %ebx,(%ecx)

    movl -4(%ebp),%ebx
    movl %ebp,%esp
    popl %ebp
    ret
```

Set Up

Body

Finish

`swap` Setup




```
swap:
    pushl %ebp
    movl %esp,%ebp
    pushl %ebx
```

swap Finish



Observation

- Saved & restored register `%ebx`
- Didn't do so for `%eax`, `%ecx`, or `%edx`

Register Saving Conventions

When procedure `yoo` calls `who`:

- `yoo` is the *caller*, `who` is the *callee*

Can Register be Used for Temporary Storage?

```
yoo:
    • • •
    movl $15213, %edx
    call who
    addl %edx, %eax
    • • •
    ret
```

```
who:
    • • •
    movl 8(%ebp), %edx
    addl $91125, %edx
    • • •
    ret
```

- Contents of register `%edx` overwritten by `who`

Conventions

- "Caller Save"
  - Caller saves temporary in its frame before calling
- "Callee Save"
  - Callee saves temporary in its frame before using

IA32/Linux Register Usage

- Surmised by looking at code examples

Integer Registers

- Two have special uses
  `%ebp, %esp`
- Three managed as callee-save
  `%ebx, %esi, %edi`
  - Old values saved on stack prior to using
- Three managed as caller-save
  `%ebx, %esi, %edi`
  - Do what you please, but expect any callee to do so, as well
- Register `%eax` also stores returned value



Recursive Factorial

```
int rfact(int x)
{
  int rval;
  if (x <= 1)
    return 1;
  rval = rfact(x-1);
  return rval * x;
}
```

Complete Assembly

- Assembler directives
  - Lines beginning with "."
  - Not of concern to us
- Labels
  - `.Lxx`
- Actual instructions

```
.globl rfact
    .type
rfact,@function
rfact:
    pushl %ebp
    movl %esp,%ebp
    pushl %ebx
    movl 8(%ebp),%ebx
    cmpl $1,%ebx
    jle .L78
    leal -1(%ebx),%eax
    pushl %eax
    call rfact
    imull %ebx,%eax
    jmp .L79
    .align 4
.L78:
    movl $1,%eax
.L79:
    movl -4(%ebp),%ebx
    movl %ebp,%esp
    popl %ebp
    ret
```

Rfact Stack Setup



Rfact Body

```
  movl 8(%ebp),%ebx   # ebx = x
  cmpl $1,%ebx        # Compare x : 1
  jle .L78            # If <= goto Term
  leal -1(%ebx),%eax  # eax = x-1
  pushl %eax          # Push x-1
  call rfact          # rfact(x-1)
  imull %ebx,%eax     # rval * x
  jmp .L79            # Goto done
.L78:                 # Term:
  movl $1,%eax        # return val = 1
.L79:                 # Done:
```

```
int rfact(int x)
{
  int rval;
  if (x <= 1)
    return 1;
  rval = rfact(x-1);
  return rval * x;
}
```

Registers

- $ebx Stored value of x
- $eax
  - Temporary value of x-1
  - Returned value from rfact(x-1)
  - Returned value from this call

Rfact Recursion



Rfact Result



Rfact Completion



Pointer Code

Recursive Procedure

```
void s_helper
  (int x, int *accum)
{
  if (x <= 1)
    return;
  else {
    int z = *accum * x;
    *accum = z;
    s_helper (x-1,accum);
  }
}
```

Top-Level Call

```
int sfact(int x)
{
  int val = 1;
  s_helper(x, &val);
  return val;
}
```

- Pass pointer to update location
- Uses tail recursion
  - But GCC only partially optimizes it

Creating & Initializing Pointer

Initial part of `sfact`

```
_sfact:
   pushl %ebp          # Save %ebp
   movl %esp,%ebp      # Set %ebp
   subl $16,%esp       # Add 16 bytes
   movl 8(%ebp),%edx   # edx = x
   movl $1,-4(%ebp)    # val = 1
```



Using Stack for Local Variable

- Variable `val` must be stored on stack
  - Need to create pointer to it
- Compute pointer as `-4(%ebp)`
- Push on stack as second argument

```
int sfact(int x)
{
  int val = 1;
  s_helper(x, &val);
  return val;
}
```


Passing Pointer

Calling `s_helper` from `sfact`

```
   leal -4(%ebp),%eax  # Compute &val
   pushl %eax          # Push on stack
   pushl %edx          # Push x
   call _s_helper      # call
   movl -4(%ebp),%eax  # Return val
   • • •               # Finish
```

```
int sfact(int x)
{
  int val = 1;
  s_helper(x, &val);
  return val;
}
```

Stack at time of call



Using Pointer

```
void s_helper
  (int x, int *accum)
{
  • • •
    int z = *accum * x;
    *accum = z;
  • • •
}
```

```
  • • •
  movl %ecx,%eax     # z = x
  imull (%edx),%eax  # z *= *accum
  movl %eax,(%edx)   # *accum = z
  • • •
```

- **Register `%ecx` holds `x`**
- **Register `%edx` holds `accum`**
  - Use access `(%edx)` to reference memory

Multi-Way Recursion

```
int r_prod
  (int from, int to)
{
  int middle;
  int prodA, prodB;
  if (from >= to)
    return from;
  middle = (from + to) >> 1;
  prodA = r_prod(from, middle);
  prodB = r_prod(middle+1, to);
  return prodA * prodB;
}
```

Top-Level Call

```
int bfact(int x)
{
  return r_prod(1,x);
}
```

- **Compute product** $x * (x+1) * \ldots * (y-1) * y$
- **Split into two ranges:**
  - **Left:** $x * (x+1) * \ldots * (m-1) * m$
  - **Right:** $(m+1) * \ldots * (y-1) * y$
    $m = \lfloor (x+y)/2 \rfloor$
- **No real advantage algorithmically**

Binary Splitting Example



Multi-Way Recursive Code

Stack Frame

12	from
8	to
4	Rtn Adr
0	Old $ebp
-4	Old $edi
-8	Old $esi
-12	Old $ebx

`$eax`
  from
  return values

Callee Save Regs.

`$ebx` middle
`$edi` to
`$esi` prodA

```
_r_prod:
  • • •                  # Setup
  movl 8(%ebp),%eax      # eax = from
  movl 12(%ebp),%edi     # edi = to
  cmpl %edi,%eax         # from : to
  jge L8                 # if >= goto done
  leal (%edi,%eax),%ebx # from + to
  sarl $1,%ebx           # middle
  pushl %ebx             # 2nd arg: middle
  pushl %eax             # 1st arg: from
  call _r_prod           # 1st call
  pushl %edi             # 2nd arg: to
  movl %eax,%esi         # esi = ProdA
  incl %ebx              # middle + 1
  pushl %ebx             # ... 1st arg
  call _r_prod           # 2nd call
  imull %eax,%esi        # ProdA * ProdB
  movl %esi,%eax         # Return value
L8:                    # done:
  • • •                  # Finish
```

Multi-Way Recursive Code Finish




```
L8:                     # done:
   leal -12(%ebp),%esp # Set Stack Ptr
   popl %ebx            # Restore %ebx
   popl %esi            # Restore %esi
   popl %edi            # Restore %edi
   movl %ebp,%esp       # Restore %esp
   popl %ebp            # Restore %ebp
   ret                  # Return
```

Stack

- After making recursive calls, still has two arguments on top

Finishing Code

- Moves stack pointer to start of saved register area
- Pops registers

Mutual Recursion

Top-Level Call

```
int lrfact(int x)
{
  int left = 1;
  return
   left_prod(&left, &x);
}
```

```
int left_prod
(int *leftp, int *rightp)
{
  int left = *leftp;
  if (left >= *rightp)
    return left;
  else {
    int plus1 = left+1;
    return left *
      right_prod(&plus1, rightp);
  }
}
```

```
int right_prod
(int *leftp, int *rightp)
{
  int right = *rightp;
  if (*leftp == right)
    return right;
  else {
    int minus1 = right-1;
    return right *
      left_prod(leftp, &minus1);
  }
}
```


Mutually Recursive Execution Example

Calling

- Recursive routines pass two arguments
  - Pointer to own local variable
  - Pointer to caller's local variable



Implementation of `lrfact`

Call to Recursive Routine

```
int left = 1;
return left_prod(&left, &x);
```

Code for Call

```
leal 8(%ebp),%edx # edx = &x
pushl %edx        # push &x
leal -4(%ebp),%eax# eax = &left
pushl %eax        # push &left
call _left_prod   # Call
```

Stack at time of call



Implementation of `left_prod`

Call to Recursive Routine

```
int plus1 = left+1;
return left *
  right_prod(&plus1, rightp);
```

```
# %ebx holds left
# %edx holds rightp
leal 1(%ebx),%ecx   # left+1
movl %ecx,-4(%ebp)  # Store in plus1
pushl %edx          # Push rightp
leal -4(%ebp),%eax  # &plus1
pushl %eax          # Push &plus1
call _right_prod    # Call
```

Stack at time of call



Tail Recursion

Tail Recursive Procedure

```
int t_helper
  (int x, int val)
{
  if (x <= 1)
    return val;
  return
    t_helper(x-1, val*x);
}
```

General Form

```
t_helper(x, val)
{
   • • •
  return
   t_helper(Xexpr, Vexpr)
}
```

Top-Level Call

```
int tfact(int x)
{
  return t_helper(x, 1);
}
```

Form

- Directly return value returned by recursive call

Consequence

- Can convert into loop

Removing Tail Recursion

Optimized General Form

```
t_helper(x, val)
{
 start:
   • • •
  val = Vexpr;
  x = Xexpr;
  goto start;
}
```

Resulting Code

```
int t_helper
  (int x, int val)
{
 start:
  if (x <= 1)
    return val;
  val = val*x;
  x = x-1;
  goto start;
}
```

Effect of Optimization

- Turn recursive chain into single procedure
- No stack frame needed
- Constant space requirement
  - Vs. linear for recursive version

Generated Code for Tail Recursive Proc.

Optimized Form

```
int t_helper
  (int x, int val)
{
 start:
  if (x <= 1)
    return val;
  val = val*x;
  x = x-1;
  goto start;
}
```

Code for Loop

```
  # %edx = x
  # %ecx = val
L53:                # start:
  cmpl $1,%edx        # x : 1
  jle L52             # if <= goto done
  movl %edx,%eax      # eax = x
  imull %ecx,%eax     # eax = val * x
  decl %edx           # x--
  movl %eax,%ecx      # val = val * x
  jmp L53           # goto start
L52:                  # done:
```

Registers

$edx x

$ecx val

Main Ideas

Stack Provides Storage for Procedure Instantiation

- Save state
- Local variables
- Any variable for which must create pointer

Assembly Code Must Manage Stack

- Allocate / deallocate by decrementing / incrementing stack pointer
- Saving / restoring register state

Stack Adequate for All Forms of Recursion

- Multi-way
- Mutual