15-213 Recitation 5 - 2/19/01

Outline

- Structured Data: `structs` / `unions`
- Alignment
- Floating Point

Reminders

- Lab 2: Wednesday, 11:59
- EXAM 1: Tuesday, 2/27
  - UC McConomy

Shaheen Gandhi

e-mail:

sgandhi@andrew.cmu.edu

Office Hours:

Wednesday 12:30 – 2:30

Wean 3108

`structs` and `unions`

- Organize data
- `structs` store multiple elements, `unions` store a single element at a time
- Members of a `union` change how you look at data
- `unions` used for mutually exclusive data

Alignment

- Contiguous areas of memory
- Each block is *aligned*
  - Size is a multiple of a base value
  - "Base value" is the largest alignment of data types in structure
- Why?
  - Efficient load/store from memory
  - Virtual Memory paging
- This applies to any variable type

Structure of a `struct`

- Find largest alignment
  - Size of structure must be a multiple of this
- For each element e (top to bottom):
  - Find alignment of e
    - Starting offset must be a multiple of this
  - Pad previous element with empty space until alignment matches
  - Allocate alignment worth of space to e
- Pad last element with empty space until alignment of structure matches
- Note this isn't optimal!

Structure of a `union`

- Find largest alignment
  - Size of structure must be a multiple of this
- Allocate this much space

Examples

```
struct one {
  int i;
  double d;
  char c[2];
}
```

```
union two {
  int i;
  double d;
  char c[2];
}
```

Floating Point

(Better known as "I'm going to kill the person that thought this up")

- IEEE Floating Point
  - Standard notation
  - Tons of features we won't look at
- Floating Point at a bit level:

  - s – sign bit (S)
  - exp – exponent (maps to E, has e bits)
  - frac –significand (maps to M, has f bits)
- Numerical Equivalent: $-1^s\ M\ 2^E$
- "Normalized" and "Denormalized" encoding

"Normalized" Encoding

- exp ≠ 0 and exp ≠ 111…1
  - If exp = 111…1, it's ∞ or NAN
- E = exp – B
  - B is the "Bias"
  - Usually $2^{e-1} - 1$, but can be different
  - exp: Unsigned integer value [1, $2^e - 1$]
- M = 1.{frac}
  - {frac} are the bits of frac
  - frac is a fractional binary number
- Normalized Numbers have range [2^{1-B}, 2^{B+1})
  - And their negatives

"Denormalized" Encoding

- exp = 0
- E = -B+1
- M = 0.{frac}
- Denormalized Numbers have Range [0, 2^{1-B})
  - And their negatives



Examples

- 8 bit FP, 1 bit sign, 4 bit exponent, 3 bit significand, Bias of 7

Representation -> Number

0 0101 011	0.34375
0 0000 101	0.009765625
1 1011 110	-28.0