# Machine-Level Programming V: Advanced Topics

15-213: Introduction to Computer Systems 9<sup>th</sup> Lecture, February 13

#### **Instructors:**

Franz Franchetti, Seth Copen Goldstein, and Brian Railing

# **Today**

- Memory Layout
- Buffer Overflow
  - Vulnerability
  - Protection
- Unions

# x86-64 Linux Memory Layout

00007FFFFFFFFFFF

### Stack

- Runtime stack (8MB limit)
- E. g., local variables

## Heap

- Dynamically allocated as needed
- When call malloc(), calloc(), new()

#### Data


- Statically allocated data
- E.g., global vars, static vars, string constants

**Hex Address** 

## Text / Shared Libraries

- Executable machine instructions
- Read-only

400000



# **Memory Allocation Example**

```
char big_array[1L<<24]; /* 16 MB */
char huge_array[1L<<31]; /* 2 GB */</pre>
int global = 0;
int useless() { return 0; }
int main ()
   void *p1, *p2, *p3, *p4;
    int local = 0;
   p1 = malloc(1L << 28); /* 256 MB */
   p2 = malloc(1L << 8); /* 256 B */
   p3 = malloc(1L << 32); /* 4 GB */
   p4 = malloc(1L << 8); /* 256 B */
 /* Some print statements ... */
```

# Stack **Shared** Libraries Heap Data **Text**


Where does everything go?

**x86-64 Example Addresses** 

address range ~247

local
p1
p3
p4
p2
big\_array
huge\_array
main()
useless()

0x00007ffe4d3be87c 0x00007f7262a1e010 0x00007f7162a1d010 0x0000000008359d120 0x0000000008359d010 0x00000000080601060 0x00000000000601060 0x0000000000040060c 0x00000000000400590




00007F

# **Runaway Stack Example**

00007FFFFFFFFFF

```
int recurse(int x) {
   int a[2<<15];    /* 2~17 = 128 KiB */
   printf("x = %d. a at %p\n", x, a);
   a[0] = (2<<13)-1;
   a[a[0]] = x-1;
   if (a[a[0]] == 0)
      return -1;
   return recurse(a[a[0]]) - 1;
}</pre>
```



- Functions store local data on in stack frame
- Recursive functions cause deep nesting of frames

```
./runaway 48
x = 48. a at 0x7fffd43e45d0
x = 47. a at 0x7fffd43a45c0
x = 46. a at 0x7fffd43645b0
x = 45. a at 0x7fffd43245a0
. . .
x = 4. a at 0x7fffd38e4310
x = 3. a at 0x7fffd38a4300
x = 2. a at 0x7fffd38642f0
Segmentation fault
```

# **Today**

- Memory Layout
- Buffer Overflow
  - Vulnerability
  - Protection
- Unions

# Recall: Memory Referencing Bug Example

```
typedef struct {
  int a[2];
  double d;
} struct_t;

double fun(int i) {
  volatile struct_t s;
  s.d = 3.14;
  s.a[i] = 1073741824; /* Possibly out of bounds */
  return s.d;
}
```

```
fun(0) -> 3.14
fun(1) -> 3.14
fun(2) -> 3.1399998664856
fun(3) -> 2.00000061035156
fun(4) -> 3.14
fun(6) -> Segmentation fault
```


Result is system specific

# **Memory Referencing Bug Example**

```
typedef struct {
  int a[2];
  double d;
} struct_t;
```

```
fun(0) -> 3.14
fun(1) -> 3.14
fun(2) -> 3.1399998664856
fun(3) -> 2.00000061035156
fun(4) -> 3.14
fun(6) -> Segmentation fault
```

## **Explanation:**



# Such problems are a BIG deal

- Generally called a "buffer overflow"
  - when exceeding the memory size allocated for an array
- Why a big deal?
  - It's the #1 technical cause of security vulnerabilities
    - #1 overall cause is social engineering / user ignorance

### Most common form

- Unchecked lengths on string inputs
- Particularly for bounded character arrays on the stack
  - sometimes referred to as stack smashing

# **String Library Code**

Implementation of Unix function gets()

```
/* Get string from stdin */
char *gets(char *dest)
{
   int c = getchar();
   char *p = dest;
   while (c != EOF && c != '\n') {
        *p++ = c;
        c = getchar();
   }
   *p = '\0';
   return dest;
}
```

- No way to specify limit on number of characters to read
- Similar problems with other library functions
  - strcpy, strcat: Copy strings of arbitrary length
  - scanf, fscanf, sscanf, when given %s conversion specification

## **Vulnerable Buffer Code**

```
/* Echo Line */
void echo()
{
    char buf[4]; /* Way too small! */
    gets(buf);
    puts(buf);
}
```

←btw, how big is big enough?

```
void call_echo() {
   echo();
}
```

```
unix>./bufdemo-nsp
Type a string:012345678901234567890123
012345678901234567890123
```

```
unix>./bufdemo-nsp
Type a string:0123456789012345678901234
Segmentation Fault
```

# **Buffer Overflow Disassembly**

## echo:

```
00000000004006cf <echo>:
4006cf: 48 83 ec 18
                                       $0x18,%rsp
                                sub
4006d3: 48 89 e7
                                       %rsp,%rdi
                                mov
4006d6: e8 a5 ff ff ff
                                       400680 <gets>
                                callq
4006db: 48 89 e7
                                       %rsp,%rdi
                                mov
4006de: e8 3d fe ff ff
                                       400520 <puts@plt>
                                callq
4006e3: 48 83 c4 18
                                       $0x18,%rsp
                                add
4006e7: c3
                                retq
```

## call\_echo:

4006e	8: 48	83	ec	08		sub	\$0x8,%rsp
4006e	c: b8	00	00	00	00	mov	\$0x0,%eax
4006f	1: e8	d9	ff	ff	ff	callq	4006cf <echo></echo>
4006f	<b>5:</b> 48	83	<b>c4</b>	80		add	\$0x8,%rsp
4006f	a: c3					retq	

## **Buffer Overflow Stack**

## Before call to gets

```
Stack Frame
for call_echo
Return Address
   (8 bytes)
20 bytes unused
```


```
/* Echo Line */
void echo()
{
    char buf[4]; /* Way too small! */
    gets(buf);
    puts(buf);
}
```

```
[3][2][1][0] buf \leftarrow %rsp
```

```
echo:
subq $24, %rsp
movq %rsp, %rdi
call gets
...
```

# **Buffer Overflow Stack Example**

#### Before call to gets



```
void echo()
                    echo:
                      subq
                            $24, %rsp
    char buf[4];
                            %rsp, %rdi
                      movq
   gets(buf);
                      call
                            gets
```

## call\_echo:

```
4006f1:
         callq 4006cf <echo>
4006f6:
         add
                $0x8,%rsp
```

## **Buffer Overflow Stack Example #1**

### After call to gets

Stack Frame for call_echo						
00	00	00	00			
00	40	06	f6			
00	32	31	30			
39	38	37	36			
35	34	33	32			
31	30	39	38			
37	36	35	34			
33	32	31	30			

```
void echo()
{
    char buf[4];
    gets(buf);
}
echo:
subq $24, %rsp
movq %rsp, %rdi
call gets
...
}
```

## call\_echo:

```
4006f1: callq 4006cf <echo>
4006f6: add $0x8,%rsp
...
```

buf ← %rsp

```
unix>./bufdemo-nsp
Type a string:01234567890123456789012
01234567890123456789012
```

"01234567890123456789012\0"

#### Overflowed buffer, but did not corrupt state

## **Buffer Overflow Stack Example #2**

### After call to gets

Stack Frame for call_echo						
00	00	00	00			
00	40	00	34			
33	32	31	30			
39	38	37	36			
35	34	33	32			
31	30	39	38			
37	36	35	34			
33	32	31	30			

```
void echo()
{
    char buf[4];
    gets(buf);
}

echo:
subq $24, %rsp
movq %rsp, %rdi
call gets
...
}
```

## call\_echo:

```
4006f1: callq 4006cf <echo>
4006f6: add $0x8,%rsp
...
```


buf ← %rsp

```
unix>./bufdemo-nsp
Type a string:0123456789012345678901234
Segmentation Fault
```

"0123456789012345678901234\0"


## **Overflowed buffer and corrupted return pointer**

# **Stack Smashing Attacks**



- Overwrite normal return address A with address of some other code S
- When Q executes ret, will jump to other code


# **Crafting Smashing String**



### **Attack String (Hex)**

30 31 32 33 34 35 36 37 38 39 30 31 32 33 34 35 36 37 38 39 30 31 32 33 a3 08 40 00 00 00 00


# **Smashing String Effect**



#### Attack String (Hex)


30 31 32 33 34 35 36 37 38 39 30 31 32 33 34 35 36 37 38 39 30 31 32 33 a3 08 40 00 00 00 00

# **Code Injection Attacks**



- Input string contains byte representation of executable code
- Overwrite return address A with address of buffer B
- When Q executes ret, will jump to exploit code

## **How Does The Attack Code Execute?**



## What To Do About Buffer Overflow Attacks

- Avoid overflow vulnerabilities
- Employ system-level protections
- Have compiler use "stack canaries"

Lets talk about each...

# 1. Avoid Overflow Vulnerabilities in Code (!)

```
/* Echo Line */
void echo()
{
    char buf[4]; /* Way too small! */
    fgets(buf, 4, stdin);
    puts(buf);
}
```

- For example, use library routines that limit string lengths
  - fgets instead of gets
  - strncpy instead of strcpy
  - Don't use scanf with %s conversion specification
    - Use fgets to read the string
    - Or use %ns where n is a suitable integer

# 2. System-Level Protections can help


## Randomized stack offsets

- At start of program, allocate random amount of space on stack
- Shifts stack addresses for entire program
- Makes it difficult for hacker to predict beginning of inserted code
- E.g.: 5 executions of memory allocation code

local


0x7ffe4d3be87c 0x7fff75a4f9fc 0x7ffeadb7c80c 0x7ffeaea2fdac 0x7ffcd452017c

 Stack repositioned each time program executes



# 2. System-Level Protections can help

- Nonexecutable code segments
  - In traditional x86, can mark region of memory as either "read-only" or "writeable"
    - Can execute anything readable
  - x86-64 added explicit "execute" permission
  - Stack marked as nonexecutable



Any attempt to execute this code will fail

## 3. Stack Canaries can help

#### Idea

- Place special value ("canary") on stack just beyond buffer
- Check for corruption before exiting function

## GCC Implementation

- -fstack-protector
- Now the default (disabled earlier)

```
unix>./bufdemo-sp
Type a string:0123456
0123456
```

```
unix>./bufdemo-sp
Type a string:01234567
*** stack smashing detected ***
```

# **Protected Buffer Disassembly**

#### echo:

```
40072f:
                 $0x18,%rsp
         sub
400733:
                 %fs:0x28,%rax
         mov
40073c:
                 %rax,0x8(%rsp)
         mov
400741:
                %eax,%eax
         xor
400743:
                %rsp,%rdi
         mov
                4006e0 <gets>
400746:
         callq
40074b:
                 %rsp,%rdi
         mov
40074e:
         callq
                400570 <puts@plt>
400753:
                 0x8(%rsp),%rax
         mov
                %fs:0x28,%rax
400758:
         xor
400761:
         iе
                400768 < echo + 0x39 >
400763:
         callq
                400580 < stack chk fail@plt>
400768:
         add
                 $0x18,%rsp
40076c:
         retq
```

## **Setting Up Canary**

#### Before call to gets

Stack Frame for call\_echo

**Return Address** (8 bytes)

> Canary (8 bytes)

[3][2][1][0] buf - %rsp

```
/* Echo Line */
void echo()
    char buf[4]; /* Way too small! */
    gets(buf);
    puts(buf);
```

```
echo:
           %fs:40, %rax # Get canary
   movq
   movq %rax, 8(%rsp) # Place on stack
   xorl %eax, %eax # Erase canary
```

# **Checking Canary**

After call to gets

```
Stack Frame for main

Return Address (8 bytes)

Canary (8 bytes)

00 36 35 34

33 32 31 30
```

```
/* Echo Line */
void echo()
{
    char buf[4]; /* Way too small! */
    gets(buf);
    puts(buf);
}
```

Input: 0123456

buf ← %rsp

```
echo:

movq 8(%rsp), %rax # Retrieve from stack xorq %fs:40, %rax # Compare to canary je .L6 # If same, OK call __stack_chk_fail # FAIL
```

## **Break Time!**

**argle-bargle**: "copious but meaningless talk or writing"

Check out:

https://canvas.cmu.edu/courses/3822

# **Return-Oriented Programming Attacks**

## Challenge (for hackers)

- Stack randomization makes it hard to predict buffer location
- Marking stack nonexecutable makes it hard to insert binary code

## Alternative Strategy

- Use existing code
  - E.g., library code from stdlib
- String together fragments to achieve overall desired outcome
- Does not overcome stack canaries

## Construct program from gadgets

- Sequence of instructions ending in ret
  - Encoded by single byte 0xc3
- Code positions fixed from run to run
- Code is executable


## **Gadget Example #1**

```
long ab_plus_c
  (long a, long b, long c)
{
   return a*b + c;
}
```

Use tail end of existing functions


## **Gadget Example #2**

```
void setval(unsigned *p) {
    *p = 3347663060u;
}
```




Repurpose byte codes

## **ROP Execution**



- Trigger with ret instruction
  - Will start executing Gadget 1
- Final ret in each gadget will start next one

# **Crafting an ROB Attack String**



#### **Attack String (Hex)**

```
30 31 32 33 34 35 36 37 38 39 30 31 32 33 34 35 36 37 38 39 30 31 32 33 d4 04 40 00 00 00 00
```

Multiple gadgets will corrupt stack upwards

# **Today**


- Memory Layout
- Buffer Overflow
  - Vulnerability
  - Protection
- Unions


### **Union Allocation**

- Allocate according to largest element
- Can only use one field at a time

```
union U1 {
  char c;
  int i[2];
  double v;
} *up;
```

```
struct S1 {
  char c;
  int i[2];
  double v;
} *sp;
```





### **Using Union to Access Bit Patterns**

```
typedef union {
  float f;
  unsigned u;
} bit_float_t;
```

```
u
f
) 4
```

```
float bit2float(unsigned u)
{
  bit_float_t arg;
  arg.u = u;
  return arg.f;
}
```

```
unsigned float2bit(float f)
{
  bit_float_t arg;
  arg.f = f;
  return arg.u;
}
```

Same as (float) u?

Same as (unsigned) f?

## **Byte Ordering Revisited**

#### Idea

- Short/long/quad words stored in memory as 2/4/8 consecutive bytes
- Which byte is most (least) significant?
- Can cause problems when exchanging binary data between machines

### ■ Big Endian

- Most significant byte has lowest address
- Sparc, Internet

#### Little Endian

- Least significant byte has lowest address
- Intel x86, ARM Android and IOS

#### Bi Endian

- Can be configured either way
- ARM

### **Byte Ordering Example**

```
union {
   unsigned char c[8];
   unsigned short s[4];
   unsigned int i[2];
   unsigned long l[1];
} dw;
```

How are the bytes inside short/int/long stored?

Memory addresses growing ———

#### 32-bit

c[0]	c[1]	c[2]	c[3]	c[4]	c[5]	c[6]	c[7]	
<b>s</b> [0]		s[1]		s[2]		s[3]		
i[0]				i[1]				
1[0]								

### 64-bit


c[0]	c[1]	c[2]	c[3]	c[4]	c[5]	c[6]	c[7]			
<b>s</b> [0]		s[1]		s[2]		s[3]				
i[0]				i[1]						
1[0]										

### Byte Ordering Example (Cont).

```
int j;
for (j = 0; j < 8; j++)
   dw.c[i] = 0xf0 + i;
printf("Characters 0-7 ==
dw.c[0], dw.c[1], dw.c[2], dw.c[3],
   dw.c[4], dw.c[5], dw.c[6], dw.c[7]);
printf("Shorts 0-3 == [0x%x,0x%x,0x%x,0x%x]\n",
   dw.s[0], dw.s[1], dw.s[2], dw.s[3]);
printf("Ints 0-1 == [0x%x, 0x%x]\n",
   dw.i[0], dw.i[1]);
printf("Long 0 == [0x%lx]\n",
   dw.1[0]);
```

## **Byte Ordering on IA32**

#### **Little Endian**




#### Output:

```
Characters 0-7 == [0xf0,0xf1,0xf2,0xf3,0xf4,0xf5,0xf6,0xf7]
Shorts 0-3 == [0xf1f0,0xf3f2,0xf5f4,0xf7f6]
Ints 0-1 == [0xf3f2f1f0,0xf7f6f5f4]
Long 0 == [0xf3f2f1f0]
```

## **Byte Ordering on Sun**

### **Big Endian**




MSB LSB MSB LS

#### **Output on Sun:**

```
Characters 0-7 == [0xf0,0xf1,0xf2,0xf3,0xf4,0xf5,0xf6,0xf7]
Shorts 0-3 == [0xf0f1,0xf2f3,0xf4f5,0xf6f7]
Ints 0-1 == [0xf0f1f2f3,0xf4f5f6f7]
Long 0 == [0xf0f1f2f3]
```

### Byte Ordering on x86-64

#### **Little Endian**



#### Output on x86-64:

```
Characters 0-7 == [0xf0,0xf1,0xf2,0xf3,0xf4,0xf5,0xf6,0xf7]
Shorts 0-3 == [0xf1f0,0xf3f2,0xf5f4,0xf7f6]
Ints 0-1 == [0xf3f2f1f0,0xf7f6f5f4]
Long 0 == [0xf7f6f5f4f3f2f1f0]
```

## **Summary of Compound Types in C**

#### Arrays

- Contiguous allocation of memory
- Aligned to satisfy every element's alignment requirement
- Pointer to first element
- No bounds checking

#### Structures

- Allocate bytes in order declared
- Pad in middle and at end to satisfy alignment

#### Unions

- Overlay declarations
- Way to circumvent type system

### **Summary**

- Memory Layout
- Buffer Overflow
  - Vulnerability
  - Protection
  - Code Injection Attack
  - Return Oriented Programming
- Unions

### **Exploits Based on Buffer Overflows**

- Buffer overflow bugs can allow remote machines to execute arbitrary code on victim machines
- Distressingly common in real programs
  - Programmers keep making the same mistakes < </p>
  - Recent measures make these attacks much more difficult
- Examples across the decades
  - Original "Internet worm" (1988)
  - "IM wars" (1999)
  - Twilight hack on Wii (2000s)
  - ... and many, many more
- You will learn some of the tricks in attacklab
  - Hopefully to convince you to never leave such holes in your programs!!

# Example: the original Internet worm (1988)

### Exploited a few vulnerabilities to spread

- Early versions of the finger server (fingerd) used gets() to read the argument sent by the client:
  - finger droh@cs.cmu.edu
- Worm attacked fingerd server by sending phony argument:
  - finger "exploit-code padding new-returnaddress"
  - exploit code: executed a root shell on the victim machine with a direct TCP connection to the attacker.


### Once on a machine, scanned for other machines to attack

- lacktriangle invaded ~6000 computers in hours (10% of the Internet igotimes )
  - see June 1989 article in Comm. of the ACM
- the young author of the worm was prosecuted...
- and CERT was formed... still homed at CMU

### **Example 2: IM War**

### July, 1999

- Microsoft launches MSN Messenger (instant messaging system).
- Messenger clients can access popular AOL Instant Messaging Service (AIM) servers



## IM War (cont.)

#### August 1999

- Mysteriously, Messenger clients can no longer access AIM servers
- Microsoft and AOL begin the IM war:
  - AOL changes server to disallow Messenger clients
  - Microsoft makes changes to clients to defeat AOL changes
  - At least 13 such skirmishes
- What was really happening?
  - AOL had discovered a buffer overflow bug in their own AIM clients
  - They exploited it to detect and block Microsoft: the exploit code returned a 4-byte signature (the bytes at some location in the AIM client) to server
  - When Microsoft changed code to match signature, AOL changed signature location

Date: Wed, 11 Aug 1999 11:30:57 -0700 (PDT) From: Phil Bucking <philbucking@yahoo.com>

Subject: AOL exploiting buffer overrun bug in their own software!

To: rms@pharlap.com

Mr. Smith,

I am writing you because I have discovered something that I think you might find interesting because you are an Internet security expert with experience in this area. I have also tried to contact AOL but received no response.

I am a developer who has been working on a revolutionary new instant messaging client that should be released later this year.

. . .

It appears that the AIM client has a buffer overrun bug. By itself this might not be the end of the world, as MS surely has had its share. But AOL is now \*exploiting their own buffer overrun bug\* to help in its efforts to block MS Instant Messenger.

. . . .

Since you have significant credibility with the press I hope that you can use this information to help inform people that behind AOL's friendly exterior they are nefariously compromising peoples' security.

Sincerely,
Phil Bucking
Founder, Bucking Consulting
philbucking@yahoo.com

It was later determined that this email originated from within Microsoft!

### **Aside: Worms and Viruses**

- Worm: A program that
  - Can run by itself
  - Can propagate a fully working version of itself to other computers
- Virus: Code that
  - Adds itself to other programs
  - Does not run independently
- Both are (usually) designed to spread among computers and to wreak havoc