



Dynamic Memory Allocation: Basic Concepts

18-213/18-613:
Introduction to Computer Systems
12th Lecture, October 6th, 2021

Understanding this Error


■ What causes this error? Why does it matter?

```
$ ./mm-corrupt
*** Error in `./mm-corrupt': free(): invalid next size (fast):
0x000000000ffe010 ***
===== Backtrace: =====
/lib/x86_64-linux-gnu/libc.so.6(+0x777f5) [0x7f043efe67f5]
/lib/x86_64-linux-gnu/libc.so.6(+0x8038a) [0x7f043efef38a]
/lib/x86_64-linux-gnu/libc.so.6(cfree+0x4c) [0x7f043eff358c]
./mm-corrupt[0x400795]
/lib/x86_64-linux-gnu/libc.so.6(__libc_start_main+0xf0) [0x7f043ef8f840]
./mm-corrupt[0x400629]
===== Memory map: =====
...
```


Today

- **Basic concepts**
- **Implicit free lists**

Dynamic Memory Allocation



- Programmers use ***dynamic memory allocators*** (such as `malloc`) to acquire virtual memory (VM) at run time.
 - for data structures whose size is only known at runtime
- Dynamic memory allocators manage an area of process VM known as the ***heap***.



Dynamic Memory Allocation

- Allocator maintains heap as collection of variable sized *blocks*, which are either *allocated* or *free*
- Types of allocators
 - *Explicit allocator*: application allocates and frees space
 - E.g., `malloc` and `free` in C
 - *Implicit allocator*: application allocates, but does not free space
 - E.g., `new` and garbage collection in Java
- Will discuss simple explicit memory allocation today

The `malloc` Package

```
#include <stdlib.h>

void *malloc(size_t size)
```

- Successful:
 - Returns a pointer to a memory block of at least `size` bytes aligned to a 16-byte boundary (on x86-64)
 - If `size == 0`, returns NULL
- Unsuccessful: returns NULL (0) and sets `errno` to ENOMEM

```
void free(void *p)
```

- Returns the block pointed at by `p` to pool of available memory
- `p` must come from a previous call to `malloc`, `calloc`, or `realloc`

Other functions

- `calloc`: Version of `malloc` that initializes allocated block to zero.
- `realloc`: Changes the size of a previously allocated block.
- `sbrk`: Used internally by allocators to grow or shrink the heap

malloc Example

```
#include <stdio.h>
#include <stdlib.h>

void foo(long n) {
    long i, *p;

    /* Allocate a block of n longs */
    p = (long *) malloc(n * sizeof(long));
    if (p == NULL) {
        perror("malloc");
        exit(0);
    }

    /* Initialize allocated block */
    for (i=0; i<n; i++)
        p[i] = i;
    /* Do something with p */
    . . .
    /* Return allocated block to the heap */
    free(p);
}
```

Sample Implementation

■ Code


- File `mm-reference.c`
- Manages fixed size heap
- Functions `mm_malloc`, `mm_free`

■ Features

- Based on *words* of 8-bytes each
- Pointers returned by malloc are double-word aligned
 - Double word = 2 words
- Compile and run tests with command interpreter

Visualization Conventions


- Show 8-byte words as squares
- Allocations are double-word aligned.




Allocation Example (Conceptual)

```
#define SIZ sizeof(size_t)
```


```
p1 = malloc(4*SIZ)
```



```
p2 = malloc(5*SIZ)
```



```
p3 = malloc(6*SIZ)
```



```
free(p2)
```



```
p4 = malloc(2*SIZ)
```



Constraints

■ Applications

- Can issue arbitrary sequence of `malloc` and `free` requests
- `free` request must be to a `malloc`'d block

■ Explicit Allocators

- Can't control number or size of allocated blocks
- Must respond immediately to `malloc` requests
 - *i.e.*, can't reorder or buffer requests
- Must allocate blocks from free memory
 - *i.e.*, can only place allocated blocks in free memory
- Must align blocks so they satisfy all alignment requirements
 - 16-byte (x86-64) alignment on 64-bit systems
- Can manipulate and modify only free memory
- Can't move the allocated blocks once they are `malloc`'d
 - *i.e.*, compaction is not allowed. *Why not?*

Performance Goal: Throughput

- Given some sequence of `malloc` and `free` requests:
 - $R_0, R_1, \dots, R_k, \dots, R_{n-1}$
- Goals: maximize throughput and peak memory utilization
 - These goals are often conflicting
- Throughput:
 - Number of completed requests per unit time
 - Example:
 - 5,000 `malloc` calls and 5,000 `free` calls in 10 seconds
 - Throughput is 1,000 operations/second

Performance Goal: Minimize Overhead

- Given some sequence of `malloc` and `free` requests:
 - $R_0, R_1, \dots, R_k, \dots, R_{n-1}$
- **Def:** *Aggregate payload* P_k
 - `malloc(p)` results in a block with a *payload* of p bytes
 - After request R_k has completed, the *aggregate payload* P_k is the sum of currently allocated payloads
- **Def:** *Current heap size* H_k
 - Assume H_k is monotonically nondecreasing
 - i.e., heap only grows when allocator uses `sbrk`
- **Def:** *Overhead after $k+1$ requests*
 - Fraction of heap space *NOT* used for program data
 - $O_k = H_k / (\max_{i \leq k} P_i) - 1.0$

Benchmark Example

■ Benchmark


syn-array-short

- Trace provided with malloc lab
- Allocate & free 10 blocks
- a = allocate
- f = free
- Bias toward allocate at beginning & free at end
- Blocks numbered 0–9
- Allocated: Sum of all allocated amounts
- Peak: Max so far of Allocated

Step	Command	Delta	Allocated	Peak
1	a 0 9904	9904	9904	9904
2	a 1 50084	50084	59988	59988
3	a 2 20	20	60008	60008
4	a 3 16784	16784	76792	76792
5	f 3	-16784	60008	76792
6	a 4 840	840	60848	76792
7	a 5 3244	3244	64092	76792
8	f 0	-9904	54188	76792
9	a 6 2012	2012	56200	76792
10	f 2	-20	56180	76792
11	a 7 33856	33856	90036	90036
12	f 1	-50084	39952	90036
13	a 8 136	136	40088	90036
14	f 7	-33856	6232	90036
15	f 6	-2012	4220	90036
16	a 9 20	20	4240	90036
17	f 4	-840	3400	90036
18	f 8	-136	3264	90036
19	f 5	-3244	20	90036
20	f 9	-20	0	90036


Benchmark Visualization

Step	Command	Delta	Allocated	Peak
1	a 0 9904	9904	9904	9904
2	a 1 50084	50084	59988	59988
3	a 2 20	20	60008	60008
4	a 3 16784	16784	76792	76792
5	f 3	-16784	60008	76792
6	a 4 840	840	60848	76792
7	a 5 3244	3244	64092	76792
8	f 0	-9904	54188	76792
9	a 6 2012	2012	56200	76792
10	f 2	-20	56180	76792
11	a 7 33856	33856	90036	90036
12	f 1	-50084	39952	90036
13	a 8 136	136	40088	90036
14	f 7	-33856	6232	90036
15	f 6	-2012	4220	90036
16	a 9 20	20	4240	90036
17	f 4	-840	3400	90036
18	f 8	-136	3264	90036
19	f 5	-3244	20	90036
20	f 9	-20	0	90036



- Data line shows total allocated data (P_i)
- Data Fit line shows peak of total ($\max_{i \leq k} P_i$)
- Normalized in X & Y

Full Benchmark Behavior




- Given sequence of mallocs & frees (40,000 blocks)
 - Starts with all mallocs, and shifts toward all frees
- Manage space for all allocated blocks
- Metrics
 - Data: P_i
 - Data fit: $\max_{i \leq k} P_i$

Fragmentation

- Poor memory utilization caused by *fragmentation*
 - *internal* fragmentation
 - *external* fragmentation


Internal Fragmentation

- For a given block, *internal fragmentation* occurs if payload is smaller than block size



- Caused by
 - Overhead of maintaining heap data structures
 - Padding for alignment purposes
 - Explicit policy decisions
(e.g., to return a big block to satisfy a small request)
- Depends only on the pattern of *previous* requests
 - Thus, easy to measure

Internal Fragmentation Effect




- **Perfect Fit: Only requires space for allocated data, data structures, and unused space due to alignment constraints**
 - For this benchmark, 1.5% overhead
 - Cannot achieve in practice
 - Especially since cannot move allocated blocks

External Fragmentation


```
#define SIZ sizeof(size_t)
```

- Occurs when there is enough aggregate heap memory, but no single free block is large enough


```
p1 = malloc(4*SIZ)
```



```
p2 = malloc(5*SIZ)
```



```
p3 = malloc(6*SIZ)
```



```
free(p2)
```




```
p4 = malloc(7*SIZ)
```

Yikes! (what would happen now?)

- Amount of external fragmentation depends on the pattern of future requests
 - Thus, difficult to measure

External Fragmentation Effect



■ Best Fit: One allocation strategy

- (To be discussed later)
- Total overhead = 8.3% on this benchmark


Implementation Issues

- **How do we know how much memory to free given just a pointer?**
- **How do we keep track of the free blocks?**
- **What do we do with the extra space when allocating a structure that is smaller than the free block it is placed in?**
- **How do we pick a block to use for allocation -- many might fit?**
- **How do we reuse a block that has been freed?**

Knowing How Much to Free


■ Standard method

- Keep the length (in bytes) of a block in the word *preceding* the block.
 - Including the header
 - This word is often called the **header field** or **header**
- Requires an extra word for every allocated block




Keeping Track of Free Blocks

- Method 1: *Implicit list* using length—links all blocks



Need to tag each block as allocated/free

- Method 2: *Explicit list* among the free blocks using pointers



Need space for pointers

- Method 3: *Segregated free list*

- Different free lists for different size classes

- Method 4: *Blocks sorted by size*

- Can use a balanced tree (e.g. Red-Black tree) with pointers within each free block, and the length used as a key


Today

- Basic concepts
- Implicit free lists

Method 1: Implicit Free List

- For each block we need both size and allocation status
 - Could store this information in two words: wasteful!
- Standard trick
 - When blocks are aligned, some low-order address bits are always 0
 - Instead of storing an always-0 bit, use it as an allocated/free flag
 - When reading the Size word, must mask out this bit

*Format of
allocated and
free blocks*




a = 1: Allocated block
a = 0: Free block

Size: total block size

**Payload: application data
(allocated blocks only)**

Detailed Implicit Free List Example



Double-word
aligned

Allocated blocks: shaded
Free blocks: unshaded
Headers: labeled with “size in words/allocated bit”
Headers are at non-aligned positions
➔ Payloads are aligned

Implicit List: Data Structures



■ Block declaration

```
typedef uint64_t word_t;

typedef struct block
{
    word_t header;
    unsigned char payload[0];           // Zero length array
} block_t;
```

■ Getting payload from block pointer // block_t *block

```
return (void *) (block->payload);
```

■ Getting header from payload // bp points to a payload

```
return (block_t *) ((unsigned char *) bp
                    - offsetof(block_t, payload));
```

C function `offsetof(struct, member)` returns offset of member within struct

Implicit List: Header access

Size	a
------	---

- Getting allocated bit from header

```
return header & 0x1;
```

- Getting size from header

```
return header & ~0xfL;
```

- Initializing header

// block_t *block


```
block->header = size | alloc;
```

Implicit List: Traversing list



■ Find next block

```
static block_t *find_next(block_t *block)
{
    return (block_t *) ((unsigned char *) block
                        + get_size(block));
}
```




Implicit List: Finding a Free Block

■ *First fit:*

- Search list from beginning, choose *first* free block that fits:
- Finding space for **asize** bytes (including header):

```
static block_t *find_fit(size_t asize)
{
    block_t *block;
    for (block = heap_start; block != heap_end;
         block = find_next(block)) {
        if (!get_alloc(block)
            && (asize <= get_size(block)))
            return block;
    }
    return NULL; // No fit found
}
```



Implicit List: Finding a Free Block

■ *First fit:*

- Search list from beginning, choose *first* free block that fits:
- Can take linear time in total number of blocks (allocated and free)
- In practice it can cause “splinters” at beginning of list


■ *Next fit:*

- Like first fit, but search list starting where previous search finished
- Should often be faster than first fit: avoids re-scanning unhelpful blocks
- Some research suggests that fragmentation is worse

■ *Best fit:*

- Search the list, choose the *best* free block: fits, with fewest bytes left over
- Keeps fragments small—usually improves memory utilization
- Will typically run slower than first fit
- Still a greedy algorithm. No guarantee of optimality

Comparing Strategies




■ Total Overheads (for this benchmark)

- Perfect Fit: 1.6%
- Best Fit: 8.3%
- First Fit: 11.9%
- Next Fit: 21.6%


Implicit List: Allocating in Free Block

■ Allocating in a free block: *splitting*

- Since allocated space might be smaller than free space, we might want to split the block





split_block(p, 32)



Implicit List: Splitting Free Block

```
split_block(p, 32)
```



```
// Warning: This code is incomplete


static void split_block(block_t *block, size_t asize) {
    size_t block_size = get_size(block);

    if ((block_size - asize) >= min_block_size) {
        write_header(block, asize, true);
        block_t *block_next = find_next(block);
        write_header(block_next, block_size - asize, false);
    }
}
```

Implicit List: Freeing a Block

■ Simplest implementation:

- Need only clear the “allocated” flag
- But can lead to “false fragmentation”




`malloc(5*SIZ)` *Yikes!*

There is enough contiguous free space, but the allocator won't be able to find it

Implicit List: Coalescing


- Join (*coalesce*) with next/previous blocks, if they are free
 - Coalescing with next block



Implicit List: Coalescing

■ Join (*coalesce*) with next block, if it is free

- Coalescing with next block




- How do we coalesce with *previous* block?
 - How do we know where it starts?
 - How can we determine whether its allocated?


Implicit List: Bidirectional Coalescing

■ **Boundary tags** [Knuth73]

- Replicate size/allocated word at “bottom” (end) of free blocks
- Allows us to traverse the “list” backwards, but requires extra space
- Important and general technique!



*Format of
allocated and
free blocks*



$a = 1$: Allocated block
 $a = 0$: Free block

Size: Total block size


Payload: Application data
(allocated blocks only)

Quiz Time!

Check out:

Canvas > Day 12 – Malloc Basics

Implementation with Footers




■ Locating footer of current block

```
const size_t dsize = 2*sizeof(word_t);

static word_t *header_to_footer(block_t *block)
{
    size_t asize = get_size(block);
    return (word_t *) (block->payload + asize - dsize);
}
```

Implementation with Footers





■ Locating footer of previous block

```
static word_t *find_prev_footer(block_t *block)
{
    return &(block->header) - 1;
}
```

Splitting Free Block: Full Version


split_block(p, 32)




```
static void split_block(block_t *block, size_t asize) {
    size_t block_size = get_size(block);

    if ((block_size - asize) >= min_block_size) {
        write_header(block, asize, true);
        write_footer(block, asize, true);
        block_t *block_next = find_next(block);
        write_header(block_next, block_size - asize, false);
        write_footer(block_next, block_size - asize, false);
    }
}
```


Constant Time Coalescing




Constant Time Coalescing (Case 1)




Constant Time Coalescing (Case 2)




Constant Time Coalescing (Case 3)



Constant Time Coalescing (Case 4)



Heap Structure



■ Dummy footer before first header

- Marked as allocated
- Prevents accidental coalescing when freeing first block

■ Dummy header after last footer

- Prevents accidental coalescing when freeing final block

Top-Level Malloc Code

```
const size_t dsize = 2*sizeof(word_t);

void *mm_malloc(size_t size)
{
    size_t asize = round_up(size + dsize, dsize);
    block_t *block = find_fit(asize);

    if (block == NULL)
        return NULL;

    size_t block_size = get_size(block);
    write_header(block, block_size, true);
    write_footer(block, block_size, true);

    split_block(block, asize);

    return header_to_payload(block);
}
```

round_up(n, m)
=
m * ((n+m-1)/m)

Top-Level Free Code

```
void mm_free(void *bp)
{
    block_t *block = payload_to_header(bp);
    size_t size = get_size(block);

    write_header(block, size, false);
    write_footer(block, size, false);


    coalesce_block(block);
}
```

Disadvantages of Boundary Tags

- Internal fragmentation


- Can it be optimized?

- Which blocks need the footer tag?
- What does that mean?



No Boundary Tag for Allocated Blocks


- Boundary tag needed only for free blocks
- When sizes are multiples of 16, have 4 spare bits



Allocated
Block


a = 1: Allocated block
a = 0: Free block
b = 1: Previous block is allocated
b = 0: Previous block is free

Size: block size
Payload: application data




Free
Block

No Boundary Tag for Allocated Blocks (Case 1)




Header: Use 2 bits (address bits always zero due to alignment):
(previous block allocated) << 1 | (current block allocated)

No Boundary Tag for Allocated Blocks (Case 2)




Header: Use 2 bits (address bits always zero due to alignment):
(previous block allocated) << 1 | (current block allocated)

No Boundary Tag for Allocated Blocks (Case 3)



Header: Use 2 bits (address bits always zero due to alignment):
(previous block allocated) << 1 | (current block allocated)

No Boundary Tag for Allocated Blocks (Case 4)



Header: Use 2 bits (address bits always zero due to alignment):
(previous block allocated) << 1 | (current block allocated)

Summary of Key Allocator Policies

■ Placement policy:

- First-fit, next-fit, best-fit, etc.
- Trades off lower throughput for less fragmentation
- ***Interesting observation:*** segregated free lists (next lecture) approximate a best fit placement policy without having to search entire free list

■ Splitting policy:

- When do we go ahead and split free blocks?
- How much internal fragmentation are we willing to tolerate?

■ Coalescing policy:

- ***Immediate coalescing:*** coalesce each time `free` is called
- ***Deferred coalescing:*** try to improve performance of `free` by deferring coalescing until needed.

Implicit Lists: Summary

- **Implementation: very simple**
- **Allocate cost:**
 - linear time worst case
- **Free cost:**
 - constant time worst case
 - even with coalescing
- **Memory Overhead**
 - will depend on placement policy
 - First-fit, next-fit or best-fit
- **Not used in practice for `malloc/free` because of linear-time allocation**
 - used in many special purpose applications
- **However, the concepts of splitting and boundary tag coalescing are general to *all* allocators**