Appendix D: Standard Object IDs and Global Names

This entire appendix is new.

Standard Objects

Note that these can also be properties or types, since they are denoted by objects.

`CM_StdObjID_TOC` 1
TOC object ID (object)

`CM_StdObjID_TOC_Seed` 2
TOC object starting seed (property)

`CM_StdObjID_TOC_MinSeed` 3
TOC object minimum seed (property)

`CM_StdObjID_TOC_Object` 4
TOC object (property)

`CM_StdObjID_TOC_Container` 5
TOC object—entire container (property)

`CM_StdObjID_TOC_Deleted` 6
TOC object amount deleted (property)

`CM_StdObjID_TOC_Free` 7
TOC object—free space (property)

`CM_StdObjID_TOC_NewValuesTOC` 8
TOC object new values TOC (property)

`CM_StdObjID_TOC_Target` 9
TOC object—target container ref. (property)

`CM_StdObjID_TOC_DeleteList` 10
TOC object delete update list (property)

`CM_StdObjID_TOC_Type` 19
TOC object property value type (type)

`CM_StdObjID_7BitASCII` 21
7-bit ASCII (type)

`CM_StdObjID_8BitASCII` 22
8-bit ASCII (type)

`CM_StdObjID_GlobalTypeName` 23
Global type name (property)

`CM_StdObjID_GlobalPropName` 24
Global property name (property)

 Copyright 1993 Apple Computer

`CM_StdObjID_DynamicValues` 25
Dynamic values (property)

`CM_StdObjID_BaseTypes` 26
Base types (property)

`CM_StdObjID_BaseTypeList` 27
Base type list (type)

`CM_StdObjID_TargetContainer` 28
Target container (type)

`CM_StdObjID_ValueUpdates` 29
Value updates for object (property)

`CM_StdObjID_UpdatesData` 30
Internal updating instruction data (type)

`CM_StdObjID_ObjReferences` 31
Referenced objects from an object (property)

`CM_StdObjID_ObjRefData` 32
Reference data (type)

`CM_StdObjID_32BitImmValue` 40
32-bit immediate data value (type)

`CM_StdObjID_16BitImmValue` 41
16-bit immediate data value (type)

`CM_StdObjID_8BitImmValue` 42
8-bit immediate data value (type)

Global Names

`CMTOCSeedGlobalName`
Apple:Global_Name_TOC_Seed (property)

`CMTOCMinSeedGlobalName`
Apple:Global_Name_TOC_MinSeed (property)

`CMTOCObjectGlobalName`
Apple:Global_Name_TOC_Object (property)

`CMTOCContainerGlobalName`
Apple:Global_Name_TOC_Container (property)

`CMTOCDeletedGlobalName`
Apple:Global_Name_TOC_Deleted (property)

`CMTOCTotalFreeGlobalName`
Apple:Global_Name_TOC_Free (property)

 Copyright 1993 Apple Computer

`CMTOCNewValuesTOCGlobalName`
Apple:Global_Name_TOC_NewValuesTOC (property)

`CMTOCTargetGlobalName`
Apple:Global_Name_TOC_Target (property)

`CMTOCDeleteListGlobalName`
Apple:Global_Name_TOC_DeleteList (property)

`CMTOCValueTypeGlobalName`
Apple:Global_Name_TOC_Type (type)

`CMDynamicValueGlobalName`
Apple:Dynamic_Value (property)

`CMBaseTypesGlobalName`
Apple:Type_BaseType (property)

`CMBaseTypeListGlobalName`
Apple:Type_BaseTypeList (type)

`CMTargetContainerName`
Apple:Target_Container (type)

`CMValueUpdatesGlobalName`
Apple:Type_ValueUpdates (property)

`CMUpdatesDataGlobalName`
Apple:Type_UpdatesData (type)

"

 Copyright 1993 Apple Computer

 Copyright 1993 Apple Computer