

# 15110 PRINCIPLES OF COMPUTING – EXAM 1A – FALL 2012

Name \_\_\_\_\_ Section \_\_\_\_\_

Andrew id \_\_\_\_\_

*Directions: Answer each question neatly in the space provided.  
Please read each question carefully. You have 50 minutes for  
this exam. No electronic devices allowed. Good luck!*

1	_____
2	_____
3	_____
4	_____
5	_____
6	_____
TOTAL	_____

1.(14 pts total) History of computation

(a) (4 pts) Match each item in the left column with the most relevant item in the right column.

*not covered in spring '13*

Jacquard's loom

ENIAC

Moore's Law

Difference Engine

Harvard Mark I

Grace Hopper

Ada Lovelace

Alan Turing

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

1. Electromechanical computer

2. Enigma cipher

3. Polynomial function

4. Vacuum tubes

5. First programmer

6. Hollerith tabulating machine

7. Exponential function

8. Debugging

(b) (6 pts) We want to use the method of finite differences to create a table of numbers for the function  $f(x) = 5x^2 - 4x + 3$ . Compute the necessary difference functions and the initial values for  $x = 0$  for this machine. Then fill in the table for  $x$  values from 1 to 3.

$$\Delta f(x) = \text{_____} x + \text{_____}$$

$$\Delta^2 f(x) = \text{_____}$$

x	$\Delta^2 f(x)$	$\Delta f(x)$	f(x)
0			
1			
2			
3			

(c) (2 pts) A byte is \_\_\_\_\_ bits, so a kilobyte is \_\_\_\_\_ bits.

(d) (2 pts) Moore's Law says that the \_\_\_\_\_ of integrated circuit chips \_\_\_\_\_ every 18 months.

2. This problem focuses on expressions and data types.


(a) (6 pts) For each of the following Ruby expression, write down the value that would be output if the expression was evaluated in irb.

40 / 9	_____	15.0 / 2	_____
2 * 2 ** 4	_____	15 % 2	_____
6 + 4 * 2 - 1	_____	2 != 2	_____

(b) (2 pts) Write a Ruby function `triangle_area` that takes two parameters `h` and `b`, respectively, for the height and base of a triangle, and returns the area of the triangle given by the formula

$$A = \frac{1}{2} (\text{height} \times \text{base}).$$

(c) (2 pts) Write a Ruby function `truncated_triangle` that takes height and base parameters (h and b) as input, and computes the area of a triangle that the tip cut off. The tip is also a triangle; its height and base are 10% of the height and base, respectively, of the larger triangle, as shown in the figure. Use the `triangle_area` function in your solution.



(d) (2 pts)

```
def mystery1(m, n)
  i = 0
  while i <= n-1 do
    i = i + 1
    print i ** m, " "
  end
end
```

The Ruby function above prints a sequence of numbers. Which of the following is the output of the function expressed in terms of m and n? Circle your answer.

1    $2^m$     $3^m$  ...  $n^m$

OR

1    $m^2$     $m^3$  ...  $m^n$

(e) (4 pts) If the print statement was taken outside of the while loop to occur right after the while statement, as shown below, what would the function call `mystery2(2, 3)` print?

```
def mystery2(m, n)
  i = 0
  while i <= (n-1) do
    i = i + 1
  end
  print i ** m, " "
end
```

---

(f) (4 pts) Consider the following Ruby function:

```
def mystery3(m, n)
  i = 0
  result = 0
  while i <= (n-1) do
    i = i + 1
    result = result + i ** m
  end
  return result
end
```

What would the value of the variable x be after executing the following assignment statement below?

```
x = mystery3(2, 4)
```

\_\_\_\_\_

(3) (20 pts total) This question focuses on the array data type and iterators.

(a) (6 pts) Assume the following list definition in Ruby using an array.

```
cars = ["Honda", "Toyota", "Kia", "Chrysler", "Mercedes"]
```

What would be displayed in `irb` for each of the following Ruby expressions?

<code>cars.length</code>	_____
<code>cars.first</code>	_____
<code>cars[1]</code>	_____
<code>cars.include?("Mazda")</code>	_____
<code>cars.include?("KIA")</code>	_____
<code>cars.each {  x  print x + "*" if x &gt; "Kia" }</code>	_____

↓  
this iterator not covered in class by week 4  
but you ~~can~~ can learn about it  
in Section 3.4 of EC.

(b) (4 pts) Assume the following list definition in Ruby using an array.

`a = [1, 2, [3, 4, 5], 6]`

What would be displayed in irb for each of the following Ruby expressions?

`a.length` \_\_\_\_\_

`a.first` \_\_\_\_\_

`a[2]` \_\_\_\_\_

`a + a` \_\_\_\_\_

*not covered in class as of week 4*

(c) (10 pts) Assume the following list definition in Ruby using an array.

`a = [2, 4, 6, 7, 8]`

What would be returned in irb for if the following Ruby expressions are executed in the given order?

`a.collect{ |x| x / 2 }` \_\_\_\_\_

`a` \_\_\_\_\_

`a.select{ |x| x.even? }` \_\_\_\_\_

`a.delete_if{ |x| x % 3 == 0 }` \_\_\_\_\_

**Hint: delete\_if is a destructive method in Ruby.**

`a` \_\_\_\_\_

*not covered as of week 4*

4. (20 pts total) This question focuses on looping.

(a) (8 pts) We wish to define a Ruby function `out_of_order` that takes an “almost sorted” list as input and returns the first item that is not in ascending order. The function should return `nil` if the list is entirely in ascending order. For example, `out_of_order([1, 5, 17, 12, 24])` should return 12, since 12 is less than the preceding item, 17. Complete the following iterative function `out_of_order`.

```
def out_of_order(list)
  index = _____
  while index < _____
    if _____ > _____ then
      return _____
    end
    index = _____
  end
  return _____
end
```

(b) (8 pts) Consider the following recursive algorithm for returning the first item in a list that is not in ascending order, else `nil`. Complete the recursive definition of `out_of_order`.

1. If the list has fewer than two elements, return `nil`.
2. If the first element in the list is greater than the second element, return the first element.
3. Otherwise return the result of a recursive call on the tail of the list (i.e., everything beyond the first element.)

```
def out_of_order(list)
  if _____ < 2 then
    return _____
  elsif _____ > _____ then
    return _____
  else
    return _____
  end
end
```

(c) (2 pts) Give an example of a six element list that would be a worst case input for `out_of_order`.

\_\_\_\_\_

(d) (2 pts) What is the big O worst case complexity of `out_of_order`?

\_\_\_\_\_

5. (20 pts) This question deals with searching and sorting.

(a) (2 pts)

What is the big O complexity of binary search? \_\_\_\_\_

What is the big O complexity of insertion sort? \_\_\_\_\_

(b) (6 pts) Fill in the table below to show how binary search would locate the value "e" in the list ["a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k"]. Use the binary search algorithm taught in the book and covered in lecture. Note: this table may contain extra rows.

Iteration	Low	High	Mid	list[mid]
1	-1	11	5	f



(c) (6 pts) For each sorting algorithm described below, give its correct name:

- For each input item, find its proper position in the result list and add it at that position.

\_\_\_\_\_

- For each position  $i$  in the list, find the index of the smallest item at or to the right of position  $i$ , and swap `list[i]` with `list[index_of_smallest]`.

\_\_\_\_\_

- Organize the inputs into  $N$  groups of size 1. Systematically combine adjacent groups to form  $N/2$  sorted groups, each of size 2. Repeat the process, combining adjacent groups of size 2 to form  $N/4$  sorted groups of size 4. Keep going until you have one sorted group of size  $N$ .

\_\_\_\_\_

(d) (6 pts) Suppose we want to know if all the elements of a list are the same. For example,

`all_same([1, 1, 1, 99, 1, 1])` should return false, but

`all_same(["f", "f", "f", "f"])` should return true. Here are two solutions. Fill in the missing elements.

```
def all_same1(list)
  sorted_list = list.sort
  if sorted_list[0] == sorted_list[ _____ ] then
    return _____
  else
    return _____
  end
end
```

```
def all_same2(list)
  list.each { |x| return _____ if _____ != list[0] }
  return _____
end
```



What is the big O complexity of all\_same1? \_\_\_\_\_

What is the big O complexity of all\_same2? \_\_\_\_\_

6. (6 pts) This question is based on your readings from the book *Blown to Bits*.

When you print a report using a laser printer, can you assume that no one can tell who printed it? Give a yes/no answer followed by a one sentence explanation.