15–150: Principles of Functional Programming
List Reversal

Michael Erdmann

Spring 2026

This note proves an extensional equivalence for list reversal as discussed in lecture.

SUGGESTION: Read the first page of this note, then try to prove the Theorem. Then look at the second page for a solution. That is a good way to prepare yourself for homework and midterm.

Here is the relevant code:

```
(* rev : int list -> int list
   REQUIRES: true
   ENSURES:  rev(L) evaluates to the list L in reverse order.
*)
fun rev ([] : int list) : int list = []
  | rev (x::xs) = (rev xs) @ [x]

(* trev : int list * int list -> int list
   REQUIRES: true
   ENSURES:  trev(L, acc) ≅ (rev L) @ acc
*)
fun trev([] : int list, acc : int list) : int list = acc
  | trev(x::xs, acc) = trev(xs, x::acc)

(* reverse : int list -> int list
   REQUIRES: true
   ENSURES:  reverse(L) evaluates to the list L in reverse order.
*)
fun reverse(L : int list) : int list = trev(L, [])
```

Theorem: For all values `L` and `acc` of type `int list`, `trev(L, acc)` ≅ `rev(L) @ acc`.

In order to prove the theorem, we will use two lemmas, stated next. The first lemma says that `@` is an associative operator. The second lemma says that appending a list consisting of one element onto a second list reduces to the process of consing that one element onto the second list.

Lemma 1: For all expressions e_1, e_2, e_3 of type `int list`, e_1 `@` (e_2 `@` e_3) ≅ (e_1 `@` e_2) `@` e_3.

Lemma 1 is proved in the structural induction notes accompanying this lecture.

Lemma 2: For all values `x : int` and `acc : int list`, `[x] @ acc` $\Longrightarrow$ `x::acc`.

Exercise: Prove Lemma 2 from the code for `@` given here:

```
fun @ ([] : int list, R : int list) : int list = R
  | @ (x::xs, R) = x :: @(xs, R)
infixr @
```

Proof: By structural induction on `L`.

BASE CASE: `L = []`.

NEED TO SHOW: `trev([], acc)` $\cong$ `rev([]) @ acc` for all values `acc : int list`.

SHOWING: Let us evaluate the left and right sides of this "NEED TO SHOW" separately:

```
    trev([], acc)
==> acc                              [first clause of trev]

    rev([]) @ acc
==> [] @ acc                         [first clause of rev]
==> acc                              [first clause of @]
```

Since both expressions reduce to the same value, they are extensionally equivalent.
That establishes the base case.

INDUCTIVE CASE: `L = x::xs`, for some values `x : int` and `xs : int list`.

INDUCTION HYPOTHESIS:
For all values `acc' : int list`, `trev(xs, acc')` $\cong$ `rev(xs) @ acc'`.
(We wrote `acc'` rather than `acc` merely to distinguish it from the `acc` used below. We emphasize that the quantification in the IH is *for all* accumulator arguments.)

NEED TO SHOW: For all values `acc : int list`, `trev(x::xs, acc)` $\cong$ `rev(x::xs) @ acc`.

SHOWING: We could again evaluate the left and right sides of the "NEED TO SHOW" separately. However, to illustrate a different proof approach, we will use explicit equivalences at each step:

```
   trev(x::xs, acc)
≅  trev(xs, x::acc)                  [second clause of trev]
≅  rev(xs) @ (x::acc)                [IH, with value acc' = x::acc]
≅  rev(xs) @ ([x] @ acc)                                [Lemma 2]
≅  (rev(xs) @ [x]) @ acc                                [Lemma 1]
≅  rev(x::xs) @ acc                  [second clause of rev]
```

That establishes the inductive case.

The base case and the inductive case together establish the Theorem, by a principle of structural induction for `int list`.

Thought Questions:

- Lemma 2 says `[x] @ acc` $\Longrightarrow$ `x::acc`, but above we use `x::acc` $\cong$ `[x] @ acc`. Why is that valid?
- Why is the last step above, which cites the second clause of `rev`, a valid equivalence?