15-410 *"...misbehave(7)..."*

Project 2 Sep. 17, 2008

> Dave Eckhardt Roger Dannenberg

L10b_P2

1

Synchronization

P2 (et seq.) partners

- "Partner Registration Page" on web site
- Almost everybody registered Thanks!
- The remaining folks have e-mail from me

Please make sure you've discussed

- How many late days?
- Project schedule in other classes
 - Write down a joint project schedule
- Auditing or pass/fail? Target 410 grade?
- Prior experience
- Interviews

Outline


What you'll build

- Mutex, condition variable
- Thread library
- Supplemental library routines
- Tests


How the pieces fit together

- A picture is worth 1000 words
- You'll need to read the handouts too
 - (two, each >1000 words)
 - kspec specifies our kernel for P2, your kernel for P3
 - thr_lib –specifies thread library


Mutex & Condition Variable



Remainder of Thread Library




Supplemental Library Routines




Tests (Yours & Ours)


7



Building a "RAM disk" image



Linking "RAM disk" to kernel



Misbehave

misbehave(int mode)

- Special debugging-support system call in our 410 kernel
- Adjusts "behavior" of system
 - Multiple legal behaviors (you will feel this during P3)
 - Each mode selects a particular mix
 - We will not document these
 - We expect you to not "document" them to classmates either
- Debug your thread library with one mode, then the next...
 - A dazzling array of flavors
 - 0...15
 - maybe even more
 - 1
- You will not be required to implement misbehave() in P3

threadinfo

simics> tidinfo 11

REGISTER DUMP FOLLOWS

CS = 0x0000043, EFLAGS = 0x00010246, SS = 0x000004b

EIP = 0x0100004a, ESP = 0xfffffa0, EBP = 0xfffffcc

EDI = 0x00000000, ESI = 0x00000000, EAX = 0x31337000

EBX = 0x00000000, ECX = 0x00000000, EDX = 0x01000c0a

Cool, what is it?

- Debugging information about thread 11
- The last instruction it executed in user space

Why would I want that?

It might help with certain hard problems

Plea – Conceptual

This code is tricky

- Most of you have already written multi-threaded code
 - That can be tricky enough
- Writing the internals is harder
 - Get a part 99% done
 - Discover a "bug"...
 - ...which is really a misconception...
 - Totally new design to fix it

Make sure core parts are solid

Better to skip readers/writers locks if not

Plea – Time

The first 90% will take the first 90% of the time

The last 10% will take the second 90% of the time

"Code complete"

- Plan to spend at least three days debugging based on the tests we release
- If your thread library doesn't pass cyclone and agility_drill it won't pass a bunch of our tests either
 - Resultant grade is unlikely to exceed a C