15-410

"...#ifndef DSFLK_FSFDDS_FSDFDS..."

#include
Feb. 6, 2004

Dave Eckhardt

Bruce Maggs

Synchronization

Register your partner today

Register your partner today

Register your partner today

How is P2 going?

- **Should have read both handout documents by now**
- **Should start thr_create() before Monday**

Outline

#ifndef DSFLK_FSFDDS_FSDFDS

What *should* go here, anyway?

What's _STDIO_H_ anyway?

```
#ifndef _STDIO_H_
#define _STDIO_H_

typedef struct FILE {
   ...
} ...;

#endif /* _STDIO_H_ */
```

Archaeology

C is old

C doesn't have modules

C has *files*

- Compilers sort of know some file types: .c, .s
- Compilers *don't* really know about .h
  - Auxiliary “pre-processor” brain hides them

People use *conventions* to get module-like C

- These conventions evolved slowly

The ".h Responsibility" Dilemma

Assume: "stdio module"

Assume: "network stack module"

- (Trust us, it's modular!)

Both need to know

- What's a `size_t` on this machine, anyway?
- #include <sys/types.h>

Nested Responsibility

Program 1:

- #include <stdio.h>

Program 2:

- #include <netinet/tcp_var.h>

Assume

- Program 1, 2 don't need sys/types.h themselves

Solution 1

- stdio.h and netinet/tcp_var.h each include sys/types.h

Too Much

Program 3:

- #include <stdio.h>
- #include <netinet/tcp_var.h>

Problem

- Now we get *two* copies sys/types.h
- Lots of whining about redefinitions
- Maybe compilation fails

Passing the Buck

Blame the user!

Solution 2

- Require *main program* to #include <sys/types.h>

Problem

- Annoying for user
- Modules' needs *change over time*
  - Didn't you know? Since last night xxx needs yyy...

Solution: Idempotent .h files

.h responsibility

- Activate only once
- No matter how many times included
- **Choose string "unlikely to be used elsewhere"**

```
#ifndef _STDIO_H_
#define _STDIO_H_
...
#endif /* _STDIO_H_ */
```

What *Belongs* In a .h?

Types (C: *declarations*, not *definitions*)

Exported interface routines ("public methods")

Constants (#define or enum)

Macros (when *appropriate*)

Data items exported by module

- **Try to avoid this**
- **Same reason as other languages: data != semantics**

No code!

But What About...?

Real modules have multiple .c files

- Who declares *internal* data structures?
  - (Internally, we agree on semantics)
- Who declares *internal* functions?

Not "the" .h file

- We *don't want* to publish internal details

Maybe a ".i" file?

- Help?

Use the *Other* .h File!

stdio.h

- Included by module clients
- Included by module parts

stdio_private.h

- Included only by module parts
- Ideally, not available to user's prying eyes

***_private.h should be idempotent, too**

Summary

#ifndef DSFLK_FSFDDS_FSDFDS

- Well, use a better string
- Used to make .h files idempotent

What *should* go here, anyway?

- There are two “here”'s here
  - foo.h: public interface, available to public
  - foo_private.h: internal communication, maybe unpublished