

15-410

“Now that we've covered the 1970's...”

Plan 9
Apr. 9, 2008

Dave Eckhardt

Roger Dannenberg

Synchronization

Upcoming lectures

- Friday –Transactions
 - Taught by Jeff Eppinger, an expert
- Next week
 - Special topics, Spring Carnival
- Week of the 21st-25th - Security
- Final week –various wrap-up
 - “Review session” works best if you come with questions

Synchronization

Survey

- How many have installed *nix on a box?
 - Windows?
- How many have *done an in-place upgrade?*
- How many have a personally owned box with multiple users?
 - Done an upgrade?
- What does “PC” stand for?

Today: Plan 9 from Bell Labs

Overview

What style of computing?

- The death of timesharing
- The “Unix workstation problem”

Design principles

Name spaces

File servers

- The TCP file system...

Runtime environment

Evolution (?) of Timesharing

One computer per ...

- City: Multics
- Campus: IBM mainframe
- Department: minicomputer

Benefits

- Sharing, protection easy inside “the community”
 - Easy to add a “user” to access control list (or user group)
- Administration amortized across user base
 - Backups & printers, too...

The Personal Computing Revolution

Consequence of the microprocessor

Get *your own* machine!

No more “disk quota”

***You* decide which software is on the box**

- Upgrade whenever *you* want
 - Mainframe sysadmin's schedule is *always* too (fast xor slow)

Great!

The Rallying Cry

One of the Alto's most attractive features is that it does not run faster at night.

- Butler Lampson?

The Personal Computing *Disaster*

You do your own backups

- Probably not!

You do emergency security upgrades

- Day or night!

Sharing files is hard, risky

- machine:/usr/... (until it retires)

Every machine you use has different software

- If you're lucky, packages are just missing
- If you're unlucky, they're there with subtly wrong versions
 - Or different machines have different fonts –whee!

Hybrid Approach

A form of distributed computing

- Centralize “the right” resources
 - Backed-up, easily-shared file systems
 - Complex (licensed) software packages
 - Version management / bug patches
- Access those resources from a fast local machine

Which OS on the servers?

- Don't care –black boxes

Which OS on the workstation?

Workstation Operating Systems

Unix?

- Good: It's the system you're used to using
- Bad: Administer it yourself
 - `/etc/passwd`, `/etc/group`, anti-relay your sendmail...

Windows

- Your very own copy of VMS!
- Support for organization-wide user directory
- Firm central control over machine
 - “install software” is a privilege
- Access to *services* is tied to *machines*
- Firmly client/server (no distributed execution)

Workstation Operating Systems

Mac OS 9

- Your own ... whatever it was

Mac OS X

- Your own Unix system! (see above)

VM/CMS or MVS!!!

- IBM PC XT/370
- Your own *mainframe!*
 - You and your *whole family* can (must) administer it

The “Network Computer”

Your own display, keyboard, mouse

Log in to a real computer for your real computing

Every keystroke & every mouse click cross the net

- Every font glyph...

Also known as

- Thin client, X terminal, Windows Terminal Services

Once “The Next Big Thing”

- (thud)

The Core Issues

Who defines and administers resources?

- One administrator per ...?
 - Department?
 - Laptop?

What travels across the network?

- X terminal: keystrokes, bitmaps... lots of little things
- AFS: files... as long as your sharing pattern matches

Are legacy OS's right for this job?

The Plan 9 Approach

“Build a UNIX out of little systems”

- ...not “a system out of little Unixes”

Compatibility of essence with Unix

- Not real portability

Take the good things

- Tree-structured file system
- “Everything is a file” model

Toss the rest (ttys, *signals!*)

Design Principles

“Everything is a file”

- Standard *naming system* for all resources: pathnames

“Remote access” is the common case

- Standard *resource access protocol*: “9P”
- Used to access any file-like thing, remote or local

Personal namespaces

- Naming *conventions* keep it sane

A practical issue: Open Source

- Unix source not available at “Bell Labs”, its birthplace!

System Architecture

Reliable machine-room *file servers*

- Plan 9's eternal versioned file system

Shared-memory multiprocessor *cycle servers*

- Located near file servers for fast access

Remote-access workstation *terminals*

- Access your *view* of the environment
- Don't *contain* your environment
- Disk is optional
 - Typically used for faster booting, file cache
- “Root directory” is located on your primary file server

Outline

Namespaces

Unusual file systems

A slightly irregular file system

Run-time environment

Custom Namespaces

/bin/date means *your architecture*'s binary

/dev/cons means *your* terminal

- Per-*window* devices (below)

/mail/fs/mbox/25 is the 25th message in your box

No “links” - “hard” or “soft”

- A link is something *in the file system* which causes everybody to buy into a naming illusion
 - Some illusions cause security holes, as we've seen
- In Plan 9, namespaces are *consensual* illusions
 - List of mount points for partial file systems
 - Stored in process control blocks, not in the file system

The /bin File System

Look, Ma, no \$PATH!

```
% bind /386/bin /bin
```

```
% bind -a /rc/bin /bin
```

```
% bind -a /usr/davide/386/bin /bin
```

/bin is a *union* directory

- Each backing directory searched in order by open(), exec(), ...

/dev/tty vs. /dev/cons

% (process_foo <foo >bar) >&errs

- csh-speak for
 - Run “process_foo”
 - Standard input is “foo”
 - Standard output sent to “bar”
 - Standard error sent to “errs”

“process_foo” is pretty well connected to *files*

- What if it wants to talk *to the user*?

/dev/tty vs. /dev/cons

% (process_foo <foo >bar) >&errs

- **cs**h-speak for
 - Run “process_foo”
 - Standard input is “foo”
 - Standard output sent to “bar”
 - Standard error sent to “errs”

“process_foo” is pretty well connected to *files*

- What if it wants to talk *to the user?*

Unix solution –magic device “/dev/tty”

- Rummages through your process, guesses your terminal
 - See O_NOCTTY flag to open(2), see vhangup(2)-or don't...
- Opens /dev/ttyXX for you, returns that

/dev/tty vs. /dev/cons

% (process_foo <foo >bar) >&errs

What if process_foo wants to talk *to the user*?

Plan 9 –your *namespace* contains /dev/cons

- The right device is *mounted* as /dev/cons
- By whoever runs you
 - window manager, login, remote login
- Unix riddle: what is the name of the terminal I'm running on? ttyp7? ttyq9?
- Plan 9 answer: whoever connected you to your terminal arranged for it to have the conventional name - /dev/cons

/dev/tty vs. /dev/cons

Unix remote login

- csh talks to /dev/tty (delegated to /dev/ttyp1)
 - “pseudo-tty” - careful emulation of a serial line
- Pseudo-tty master (/dev/ptyp1) is managed by sshd
- ASCII characters flow across the network, plus signals!
- Your ssh client is running on /dev/ttyq3
 - Which is connected to a screen window by “xterm”
- What happens when you resize your xterm??

Plan 9 remote login

- Shell's /dev/cons is a *remote file mount* of a window
- Same as if the window were local (albeit slower)
- One protocol: read()/write(), running over 9P

Per-Window Devices

X: a complex monolithic server somewhere

- House of a thousand mysteries
- **Not** on the 15-410 reading list: ICCCM
 - “Inter-client communication conventions manual”

Plan 9: Per-window devices

- I/O - /dev/mouse, /dev/cursor, /dev/cons
- Contents - /dev/text, /dev/window
- Window title - /dev/label (a 1-line text file)
- Working directory - /dev/wdir

% echo top > /dev/wctl

- Requests window manager to bring your window to top

Per-Window Devices

Screen shot

```
% cp /dev/screen /tmp/screen-image
```

Window shot

```
% cp /dev/window /tmp/window-image
```

The Serial-Port File System

Look, Ma, no ioctl()!

```
% bind -a '#t' /dev
```

```
% echo b9600 > /dev/eia1ctl
```

```
% echo "foo" > /dev/eia1
```

The CD-Burner File System

Burn audio tracks to CD

```
% cdfs -d /dev/sdD0
```

- Uses /dev/sdD0/raw to send SCSI commands to hardware
- Mounts itself as /mnt/cd in your namespace

```
% cp *.cda /mnt/cd/wa/
```

- Write CD-Audio tracks to the “write audio” directory

```
% rm /mnt/cd/wa
```

- Remove “write audio” directory to indicate “done writing”
- cdfs will “finalize” the CD

```
% echo eject > /mnt/cd/ctl
```

The tar-ball File System

Rummage through a tar file

```
% fs/tarfs -m /n/tarball foo.tar
```

```
% cat /n/tarball/README
```

The TCP File System

Look, Ma, no finger command!

```
#!/bin/rc
# hold clone & ctl open during connection
{ conn=`{read} cd /net/tcp/$conn
  { echo 'connect 128.2.194.80!79' > ctl ;
    echo davide > data; cat data } < ctl
} < /net/tcp/clone
```

Look, Ma, no NAT proxy setup!

```
% import gateway.srv /net/tcp
```

The /tmp Problem

Unix /tmp: security hole generator

Programs write /tmp/program.3802398

- Or /tmp/program.\$USER.3432432

No name collision “in practice”

- Unless *an adversary* is doing the practicing
% ln -s /tmp/program.3802398 /.cshrc
- Now a setuid-root program will put your commands into root's .cshrc...

Fixing /tmp

No inter-user security problem if *only one user!*

Plan 9 /tmp is per-user

- User chooses what backs the /tmp name
 - Temporary “RAM disk” file system?
 - /usr/\$user/tmp

Matches (sloppy) programmer mental model

Plan 9 3-Level File Store

Exports one tree spanning many disks

- Users bind parts of the tree into namespaces

Original implementation –3-level store

- RAM caches disks, disks cache WORM jukebox

Plug-compatible modern implementation

- Hash-capability log-structured disk store

Daily snapshots, available forever

- `/n/dump/1995/0315` is 1995-03-15 snapshot
- Time travel without “restoring from tape”
 - Public files are *eternally* public –be careful!

Plan 9 Process Model

New-process model

- `fork()`, `mount()/bind()`, `exec()`

System calls block

Task/thread continuum via `rfork()`

- Resources are shared/copied/blank
 - Namespace, environment strings
 - File descriptor table, memory segments, notes
 - Rendezvous space
- `rfork()` w/o “new process” bit edits current process

Process Synchronization

rendezvous(tag, value)

- Sleeps until a 2nd process presents matching tag
- Two processes swap values
- “Tag space” sharing via rfork() like other resources

Shared-memory locks

- Spin-lock, queue-lock

Summary

Files, files, files

- “Plumber” paper
 - Programmable file server
 - Parses strings, extracts filenames
 - Sends filenames to programs
 - File, file, blah, blah, ho hum?
- Isn't it cleaner than
 - Sockets, ICCCM, RPC program numbers, CORBA?

Not just another reimplementation of 1970

- Every compile is a cross-compile
- Every debug is a remote cross-platform debug
- Unicode everywhere
- ...

More Information

“Gold Server” multi-computer environment approach

- How to build a system out of a bunch of Unixes
- Similar approach to Andrew
- Difficult
- <http://www.infrastructures.org/papers/bootstrap/>

Plan 9

- <http://www.cs.bell-labs.com/plan9/>

Disclaimer

A distributed system is a system in which I can't do my work because some computer has failed that I've never even heard of.

- Leslie Lamport