EXPLORING THE PROSODY OF FLOOR MECHANISMS IN ENGLISH USING THE FFV SPECTRUM

Kornel Laskowski^{1,2}, Mattias Heldner³ and Jens Edlund³

Language Technologies Institute, Carnegie Mellon University, USA
 Institut für Anthropomatik, Universität Karlsruhe, Germany
 Department of Speech, Music and Hearing, KTH, Sweden

Goal

Determine if fundamental frequency variation (FFV) discriminates between floor mechanisms and other dialog act (DA) types.

floor holder (fh) hold floor within turn


hold (h) secure offered floor at start of turn

floor grabber (fg) secure unoffered floor at start of turn


NB: Floor mechanisms lexically similar to other short DA types.

What Is the Fundamental Frequency Variation Spectrum?

• dot product of two spectra, F_L and F_R ...



- ... after dilating one of F_L and F_R by factor 2^ρ
- FFV spectrum is value of dot product over range of ρ



- 7-filter filterbank:
 - flat pitch
 - slowly falling (rising) pitch
 - quickly falling (rising) pitch
 - 2 normalization values


Experiments

- ICSI Meeting Corpus
- naturally occuring, spontaneous multiparty speech
- close-talk-mic 16kHz audio
- ► training: 2×7000 talkspurts
- ► testing: 2×1000 talkspurts
- compute HMM density models
- classify: $\neg \{fh + h\}$ or $\{fh + h\}$
 - first 500ms of every talkspurt
 - ▶ last 500ms of every talkspurt
- test accuracy: 64.1-65.3%
- test ROC area: 70.6–72.2%

Findings

- FFV discriminates between floor mechanisms {fh + h} and other DA types ¬{fh + h}
- consecutive frames more similar
 for {fh + h} than for
 ¬{fh + h}
 - first 500ms: effect more pronounced during flat pitch
 - last 500ms: effect independent of pitch trajectory
- FFV representation useful in:
 - multiparty dialogue scenarios
 - non-anechoic-chamber recording scenarios

Inferred Models of Talkspurt *Initiation*



Inferred Models of Talkspurt *Termination*

