Dynamic Memory Allocation: Basic Concepts

15-213/18-213/15-513: Introduction to Computer Systems 13th Lecture, October 12, 2021

Announcements

No lecture on Thursday October 14

- Malloclab out today
 - Checkpoint due on Tuesday October 26 (+ up to 2 grace days)
 - Final submission due on Tuesday November 2 (+ up to 2 grace days)

Today

- Basic concepts
- Implicit free lists

Dynamic Memory Allocation


Application

Dynamic Memory Allocator

Heap

- Programmers use dynamic memory allocators (such as malloc) to acquire virtual memory (VM) at runtime
 - For data structures whose size is only known at runtime
- Dynamic memory allocators manage an area of process
 VM known as the heap

0x400000



Dynamic Memory Allocation

- Allocator maintains heap as collection of variable sized blocks, which are either allocated or free
- Types of allocators
 - Explicit allocator: application allocates and frees space
 - e.g., malloc and free in C
 - Implicit allocator: application allocates, but does not free space
 - e.g., new and garbage collection in Java
- Will discuss simple explicit memory allocation today

The malloc Package

```
#include <stdlib.h>
void *malloc(size_t size)
```

- Successful:
 - Returns a pointer to a memory block of at least size bytes aligned to a 16-byte boundary (on x86-64)
 - If size == 0, returns NULL
- Unsuccessful: returns NULL (0) and sets errno

void free(void *p)

- Returns the block pointed at by p to pool of available memory
- p must come from a previous call to malloc, calloc, or realloc

Other functions


- calloc: Version of malloc that initializes allocated block to zero
- realloc: Changes the size of a previously allocated block
- **sbrk:** Used internally by allocators to grow or shrink the heap

malloc Example

```
#include <stdio.h>
#include <stdlib.h>
void foo(long n) {
    long i, *p;
    /* Allocate a block of n longs */
    p = (long *) malloc(n * sizeof(long));
    if (p == NULL) {
        perror("malloc");
        exit(0);
    /* Initialize allocated block */
    for (i=0; i<n; i++)</pre>
       p[i] = i;
    /* Do something with p */
    /* Return allocated block to the heap */
    free(p);
```


Visualization Conventions

- Show 8-byte words as squares
- Allocations are double-word aligned



Allocation Example (Conceptual)

#define SIZ sizeof(size_t)



Constraints

Applications

- Can issue arbitrary sequence of malloc and free requests
- free request must be to a malloc'd block

Explicit Allocators

- Can't control number or size of allocated blocks
- Must respond immediately to malloc requests
 - *i.e.*, can't reorder or buffer requests
- Must allocate blocks from free memory
 - *i.e.*, can only place allocated blocks in free memory
- Must align blocks so they satisfy all alignment requirements
 - 16-byte (x86-64) alignment on 64-bit systems
- Can manipulate and modify only free memory
- Can't move the allocated blocks once they are malloc'd
 - *i.e.*, compaction is not allowed. *Why not?*

Performance Goal: Throughput

- Given some sequence of malloc and free requests:
 - $R_0, R_1, ..., R_k, ..., R_{n-1}$
- Goals: maximize throughput and peak memory utilization
 - These goals are often conflicting
- Throughput:
 - Number of completed requests per unit time
 - Example:
 - 5,000 malloc calls and 5,000 free calls in 10 seconds
 - Throughput is 1,000 operations/second

Performance Goal: Minimize Overhead

- Given some sequence of malloc and free requests:
 - $R_0, R_1, ..., R_k, ..., R_{n-1}$
- After k requests we have:
- Def: Aggregate payload P_k
 - malloc(p) results in a block with a payload of p bytes
 - The aggregate payload P_k is the sum of currently allocated payloads
 - The *peak aggregate payload* $\max_{i \le k} P_i$ is the maximum aggregate payload at any point in the sequence up to request
- Def: Current heap size H_k
 - Assume heap only grows when allocator uses sbrk, never shrinks
- lacktriangle Def: Overhead, O_k
 - Fraction of heap space NOT used for program data
 - $O_k = (H_k / \max_{i \le k} P_i) 1.0$

Benchmark Example


Benchmark syn-array-short

- Trace provided with malloc lab
- Allocate & free 10 blocks
- a = allocate
- f = free
- Bias toward allocate at beginning & free at end
- Blocks number 1–10
- Allocated: Sum of all allocated amounts
- Peak: Max so far of Allocated

Step	Command			Delta	Allocated	Peak
1	a	0	9904	9904	9904	9904
2	a	1	50084	50084	59988	59988
3	a	2	20	20	60008	60008
4	a	3	16784	16784	76792	76792
5	f	3		-16784	60008	76792
6	a	4	840	840	60848	76792
7	a	5	3244	3244	64092	76792
8	f	0		-9904	54188	76792
9	a	6	2012	2012	56200	76792
10	f	2		-20	56180	76792
11	a	7	33856	33856	90036	90036
12	f	1		-50084	39952	90036
13	a	8	136	136	40088	90036
14	f	7		-33856	6232	90036
15	f	6		-2012	4220	90036
16	a	9	20	20	4240	90036
17	f	4		-840	3400	90036
18	f	8		-136	3264	90036
19	f	5		-3244	20	90036
20	f	9		-20	0	90036


Benchmark Visualization

Step	Command			Delta	Allocated	Peak
1	a	0	9904	9904	9904	9904
2	a	1	50084	50084	59988	59988
3	a	2	20	20	60008	60008
4	a	3	16784	16784	76792	76792
5	f	3		-16784	60008	76792
6	a	4	840	840	60848	76792
7	a	5	3244	3244	64092	76792
8	f	0		-9904	54188	76792
9	a	6	2012	2012	56200	76792
10	f	2		-20	56180	76792
11	a	7	33856	33856	90036	90036
12	f	1		-50084	39952	90036
13	a	8	136	136	40088	90036
14	f	7		-33856	6232	90036
15	f	6		-2012	4220	90036
16	a	9	20	20	4240	90036
17	f	4		-840	3400	90036
18	f	8		-136	3264	90036
19	f	5		-3244	20	90036
20	f	9		-20	0	90036



- Plot P_k (allocated) and $\max_{i \le k} P_k$ (peak) as a function of k (step)
- Y-axis normalized fraction of maximum

Typical Benchmark Behavior




- Longer sequence of mallocs & frees (40,000 blocks)
 - Starts with all mallocs, and shifts toward all frees
- Allocator must manage space efficiently the whole time
- Production allocators can shrink the heap

Fragmentation

- Poor memory utilization caused by *fragmentation*
 - Internal fragmentation
 - External fragmentation

Internal Fragmentation

■ For a given block, *internal fragmentation* occurs if payload is smaller than block size




Caused by

- Overhead of maintaining heap data structures
- Padding for alignment purposes
- Explicit policy decisions

 (e.g., to return a big block to satisfy a small request)
- Depends only on the pattern of previous requests
 - Thus, easy to measure

Internal Fragmentation Effect




- Purple line: additional heap size due to allocator's data + padding for alignment
 - For this benchmark, 1.5% overhead
 - Cannot achieve in practice
 - Especially since cannot move allocated blocks

External Fragmentation


#define SIZ sizeof(size_t)

Occurs when there is enough aggregate heap memory,
 but no single free block is large enough



- Depends on the pattern of future requests
 - Thus, difficult to measure

External Fragmentation Effect



- Green line: additional heap size due to external fragmentation
- Best Fit: One allocation strategy
 - (To be discussed later)
 - Total overhead = 8.3% on this benchmark


Implementation Issues

- How do we know how much memory to free given just a pointer?
- How do we keep track of the free blocks?
- What do we do with the extra space when allocating a structure that is smaller than the free block it is placed in?
- How do we pick a block to use for allocation -- many might fit?
- How do we reuse a block that has been freed?

Knowing How Much to Free

Standard method

- Keep the length (in bytes) of a block in the word preceding the block.
 - Including the header
 - This word is often called the *header field* or *header*
- Requires an extra word for every allocated block




Keeping Track of Free Blocks

■ Method 1: *Implicit list* using length—links all blocks



Need to tag each block as allocated/free

Method 2: Explicit list among the free blocks using pointers



Need space for pointers

- Method 3: Segregated free list
 - Different free lists for different size classes
- Method 4: *Blocks sorted by size*
 - Can use a balanced tree (e.g., Red-Black tree) with pointers within each free block, and the length used as a key

Today

- Basic concepts
- Implicit free lists


Method 1: Implicit Free List

- For each block we need both size and allocation status
 - Could store this information in two words: wasteful!

Standard trick

- When blocks are aligned, some low-order address bits are always 0
- Instead of storing an always-0 bit, use it as an allocated/free flag
- When reading the Size word, must mask out this bit

Format of allocated and free blocks




a = 1: Allocated block

a = 0: Free block

Size: total block size

Payload: application data (allocated blocks only)

Detailed Implicit Free List Example



Double-word aligned

Allocated blocks: shaded

Free blocks: unshaded

Headers: labeled with "size in words/allocated bit"

Headers are at non-aligned positions

→ Payloads are aligned

Implicit List: Data Structures

header payload

Block declaration

```
typedef uint64_t word_t;

typedef struct block
{
    word_t header;
    unsigned char payload[0];  // Zero length array
} block_t;
```

Getting payload from block pointer

```
//block_t *block
```

```
return (void *) (block->payload);
```

Getting header from payload

// bp points to a payload

C function offsetof (struct, member) returns offset of member within struct

Implicit List: Header access

Size a

Getting allocated bit from header

```
return header & 0x1;
```

Getting size from header

```
return header & ~0xfL;
```

Initializing header


```
//block_t *block
```

```
block->header = size | alloc;
```

Implicit List: Traversing list




Find next block



Implicit List: Finding a Free Block

- **■** First fit:
 - Search list from beginning, choose first free block that fits:
 - Finding space for asize bytes (including header):

```
static block_t *find_fit(size_t asize)
{
    block_t *block;
    for (block = heap_start; block != heap_end;
        block = find_next(block)) {
        if (!(get_alloc(block))
          && (asize <= get_size(block)))
        return block;
    }
    return NULL; // No fit found
}</pre>
```



Implicit List: Finding a Free Block

■ First fit:

- Search list from beginning, choose first free block that fits:
- Can take linear time in total number of blocks (allocated and free)
- In practice it can cause "splinters" at beginning of list


Next fit:

- Like first fit, but search list starting where previous search finished
- Should often be faster than first fit: avoids re-scanning unhelpful blocks
- Some research suggests that fragmentation is worse

Best fit:

- Search the list, choose the best free block: fits, with fewest bytes left over
- Keeps fragments small—usually improves memory utilization
- Will typically run slower than first fit
- Still a greedy algorithm. No guarantee of optimality

Comparing Strategies



Total Overheads (for this benchmark)

Perfect Fit: 1.6%


Best Fit: 8.3%


• First Fit: 11.9%

Next Fit: 21.6%


Implicit List: Allocating in Free Block

- Allocating in a free block: splitting
 - Since allocated space might be smaller than free space, we might want to split the block





Implicit List: Splitting Free Block




```
// Warning: This code is incomplete

static void split_block(block_t *block, size_t asize) {
    size_t block_size = get_size(block);

    if ((block_size - asize) >= min_block_size) {
        write_header(block, asize, true);
        block_t *block_next = find_next(block);
        write_header(block_next, block_size - asize, false);
}
```

Implicit List: Freeing a Block

- Simplest implementation:
 - Need only clear the "allocated" flag
 - But can lead to "false fragmentation"




malloc(5*SIZ) Yikes!

There is enough contiguous free space, but the allocator won't be able to find it


Implicit List: Coalescing

- Join (coalesce) with next/previous blocks, if they are free
 - Coalescing with next block



Implicit List: Coalescing


- Join *(coalesce)* with next block, if it is free
 - Coalescing with next block




- How do we coalesce with previous block?
 - How do we know where it starts?
 - How can we determine whether its allocated?

Implicit List: Bidirectional Coalescing

- **Boundary tags** [Knuth73]
 - Replicate size/allocated word at "bottom" (end) of free blocks
 - Allows us to traverse the "list" backwards, but requires extra space
 - Important and general technique!





a = 1: Allocated block

a = 0: Free block


Size: Total block size

Payload: Application data (allocated blocks only)

Quiz

https://canvas.cmu.edu/courses/24383/quizzes/67237

Implementation with Footers




Locating footer of current block

```
const size_t dsize = 2*sizeof(word_t);

static word_t *header_to_footer(block_t *block)
{
    size_t asize = get_size(block);
    return (word_t *) (block->payload + asize - dsize);
}
```


Implementation with Footers



Locating footer of previous block

```
static word_t *find_prev_footer(block_t *block)
{
   return &(block->header) - 1;
}
```


Splitting Free Block: Full Version




```
static void split_block(block_t *block, size_t asize) {
    size_t block_size = get_size(block);

if ((block_size - asize) >= min_block_size) {
    write_header(block, asize, true);
    write_footer(block, asize, true);
    block_t *block_next = find_next(block);
    write_header(block_next, block_size - asize, false);
    write_footer(block_next, block_size - asize, false);
}
```


Constant Time Coalescing




Constant Time Coalescing (Case 1)




Constant Time Coalescing (Case 2)



Constant Time Coalescing (Case 3)




Constant Time Coalescing (Case 4)



Heap Structure





Dummy footer before first header

- Marked as allocated
- Prevents accidental coalescing when freeing first block

Dummy header after last footer

Prevents accidental coalescing when freeing final block

Top-Level Malloc Code

```
const size t dsize = 2*sizeof(word t);
void *mm malloc(size t size)
    size t asize = round up(size + dsize, dsize);
   block t *block = find fit(asize);
    if (block == NULL)
        return NULL:
    size t block size = get size(block);
    write header(block, block size, true);
    write footer(block, block size, true);
    split block(block, asize);
    return header to payload(block);
```

```
round_up(n, m)
=
m *((n+m-1)/m)
```

Top-Level Free Code


```
void mm_free(void *bp)
{
    block_t *block = payload_to_header(bp);
    size_t size = get_size(block);

    write_header(block, size, false);
    write_footer(block, size, false);

    coalesce_block(block);
}
```


Disadvantages of Boundary Tags

- Internal fragmentation
- Can it be optimized?
 - Which blocks need the footer tag?
 - What does that mean?



No Boundary Tag for Allocated Blocks

- Boundary tag needed only for free blocks
- When sizes are multiples of 16, have 4 spare bits




Size b0
Unallocated
Size b0

Allocated Block


Free Block

No Boundary Tag for Allocated Blocks (Case 1)




Header: Use 2 bits (address bits always zero due to alignment):

No Boundary Tag for Allocated Blocks (Case 2)




Header: Use 2 bits (address bits always zero due to alignment):

No Boundary Tag for Allocated Blocks (Case 3)



Header: Use 2 bits (address bits always zero due to alignment):

No Boundary Tag for Allocated Blocks (Case 4)



Header: Use 2 bits (address bits always zero due to alignment):

Summary of Key Allocator Policies

Placement policy:

- First-fit, next-fit, best-fit, etc.
- Trades off lower throughput for less fragmentation
- Interesting observation: segregated free lists (next lecture)
 approximate a best fit placement policy without having to search
 entire free list

Splitting policy:

- When do we go ahead and split free blocks?
- How much internal fragmentation are we willing to tolerate?

Coalescing policy:

- Immediate coalescing: coalesce each time free is called
- Deferred coalescing: try to improve performance of free by deferring coalescing until needed.

Implicit Lists: Summary

- Implementation: very simple
- Allocate cost:
 - linear time worst case
- Free cost:
 - constant time worst case
 - even with coalescing
- Memory Overhead
 - will depend on placement policy
 - First-fit, next-fit or best-fit
- Not used in practice for malloc/free because of lineartime allocation
 - used in many special purpose applications
- However, the concepts of splitting and boundary tag coalescing are general to all allocators