MultiModal Learning

AI and ML II

Some of the slides are taken from: Matt Gormley

Learning objectives

Explain how modalities complement or contradict one another.

Derive CLIP training and zero-shot prediction.

Compare CLIP variants and choose suitable VLM evaluation protocols.

Distinguish VLA action prediction from JEPA representation prediction.

Overview

Multimodal foundations

Challenges of multimodal learning

Vision–language models and benchmarks

CLIP: architecture and training

CLIP extensions and variations

VLM evaluation

Vision–language–action models

Joint-Embedding Predictive Architectures

What is a modality?

A modality is a form of observation or communication.

A model may combine sensory, language, physiological and environmental signals.

Different modalities may describe the same underlying event.




Example modalities

Modality	Typical representation	Example information
Text	Tokens or embeddings	An instruction or description
Image	Pixels or patches	Shape, color and spatial layout
Audio	Waveform or spectrogram	Speech, sound and tone
Video	Frames over time	Motion and event order
Depth / motion / sensors	Point clouds or time series	Distance, pose and physical state

Why Do We Need Multimodal

The human experience of the world is multimodal, so we need AI systems capable of simultaneously processing diverse input modalities.



Yosemite National Park

73 languages

Article Talk Read Edit View history Tools

From Wikipedia, the free encyclopedia

Coordinates: 37°44′33″N 119°32′15″W

(Redirected from Yosemite)

"Yosemite" redirects here. For other uses, see Yosemite (disambiguation).


Yosemite National Park (/joʊˈsɛmɪti/ *yoh-SEM-ih-tee*[5]) is a national park in California.[6][7] It is bordered on the southeast by Sierra National Forest and on the northwest by Stanislaus National Forest. The park is managed by the National Park Service and covers 759,620 acres (1,187 sq mi; 3,074 km²)[3] in four counties – centered in Tuolumne and Mariposa, extending north and east to Mono and south to Madera. Designated a World Heritage Site in 1984, Yosemite is internationally recognized for its granite cliffs, waterfalls, clear streams, giant sequoia groves, lakes, mountains, meadows, glaciers, and biological diversity.[8] Almost 95 percent of the park is designated wilderness.[9] Yosemite is one of the largest and least fragmented habitat blocks in the Sierra Nevada.

Its geology is characterized by granite and remnants of older rock. About 10 million years ago, the Sierra Nevada was uplifted and tilted to form its unique slopes, which increased the steepness of stream and river beds, forming deep, narrow canyons. About one million years ago glaciers formed at higher elevations. They moved downslope, cutting and sculpting the U-shaped Yosemite Valley.[8]

Yosemite National Park

IUCN category II (national park)[1]

Yosemite Valley from Tunnel View




Data is often inherently multimodal

Common multimodal tasks

Task	Input	Output
Retrieval	Text query	Ranked images
Captioning	Image	Description
Visual question answering	Image + question	Answer
Conditional generation	Text or other context	Image, audio or video
Action prediction	Vision + instruction + state	Action

Multimodal Machine Learning



Learning challenges

Alignment, representations and generalization

Core challenges in multimodal learning

1. Representation

How can we encode different signals while preserving useful information? Pixels, tokens and waveforms have different structures.

2. Alignment

Which parts of the inputs correspond? Match words to image regions, or synchronize speech with video events.

3. Fusion


How should we combine evidence across modalities? Use complementary cues and handle conflicting or missing inputs.

4. Translation

How can we generate one modality from another? A caption must describe an image faithfully, although many captions may be valid.

Challenge 1: Representation

Learn representations that capture interactions between elements across modalities.



It can be seen as a "local" representation


or

representation using holistic features

Representations can describe a local element or the complete input.

Challenge 2: Alignment

Find which words, image regions or time segments correspond to one another.




Challenge 3: Fusion

Combine evidence from different modalities for a joint prediction.

Early fusion combines features before prediction.

Late fusion combines predictions from separate models.



Challenge 4: Translation


Generate one modality from another while preserving the relevant information.

An armchair in the shape of an avocado →




Fusion and coordination

Fusion



Fusion combines features to predict jointly.

Coordination



Coordination retains separate representations and relates them.

Vision–language models

Architectures, tasks and benchmarks

Vision–language models

VLMs learn relationships between visual content and language.

Contrastive models score image–text compatibility.

Generative VLMs produce text conditioned on images and a prompt.

Two architecture families

Aspect	Dual encoder	Image-conditioned language model
Inputs	Image and text, encoded separately	Visual features and text prompt
Output	Compatibility score / embedding	A sequence of text tokens
Training example	Paired image and caption	Image, instruction and response
Typical use	Retrieval and zero-shot classification	Captioning and question answering

VLM: Tasks

Common benchmarks for VLMs include


Visual reasoning:	given an image (or a pair of images) determine if some natural language statement about the image(s) is true or false
Visual grounding:	locate an object in some image given a natural language description
Visual question answering:	given an image (or images), respond to arbitrary, potentially open-ended questions about the content.
Caption generation:	create natural language descriptions of content of some image

VLM tasks: visual reasoning

Given one or two images and a statement, predict true or false.

Reasoning can require counting, comparison and relationships.

Example benchmark: NLVR2.




VLM tasks: visual grounding

Given an image and a referring expression, locate the intended object.

Descriptions may use position, appearance or relationships.

Example benchmarks: RefCOCO, RefCOCO+ and RefCOCOg.



RefCOCO:
1. giraffe on left
2. first giraffe on left

RefCOCO+:
1. giraffe with lowered head
2. giraffe head down

RefCOCOg:
1. an adult giraffe scratching its back with its horn
2. giraffe hugging another giraffe

VLM tasks: visual question answering

Given an image and a question, predict an answer.

Questions can ask about objects, actions, locations or quantities.

The answer must depend on the visual evidence.




VLM tasks: caption generation

Given an image, generate a description of its content.

Several captions may correctly describe the same image.

Compare reference and generated captions for missing or incorrect details.



Ground Truth Caption: A little boy runs away from the approaching waves of the ocean.

Generated Caption: A young boy is running on the beach.



Ground Truth Caption: A brunette girl wearing sunglasses and a yellow shirt.

Generated Caption: A woman in a black shirt and sunglasses smiles.

VLM architecture: from images to generated text

Encode the image and text as embedding vectors.

Project visual features into the language model's input dimension.

A decoder-only transformer predicts the next text token.

Encoder options: discrete visual tokens (VQ-VAE) or continuous visual features (CLIP).





IMAGE ENCODERS: **CLIP**

CLIP: the central idea

Contrastive Language–Image Pre-training learns from paired images and text.

The encoders place compatible inputs near each other in an embedding space.

The same encoders support retrieval and classification through text prompts.



A paired training batch



$$B = \{(I_1, T_1), (I_2, T_2), \ldots, (I_N, T_N)\}$$


$$N \text{ matching pairs}, \qquad N(N-1) \text{ other pairs}$$

Each image has one designated text partner in this batch.

Paired inputs in B share the same index i.

Every other cross-pair becomes a candidate negative.

The two encoders



$$I_i^{\text{enc}} = \text{ImageEncoder}(\text{image } i)$$


$$T_i^{\text{enc}} = \text{TextEncoder}(\text{text } i)$$

The image encoder extracts visual features.

The text encoder summarizes the token sequence.

Their output dimensions may differ.

Projection into a common dimension



$$I_i^{\text{proj}} = W_I I_i^{\text{enc}} \in \mathbb{R}^d$$


$$T_i^{\text{proj}} = W_T T_i^{\text{enc}} \in \mathbb{R}^d$$

Learned linear maps put both feature vectors in d dimensions.

Projection weights belong to the trainable model.

Shared dimensionality makes the similarity calculation possible.

Unit-length embeddings



$$I_i = \frac{I_i^{\text{proj}}}{\|I_i^{\text{proj}}\|_2}$$

$$T_i = \frac{T_i^{\text{proj}}}{\|T_i^{\text{proj}}\|_2}$$


$$\|I_i\|_2 = \|T_i\|_2 = 1$$

Normalization removes vector magnitude from the score.

The normalized embeddings are denoted I⍰ and T⍰ .

The dot product now equals cosine similarity.

Cosine similarity and training intuition



$$\cos(I_i, T_j) = I_i^\top T_j$$

Intuition only, not the CLIP loss:


$$\max \left[\sum_{i=1}^{N} I_i^\top T_i - \sum_{i=1}^{N} \sum_{\substack{j=1 \\ j \neq i}}^{N} I_i^\top T_j \right]$$

A larger cosine indicates stronger directional agreement.

Matched pairs should receive higher scores than competing pairs.

The unnormalized expression is intuition, not the CLIP training objective.

Temperature and logits



$$\text{logit for pair } (i, j) = \frac{I_i^\top T_j}{\tau}$$

$$\tau > 0, \qquad \text{logit scale} = \frac{1}{\tau}$$


$$\text{smaller } \tau \implies \text{sharper softmax}$$

Temperature controls the sharpness of the softmax.

A smaller temperature magnifies score differences.

The positive logit scale is 1/□ .

All image–text scores at once



rows: $I_1, \ldots, I_N$ columns: $T_1, \ldots, T_N$


$$\begin{bmatrix} I_1^\top T_1/\tau & \cdots & I_1^\top T_N/\tau \\ \vdots & \ddots & \vdots \\ I_N^\top T_1/\tau & \cdots & I_N^\top T_N/\tau \end{bmatrix}$$

Rows index images. Columns index texts.

Matrix multiplication creates every candidate pairing.

The desired partner for row i and column i lies on the diagonal.

Image-to-text probabilities



$$p_{IT}(i \text{ matches } j \mid I_i, T_1, \ldots, T_N) = \frac{\exp(I_i^\top T_j/\tau)}{\sum_{k=1}^{N} \exp(I_i^\top T_k/\tau)}$$


$$\sum_{j=1}^{N} p_{IT}(i \text{ matches } j \mid I_i, T_1, \ldots, T_N) = 1$$

Fix image i and compare all N candidate texts.

The numerator scores candidate text j; the observed match has j = i.

The denominator includes the positive and all competing texts.

Image-to-text cross-entropy



$$\ell_i^{IT} = -\log p_{IT}(i \text{ matches } i \mid I_i, T_1, \ldots, T_N)$$


$$\mathcal{L}_{IT} = -\frac{1}{N}\sum_{i=1}^{N} \log \frac{\exp(I_i^\top T_i/\tau)}{\sum_{j=1}^{N} \exp(I_i^\top T_j/\tau)}$$

The target for image i is caption i.

Negative log probability penalizes a low score for that target.

Average over every image in the batch.

Text-to-image probabilities



$$p_{TI}(i \text{ matches } j \mid T_i, I_1, \ldots, I_N) = \frac{\exp(I_j^\top T_i/\tau)}{\sum_{k=1}^{N} \exp(I_k^\top T_i/\tau)}$$


$$\mathcal{L}_{TI} = -\frac{1}{N}\sum_{i=1}^{N} \log p_{TI}(i \text{ matches } i \mid T_i, I_1, \ldots, I_N)$$

Fix text i and compare all N candidate images.

The softmax now runs down a column.

The observed matching image remains image i.

The symmetric CLIP objective



$$\max \sum_{i=1}^{N} \left[\log \frac{\exp(I_i^\top T_i/\tau)}{\sum_{j=1}^{N} \exp(I_i^\top T_j/\tau)} + \log \frac{\exp(I_i^\top T_i/\tau)}{\sum_{j=1}^{N} \exp(I_j^\top T_i/\tau)} \right]$$

$$\text{equivalently: } \min \mathcal{L}_{\text{CLIP}} = \frac{\mathcal{L}_{IT} + \mathcal{L}_{TI}}{2}$$

Both directions use the same score matrix and encoders.

Maximize the sum of the two matching log-likelihoods.

The equivalent training loss is their negative average.

CLIP: conditional matching probabilities

$$\max \sum_{i=1}^{N} \left[\log \frac{\exp(I_i^\top T_i/\tau)}{\sum_{j=1}^{N} \exp(I_i^\top T_j/\tau)} + \log \frac{\exp(I_i^\top T_i/\tau)}{\sum_{j=1}^{N} \exp(I_j^\top T_i/\tau)} \right]$$

Two conditional probability distributions

$$p_{IT}(i \text{ matches } j \mid I_i, T_1, \ldots, T_N) = \frac{\exp(I_i^\top T_j/\tau)}{\sum_{k=1}^{N} \exp(I_i^\top T_k/\tau)}$$

Image-to-text: softmax over text columns.

$$p_{TI}(i \text{ matches } j \mid T_i, I_1, \ldots, I_N) = \frac{\exp(I_j^\top T_i/\tau)}{\sum_{k=1}^{N} \exp(I_k^\top T_i/\tau)}$$

Text-to-image: softmax over image rows.

Maximize the log-likelihood of the matched pairs in both directions:

$$\sum_{i=1}^{N} [\log p_{IT}(i \text{ matches } i \mid I_i, T_1, \ldots, T_N) + \log p_{TI}(i \text{ matches } i \mid T_i, I_1, \ldots, I_N)]$$

Worked example: a batch of two

Toy logits favor the matching pair in each row and column.

For image 1, the correct-caption probability is about 0.953.

The symmetric loss is about 0.1267 nats.

$$\left[\frac{I_i^\top T_j}{\tau}\right]_{i,j=1}^{2} = \begin{bmatrix} 4 & 1 \\ 0 & 2 \end{bmatrix}$$

$$p_{IT}(1 \text{ matches } 1 \mid I_1, T_1, T_2) = \frac{e^4}{e^4 + e^1} \approx 0.953$$

$$\mathcal{L}_{IT} \approx 0.0878, \qquad \mathcal{L}_{TI} \approx 0.1657$$

$$\mathcal{L}_{\text{CLIP}} \approx 0.1267$$

What the gradient changes

For a positive pair, the score gradient is negative.

For a competing pair, the score gradient is positive.

Gradient descent therefore favors the observed match.

$$\ell_i^{IT} = -\log p_{IT}(i \text{ matches } i \mid I_i, T_1, \ldots, T_N)$$

$$\frac{\partial \ell_i^{IT}}{\partial (I_i^\top T_j / \tau)} = p_{IT}(i \text{ matches } j \mid I_i, T_1, \ldots, T_N) - \mathbf{1}[j = i]$$

$$j = i: \quad p_{IT} - 1 \leq 0$$

$$j \neq i: \quad p_{IT} \geq 0$$

One CLIP training step

1. Encode, project and normalize paired inputs.

2. Form the scaled similarity matrix.

3. Compute cross-entropy in both directions.

4. Backpropagate and update trainable parameters.


```
I = normalize(image_encoder(images) @ W_I.T)
T = normalize(text_encoder(tokens) @ W_T.T)
logits = (I @ T.T) / tau
labels = arange(N)
loss = (CE(logits, labels)
      + CE(logits.T, labels)) / 2
optimizer.zero_grad()
loss.backward()
optimizer.step()
```

Batch negatives and imperfect captions

Larger batches provide more candidate negatives per image.

Similar samples can become false negatives.


A caption can describe only a subset of visible content.



Example: a compatible caption becomes a negative

Two paired examples in the same training batch

Image I



T “A dog on a beach.”

Image I



T “A dog outdoors.”


	T	T
I	Match	Negative
I	Negative	Match

Both off-diagonal captions fit the images, but the loss treats them as negatives.

Dataset pairing defines the target; semantic compatibility can be broader.

Example: a caption omits visible information

Caption: “A dog on a beach.”




The image also shows a green ball, breaking waves and a reflection.

The caption describes the dog and setting, but leaves those details unmentioned.

The contrastive objective rewards a compatible match without explicitly supervising every detail.

Zero-shot classification with text



$$T_i = \text{normalized embedding of class prompt } i$$

$$\hat{y} = \arg\max_i \; p_{IT}(1 \text{ matches } i \mid I_1, T_1, \ldots, T_N)$$

$$= \arg\max_i \frac{\exp(I_1^\top T_i/\tau)}{\sum_{j=1}^{N} \exp(I_1^\top T_j/\tau)}$$

Write a prompt for each candidate class.

Encode the prompts and the new image.

Choose the class with the highest compatibility score.

Class probabilities and a toy prediction

Candidate prompts define the possible classes.

Softmax converts scaled similarities into a distribution over that list.

Changing the class list can change the probabilities.

$$p_{IT}(1 \text{ matches } i \mid I_1, T_1, \ldots, T_N)$$

$$= \frac{\exp(I_1^\top T_i/\tau)}{\sum_{j=1}^{N} \exp(I_1^\top T_j/\tau)}$$

$$[I_1^\top T_1, I_1^\top T_2, I_1^\top T_3] = [0.30, 0.25, 0.10]$$

$$\tau = 0.1 \quad \Longrightarrow \quad [0.574, 0.348, 0.078]$$

Prompt templates and ensembling

A template gives class names linguistic context.

Different templates can produce different class embeddings.

Average normalized template embeddings, then normalize again.

$$T_i^{(m)} = \text{normalized embedding of template } m \text{ for class } i$$

$$\overline{T}_i = \frac{\frac{1}{M}\sum_{m=1}^{M} T_i^{(m)}}{\left\| \frac{1}{M}\sum_{m=1}^{M} T_i^{(m)} \right\|_2}$$

$$\hat{y} = \arg\max_i I_1^\top \overline{T}_i$$

What CLIP learns and misses

CLIP learns reusable image–text compatibility.

Global alignment can miss counting, negation and object relationships.

Its embedding can support a larger system, but CLIP alone does not generate an answer.

Extensions and variations

Extensions of the CLIP idea

What changes?	Example	Main purpose
Training implementation / scale	OpenCLIP	Reproducible contrastive models
Pairwise objective	SigLIP	Sigmoid rather than batch softmax
Training domain	ConVIRT	Images paired with medical reports
Connection to language generation	BLIP-2, LLaVA	Visual features condition a language model

OpenCLIP: reproducible contrastive learning

OpenCLIP provides open training code and model checkpoints.

Studies vary dataset scale, architecture and training compute.

A shared objective does not guarantee identical downstream behavior.

SigLIP: a pairwise sigmoid objective

Each image–text pair receives a binary match label.

A sigmoid loss replaces row and column softmax normalization.

The bias helps handle the imbalance between positive and negative pairs.

$$\max \sum_{i=1}^{N} \sum_{j=1}^{N} \log \frac{1}{1 + \exp\left[y_{ij}(-w I_i^\top T_j + b)\right]}$$

$$y_{ij} = \begin{cases} 1 & i = j \text{ (matching pair)} \\ -1 & \text{otherwise} \end{cases}$$

$$w = \exp(w'), \qquad b \text{ learnable}$$

Domain adaptation: ConVIRT

Pair medical images with their accompanying reports.

Use cross-modal contrastive learning to learn image representations.

Domain terminology and subtle findings create different supervision demands.








Severe cardiomegaly is noted in the image with enlarged...





BLIP-2: a learned bridge to a language model

A trainable Q-Former extracts useful visual information.

The image encoder and language model remain frozen in the proposed recipe.

A second stage connects the visual representation to language generation.

LLaVA: visual instruction tuning

A projection connects vision-encoder features to a language model.

Alignment training teaches the connector to expose visual information.


Instruction tuning trains responses to image-based user requests.

PaliGemma: a contrastive encoder plus an LLM

A SigLIP vision encoder supplies visual features.

A projection adapts those features for the Gemma language model.

The language model predicts output text conditioned on image and prompt.



Evaluating VLMs

Evaluating VLMs: four questions


What output does the model produce?

What information and adaptation does the protocol allow?

Does the metric measure the intended capability?

Does the result survive controlled changes to the inputs?

Zero-shot classification: encode the candidates




Write one prompt for each candidate class.

Encode all prompts and the test image.

No target-task classifier is trained.

Zero-shot classification: compare similarities




Compute cosine similarity with each class prompt.

Predict the class with the highest score.

Compare the prediction with a reference label.

Zero-shot classification: a numerical example

Use frozen encoders and candidate class prompts.



Toy unit-length embeddings (2-D)

$$I_1 = (1, 0), \quad T_1 = (0.8, 0.6)$$
$$T_2 = (0.6, 0.8), \quad T_3 = (0, 1)$$


Temperature $\tau = 0.2$


Class	Cosine	Logit	Probability
Dog	**0.8**	**4**	**72.1%**
Cat	0.6	3	26.5%
Fish	0.0	0	1.3%


$$I_1^\top T_1 = 1(0.8) + 0(0.6) = 0.8$$
$$p_{IT}(1 \text{ matches } 1 \mid I_1, T_1, T_2, T_3)$$
$$= \frac{e^4}{e^4 + e^3 + 1} \approx 0.721$$

Predicted class: dog

Zero-shot classification: example predictions








Compare the predicted class with its reference label.

Text-to-image retrieval





Encode the text query and candidate images.

Score images by their cosine similarity to the query.

Rank the candidates from highest to lowest similarity.

Text-to-image retrieval: a search example





Query: “dog on a beach”. Inspect the ranking and relevance of the returned images.

Prompting VLMs: textual and visual prompts

Textual prompts

Templates place the class name in context.

```
templates = [
    'a photo of a {}.',
    'a blurry photo of a {}.',
    'a black and white photo of a {}.',
    'a low contrast photo of a {}.',
    'a high contrast photo of a {}.',
    'a bad photo of a {}.',
    'a good photo of a {}.',
    'a photo of a small {}.',
    'a photo of a big {}.',
    'a photo of the {}.',
    'a blurry photo of the {}.',
    'a black and white photo of the {}.',
    'a low contrast photo of the {}.',
    'a high contrast photo of the {}.',
    'a bad photo of the {}.',
    'a good photo of the {}.',
    'a photo of the small {}.',
    'a photo of the big {}.',
]
```


Visual prompts

A visual mark can direct attention to a region.




Evaluating medical VLMs

Classification




(a) ImageNet Pretraining (b) ConVIRT Pretraining


Zero-shot classification




Visual grounding



Segmentation



Text-to-image retrieval



Natural language inference

Premise: Previously-seen pneumothorax is no longer visualized.

Hypothesis: No pneumothorax is seen.


Entailment

Vision–language–action models

Connecting visual understanding and language to robot control

Vision–language–action models

A VLA model uses visual observations and a language instruction to predict robot actions.



VLA approaches

Three approaches connect vision and language to robot control.

VLM / LLM as a high-level planner


Image / video generative models as a high-level planner

End-to-end vision-language-action models


VLM / LLM as a high-level planner

VLM / LLM as a high-level planner

Use semantic knowledge of a VLM to solve long-horizon robotic tasks.



A synthesized VLA architecture




Images and instructions provide scene and task information.

Robot-state features describe the robot's configuration, such as joint positions.

The illustrated action head refines noisy trajectories into continuous actions, conditioned on both inputs.

Conceptual synthesis of OpenVLA, GR00T, π0.5 and Helix 02; implementations differ.

RT-2: training a VLM to output actions



Robot demonstrations connect observations and instructions to robot commands.

At inference, decode action tokens, execute a command, and observe again.

VLA example: put the red block in the bowl

Illustrative task: observe, predict a command, execute it, and observe again.



1. Observe and grasp



2. Move toward the bowl




3. Release the block

Joint-Embedding Predictive Architectures

Learning representations by predicting missing information


JEPA: prediction in representation space

Predict a target representation from the available context.



The prediction loss compares features. The target encoder follows a moving average of the context encoder.

JEPA: The Original Blueprint



x, y: two related observations.
s□ ş□ their learned representations.

Pred: predict the target representation.

$$\tilde{s}_y = \mathrm{Pred}(s_x, z), \qquad E = D(s_y, \tilde{s}_y)$$


z: a choice among possibilities that x alone cannot determine.

Example: a car at a fork can turn left or right. Different z values represent those alternatives.

Vary z over Z: the blue region is a set of possible predicted features.

Low prediction error is not enough: retain feature information and limit what z can carry.

V-JEPA (Bardes et al., 2024)




I-JEPA example: predicting a hidden region

The predictor uses visible context and the target location.

Visible context



Full image for target encoder



1. Encode visible patches.

2. Predict features for the target location.

3. Match the target encoder’s features.

The learned prediction is a feature vector for the hidden region.

JEPA for video and robot planning

V-JEPA learns visual representations by predicting masked video features.

V-JEPA 2-AC adds actions as inputs to predict how a scene changes.

A planner can compare predicted outcomes with an image goal and select an action sequence.

