15-410

"...Arguably less wrong..."

Synchronization #3
Feb. 5, 2024

Dave Eckhardt

Synchronization

Project 1 due tonight

- Again, try not to use a late day
  - But if you do, please carefully read and follow the instructions

Project 2 expected out Wednesday

Outline

Synch 1

- Two building blocks
- Three requirements for critical-section algorithms
- Algorithms people *don't* use for critical sections

Synch 2

- How critical sections are really(?) implemented

Synch 3

- Condition variables
  - Under the hood
  - The atomic-sleep problem
- Semaphores, monitors – overview

Road Map

Two Fundamental operations

- ✔ Atomic instruction sequence
- ➪ Voluntary de-scheduling

Voluntary de-scheduling

The Situation

- You hold lock on shared resources
- But they're not in “the right mode”

Action sequence

- Unlock shared resources
- Write down “wake me up when...”
- Block until a relevant resource changes state

What *Not* To Do

```
reckoning = false;
while (!reckoning) {
  mutex_lock(&scenario_lk);
  if ((date >= 1906-04-18) &&
   (hour >= 5))
    reckoning = true;
  else
    mutex_unlock(&scenario_lk);
}
wreak_general_havoc();
mutex_unlock(&scenario_lk);
```

What *Not* To Do

Is this code correct?

```
reckoning = false;
while (!reckoning) {
  mutex_lock(&scenario_lk);
  if ((date >= 1906-04-18) &&
   (hour >= 5))
    reckoning = true;
  else
    mutex_unlock(&scenario_lk);
}
wreak_general_havoc();
mutex_unlock(&scenario_lk);
```

What *Not* To Do

Is this code *right*?

```
reckoning = false;
while (!reckoning) {
  mutex_lock(&scenario_lk);
  if ((date >= 1906-04-18) &&
   (hour >= 5))
    reckoning = true;
  else
    mutex_unlock(&scenario_lk);
}
wreak_general_havoc();
mutex_unlock(&scenario_lk);
```

What *Not* To Do

Why is this wrong?

- Make sure you understand!
- See previous two lectures
- Do *not* do this in P2 or P3
  - Not even if it is *really tempting* in P3

“Arguably Less Wrong”

```
while (!reckoning) {
  mutex_lock(&scenario_lk);
  if ((date >= 1906-04-18) &&
    (hour >= 5))
    reckoning = true;
  else {
    mutex_unlock(&scenario_lk);
    sleep(1);
  }
}
wreak_general_havoc();
mutex_unlock(&scenario_lk);
```

“Arguably Less Wrong”

Don't do this either

- How wrong is “sleep(1)”?

“Arguably Less Wrong”

Don't do this either

- How wrong is “sleep(1)”?
  - N-1 times it's much too short
  - Nth time it's much too long

“Arguably Less Wrong”

Don't do this either

- How wrong is “sleep(1)”?
  - N-1 times it's much too short
  - Nth time it's much too long
  - It's wrong *every time*

“Arguably Less Wrong”

Don't do this either

- How wrong is “sleep(1)”?
  - N-1 times it's much too short
  - Nth time it's much too long
  - It's wrong *every time*
- What's the problem?

“Arguably Less Wrong”

Don't do this either

- How wrong is “sleep(1)”?
  - N-1 times it's much too short
  - Nth time it's much too long
  - It's wrong *every time*
- What's the problem?
  - We don't really want to wait for some *duration*!
  - We want to wait for a *condition change*

“Honorable Mention”?

```
while (!reckoning) {
  mutex_lock(&scenario_lk);
  if ((date >= 1906-04-18) &&
    (hour >= 5))
    reckoning = true;
  else {
    mutex_unlock(&scenario_lk);
    yield(); // Better than sleep()????
  }
}
wreak_general_havoc();
mutex_unlock(&scenario_lk);
```

Something Is Missing...

✔ **"Protect shared state" is solved**

- We use a "mutex object"
- Also encapsulates "Which code interferes with this?"
- Good

➪ **How to solve "block for the right duration"?**

Something Is Missing...

✔ **"Protect shared state" is solved**

- We use a "mutex object"
- Also encapsulates "Which code interferes with this?"
- Good

➪ **How to solve "block for the right duration"?**

- Get an expert to tell us!
- Encapsulate "the right duration"...
  - ...into a *condition variable* object

Once More, With Feeling!

```
mutex_lock(&scenario_lk);
while (cvarp = wait_on()) {
  cond_wait(cvarp, &scenario_lk);
}
wreak_general_havoc(); /* locked! */
mutex_unlock(&scenario_lk);
```

wait_on()?

```
if (y < 1906)
  return (&new_year);
else if (m < 4)
  return (&new_month);
else if (d < 18)
  return (&new_day);
else if (h < 5)
  return (&new_hour);
else
  return (0); // done!

// Code is “conceptual example”, not 100% correct
```

What Awakens Us?

```
for (y = 1900; y < 2000; y++)
  cond_broadcast(&new_year);
  for (m = 1; m <= 12; m++)
    cond_broadcast(&new_month);
    for (d = 1; d <= days(m); d++)
      cond_broadcast(&new_day);
      for (h = 0; h < 24; h++)
        cond_broadcast(&new_hour);
        ...

// Code is “conceptual example”, not 100% correct
```

Condition Variable Requirements

Keep track of threads blocked "for a while"

Allow notifier thread(s) to unblock blocked thread(s)

Must be "thread-safe"

- Many threads may call condition_wait() at same time
- Many threads may call condition_signal() at same time
- Say, those look like "interfering sequences"...

Why *Two* Parameters?

```
condition_wait(&cvar, &mutex);
```

Mutex required to examine/modify the "world" state

- If you examine unlocked state, it's changing.

Whoever awakens you will need to hold that mutex

- So you'd better give it up.

When you wake up, you will need to hold it again

- "Convenient" for condition_wait() to un-lock/re-lock

But there's something more subtle

- Try to recall this issue when working on P2...

Inside a Condition Variable

cvar->queue

- of blocked threads
- FIFO, or more exotic

cvar->mutex

- Protects queue against interfering wait()/signal() calls
- This isn't the caller's mutex (locking caller's world state)
- This is our secret invisible mutex

Inside a Condition Variable

```
cond_wait(cvar, world_mutex)
{
  lock(cvar->mutex);
  enq(cvar->queue, my_thread_id());
  unlock(world_mutex);
  ATOMICALLY {
    unlock(cvar->mutex);
    kernel_please_pause_this_thread();
  }
  lock(world_mutex);
}
```

What is this "ATOMICALLY" stuff?

What We Hope For

cond_wait(m,c)	cond_signal(c)
enq(c->que,me);	
unlock(m);	
unlock(c->m);	
kern_thr_pause();	
	lock(c->m);
	id = deq(c->que);
	kern_thr_wake(id);
	unlock(c->m);

Pathological Execution Sequence

cond_wait(m,c)	cond_signal(c)
enq(c->que,me);	
unlock(m);	
unlock(c->m);	
	lock(c->m);
	id = deq(c->que);
	kern_thr_wake(id);
	unlock(c->m);
kern_thr_pause();	

kern_thr_wake(id) ⇒ ERR_NOT_ASLEEP

Achieving “wait() Atomicity”

Rules of the game

- There isn't an underlying unlock_and_block() primitive
  - Because we can't assume the thing we're building!

Achieving “wait() Atomicity”

Rules of the game

- There isn't an underlying unlock_and_block() primitive
- We have unlock(), and block(), and maybe “other stuff”
- From outside cond_wait()/cond_signal(), we must achieve *apparent* (as-if) “atomicity of unlock and block”.

Approaches

- Disable interrupts (if you are a kernel)
- Rely on OS to implement condition variables
  - (Why is this not the best idea?)
- Have a better kernel thread-block interface
- Hmmm....

Achieving “wait() Atomicity”

P2 challenges

- Understand the issues!
  - mutex, cvar
- Understand the host kernel we give you
- Put the parts together
  - Don't use “wrong” or “arguably less wrong” approaches!
  - Seek solid, clear solutions
    - There's more than one way to do it
    - Make sure to pick a correct way...
    - Try to pick a *good* way.

Outline

Last time

- How mutual exclusion is really implemented

Condition variables

- Under the hood
- The atomic-sleep problem

⇒ Semaphores

Monitors

Semaphore Concept

Semaphore is a different encapsulation object

- Can produce mutual exclusion
- Can produce block-until-it's-time

Intuition: counted resource

- Integer represents “number available”
  - Number of buffers, number of pairs of scissors, ...
  - Semaphore object initialized to a particular count
- Thread blocks until it is allocated an instance

Semaphore Concept

wait(), aka P(), Dutch probeer te verlagen ("try to decrease")

- wait until value > 0
- then decrement value ("taking" one instance)

signal(), aka V(), Dutch verhogen ("increase")

- increment value ("releasing" one instance)

Just one small issue...

- wait() and signal() *must be atomic*

“Mutex-style” Semaphore

```
semaphore m = 1;

do {
  wait(m);   // entry / mutex_lock()
  ..critical section...
  signal(m); // exit / mutex_unlock()

  ...remainder section...
} while (1);
```

“Condition-style” Semaphore

Thread 0	Thread 1
	`wait(c);`
`result = 42;`	
`signal(c);`	
	`use(result);`

“Condition with Memory”

Semaphores *retain memory* of signal() events

- **“full/empty bit” - *unlike* condition variables**

Thread 0	Thread 1
`result = 42;`	
`signal(c);`	
	`wait(c);`
	`use(result);`

Semaphore vs. Mutex/Condition

Good news

- Semaphore is a higher-level construct
- Integrates mutual exclusion, waiting
- Avoids mistakes common in mutex/condition API
  - signal() too early is “lost”
  - ...

Semaphore vs. Mutex/Condition

Bad news

- Semaphore is a higher-level construct
- Integrates mutual exclusion, waiting
  - Some semaphores are “mutex-like”
  - Some semaphores are “condition-like”

Semaphore vs. Mutex/Condition

Bad news

- Semaphore is a higher-level construct
- Integrates mutual exclusion, waiting
  - Some semaphores are “mutex-like”
  - Some semaphores are “condition-like”
  - How's a poor library to know?
    - Spin-wait or not???

Semaphores - 31 Flavors

Binary semaphore

- It counts, but only from 0 to 1!
  - "Available" / "Not available"
- Consider this a hint to the implementor...
  - "Think mutex!"

Non-blocking semaphore

- wait(semaphore, timeout);

Deadlock-avoidance semaphore

- #include <deadlock.lecture>

My Personal Opinion

One *"simple, intuitive"* synchronization object

- **In 31 performance-enhancing flavors!!!**

"The nice thing about standards is that you have so many to choose from."

- **Andrew S. Tanenbaum**

Conceptually simpler to have two objects

- **One for mutual exclusion**
- **One for waiting**
- **...after you've understood what's actually happening**

Semaphore Wait: Inside Story

```
wait(semaphore s)
  ACQUIRE EXCLUSIVE ACCESS
  --s->count;
  if (s->count < 0) {
    enqueue(s->queue, my_id());
    ATOMICALLY {
      RELEASE EXCLUSIVE ACCESS
      thread_block()
    }
  } else {
      RELEASE EXCLUSIVE ACCESS
  }
```

Semaphore Signal: Inside Story

```
signal(semaphore s)
  ACQUIRE EXCLUSIVE ACCESS
  ++s->count;
  if (s->count <= 0) {
    tid = dequeue(s->queue);
    thread_unblock(tid);
  }
  RELEASE EXCLUSIVE ACCESS
```

What's all the shouting?

- An exclusion algorithm much like a mutex, or
- OS-assisted atomic de-scheduling / awakening

Monitor

Basic concept

- Semaphores eliminate some mutex/condition mistakes
- Still some common errors
  - Swapping “signal()” & “wait()”
  - Accidentally omitting one

Monitor: higher-level abstraction

- Module of high-level language procedures
  - All access some shared state
- *Compiler* adds synchronization code
  - Thread running in any procedure blocks *all* thread entries

Monitor “Commerce”

```
int cash_in_till[N_STORES] = { 0 };
int wallet[N_CUSTOMERS] = { 0 } ;

boolean buy(int cust, store, price) {
  if (wallet[cust] >= price) {
    cash_in_till[store] += price;
    wallet[cust] -= price;
    return (true);
  } else
    return (false);
}
```

Monitors – What about waiting?

Automatic mutal exclusion is nice...

- **...but it is too strong**

Sometimes one thread needs to wait for another

- **Automatic mutual exclusion forbids this**
- **Must leave monitor, re-enter - *when?***

Have we heard this "when" question before?

Monitor Waiting – The Problem

```
void
stubbornly_cash_check(acct a, check c)
{
  while (account[a].bal < check.val) {
    ...Sigh, must wait for a while...
    ...But I'm holding “the mutex”...
    ...Uh-oh?  Need something else?...
  }
  account[a].bal -= check.val;
}
```

Monitor Waiting – Wrong Solution

```
boolean
try_cash_check(acct a, check c)
{
  if (account[a].bal < check.val)
    return (false); /* pass the buck */
  account[a].bal -= check.val;
  return (true);
}
```

Monitor condition variables

Similar to condition variables we've seen

condition_wait(cvar)

- Only one parameter
- Mutex-to-drop is implicit
  - (the “monitor mutex”)
- Operation
  - “Temporarily exit monitor” -- drop the mutex
  - Wait until signalled
  - “Re-enter monitor” - re-acquire the mutex

Monitor Waiting

```
void
stubbornly_cash_check(acct a, check c)
{
  while (account[a].bal < check.val) {
    cond_wait(account[a].activity);
  }
  account[a].bal -= check.val;
}
```

Q: Who would broadcast() on this cvar?

Monitor condition variables

signal() policy question - which thread to run?

- Signalling thread? Signalled thread?
  - Can argue either way
- Or: signal() *exits monitor* as side effect!
- Different signal() policies mean different monitor flavors

Summary

Two fundamental operations

- Mutual exclusion for must-be-atomic sequences
- Atomic de-scheduling (and then wakeup)

Mutex/condition-variable ("pthreads") style

- Two objects for two core operations

Semaphores, Monitors

- Semaphore: one object
- Monitor: invisible compiler-generated object
- *Same core ideas inside*

Summary

What you should know

- Issues/goals
- Underlying techniques
- How environment/application design matters

All done with synchronization?

- Only one minor issue left
  - Deadlock