

# Machine Learning

10-701/15-781, Spring 2008

## Reinforcement learning 1

Eric Xing

Lecture 27, April 28, 2008

Reading: Chap. 13, T.M. book

|   |       |   |   |         |
|---|-------|---|---|---------|
| 3 |       |   |   | $\pm 1$ |
| 2 |       |   |   | $-1$    |
| 1 | start |   |   |         |
|   | 1     | 2 | 3 | 4       |

Eric Xing



## Outline

- Intro to reinforcement learning
- MDP: Markov decision problem
- Dynamic programming:
  - Value iteration
  - Policy iteration

Eric Xing

2



## What is Learning?



- Learning takes place as a result of interaction between an **agent** and the **world**, the idea behind learning is that
  - Percepts received by an agent should be used not only for understanding/interpreting/prediction, as in the machine learning tasks we have addressed so far, but also for **acting**, and further more for improving the agent's ability to behave optimally in the future to achieve the goal.

Eric Xing

3

## Types of Learning



- Supervised Learning
  - A situation in which sample (input, output) pairs of the function to be learned can be perceived or are given
  - You can think it as if there is a kind teacher
    - Training data:  $(X, Y)$ . (features, label)
    - Predict  $Y$ , minimizing some loss.
    - **Regression, Classification.**
- Unsupervised Learning
  - Training data:  $X$ . (features only)
  - Find "similar" points in high-dim  $X$ -space.
  - **Clustering.**

Eric Xing

4

## Example of Supervised Learning



- Predict the price of a stock in 6 months from now, based on economic data. (Regression)
- Predict whether a patient, hospitalized due to a heart attack, will have a second heart attack. The prediction is to be based on demographic, diet and clinical measurements for that patient. (Logistic Regression)
- Identify the numbers in a handwritten ZIP code, from a digitized image (pixels). (Classification)



$$X \rightarrow y$$
$$\{x_i, y_i\}$$

Eric Xing

FIGURE 1.2. Examples of handwritten digits from U.S. postal envelopes.

5

## Example of Unsupervised Learning



- From the DNA micro-array data, determine which genes are most “similar” in terms of their expression profiles. (Clustering)



Eric Xing

6

## Types of Learning (Cont'd)

- Reinforcement Learning


- in the case of the agent acts on its environment, it receives some evaluation of its action (reinforcement), but is not told of which action is the correct one to achieve its goal

- Training data: (S, A, R). (State-Action-Reward)
- Develop an optimal policy (sequence of decision rules) for the learner so as to maximize its long-term reward.  $T_t(s) \rightarrow a_t$
- Robotics, Board game playing programs.

Eric Xing

7

## RL is learning from interaction



Eric Xing

8

## Examples of Reinforcement Learning


- How should a robot behave so as to optimize its “performance”? (Robotics)
- How to automate the motion of a helicopter? (Control Theory)
- How to make a good chess-playing program? (Artificial Intelligence)



Eric Xing

9

## Robot in a room



actions: UP, DOWN, LEFT, RIGHT

UP

80% move UP  
10% move LEFT  
10% move RIGHT



$$S_t = \{x_t, y_t\}$$

$$R = \{r_t\}$$

- ℳ.
- reward +1 at [4,3], -1 at [4,2]
  - reward -0.04 for each step

- what's the strategy to achieve max reward?
- what if the actions were deterministic?

Eric Xing

10

# History of Reinforcement Learning



- Roots in the **psychology of animal learning** (Thorndike, 1911).
- Another independent thread was the problem of **optimal control**, and its solution using **dynamic programming** (Bellman, 1957).
- Idea of **temporal difference** learning (on-line method), e.g., playing board games (Samuel, 1959).
- A major breakthrough was the discovery of **Q-learning** (Watkins, 1989).

Eric Xing

11

# What is special about RL?



- RL is learning how to map states to actions, so as to **maximize** a numerical **reward** over time.
- Unlike other forms of learning, it is a multistage decision-making process (often **Markovian**).
- An RL agent must learn by **trial-and-error**. (Not entirely supervised, but interactive)
- Actions may affect not only the immediate reward but also subsequent rewards (**Delayed effect**).

Eric Xing

12

## Elements of RL



- A **policy**
  - A map from **state space** to **action space**.
  - May be stochastic.
- A **reward function**
  - It maps each state (or, state-action pair) to a real number, called **reward**.
- A **value function**
  - Value of a state (or, state-action pair) is the **total expected reward**, starting from that state (or, state-action pair).



Eric Xing

13

## Policy



|   |   |   |    |
|---|---|---|----|
| → | → | → | +1 |
| ↑ |   | ↑ | -1 |
| ↑ | ← | ← | ←  |

Eric Xing

14

## Reward for each step -2



|   |   |   |    |
|---|---|---|----|
| → | → | → | +1 |
| ↑ |   | → | -1 |
| → | → | → | ↑  |

Eric Xing

15

## Reward for each step: -0.1



|   |   |   |    |
|---|---|---|----|
| → | → | → | +1 |
| ↑ |   | ↑ | -1 |
| ↑ | → | ↑ | ←  |

Eric Xing

16



## Reward for each step: -0.04



|  |  |  |    |
|--|--|--|----|
|  |  |  | +1 |
|  |  |  | -1 |
|  |  |  |    |

$V_t$

Eric Xing

17

## The Precise Goal



- To find a **policy** that maximizes the **Value function**.
  - transitions and rewards usually not available
- There are different approaches to achieve this goal in various situations.
- Value iteration and Policy iteration are two more classic approaches to this problem. But essentially both are **dynamic programming**.
- Q-learning is a more recent approaches to this problem. Essentially it is a **temporal-difference method**.

Eric Xing

18

# Markov Decision Processes



A Markov decision process is a tuple  $(S, A, \{P_{sa}\}, \gamma, R)$  where:

- $S$  is a set of **states**. (For example, in autonomous helicopter flight,  $S$  might be the set of all possible positions and orientations of the helicopter.)
- $A$  is a set of **actions**. (For example, the set of all possible directions in which you can push the helicopter's control sticks.)  $s \xrightarrow{a} s'$
- $P_{sa}$  are the state transition probabilities. For each state  $s \in S$  and action  $a \in A$ ,  $P_{sa}$  is a distribution over the state space. We'll say more about this later, but briefly,  $P_{sa}$  gives the distribution over what states we will transition to if we take action  $a$  in state  $s$ .
- $\gamma \in [0, 1)$  is called the **discount factor**.
- $R : S \times A \mapsto \mathbb{R}$  is the **reward function**. (Rewards are sometimes also written as a function of a state  $S$  only, in which case we would have  $R : S \mapsto \mathbb{R}$ ).

Eric Xing

19

## The dynamics of an MDP



- We start in some state  $s_0$ , and get to choose some action  $a_0 \in A$
- As a result of our choice, the state of the MDP randomly transitions to some successor state  $s_1$ , drawn according to  $s_1 \sim P_{s_0 a_0}$
- Then, we get to pick another action  $a_1$
- ...

$$s_0 \xrightarrow{a_0} s_1 \xrightarrow{a_1} s_2 \xrightarrow{a_2} s_3 \xrightarrow{a_3} \dots \dots \dots \text{goal}$$

$V(s_0)$   $\gamma$

Eric Xing

20

## The dynamics of an MDP, (Cont'd)



- Upon visiting the sequence of states  $s_0, s_1, \dots$ , with actions  $a_0, a_1, \dots$ , our total payoff is given by

$$R(s_0, a_0) + \gamma R(s_1, a_1) + \gamma^2 R(s_2, a_2) + \dots$$

- Or, when we are writing rewards as a function of the states only, this becomes

$$R(s_0) + \gamma R(s_1) + \gamma^2 R(s_2) + \dots$$

- For most of our development, we will use the simpler state-rewards  $R(s)$ , though the generalization to state-action rewards  $R(s; a)$  offers no special difficulties.

- Our goal in reinforcement learning is to choose actions over time so as to maximize the expected value of the total payoff:

$$V(s_0) = E[R(s_0) + \gamma R(s_1) + \gamma^2 R(s_2) + \dots]$$

Eric Xing

21

## Policy



- A policy is any function  $\pi : S \mapsto A$  mapping from the states to the actions.
- We say that we are executing some policy if, whenever we are in state  $s$ , we take action  $a = \pi(s)$ .
- We also define the value function for a policy  $\pi$  according to

$$V^\pi(s) = E[R(s_0) + \gamma R(s_1) + \gamma^2 R(s_2) + \dots \mid s_0 = s, \pi]$$

$V^\pi(s)$

- $V^\pi(s)$  is simply the expected sum of discounted rewards upon starting in state  $s$ , and taking actions according to  $\pi$ .



Eric Xing

22

# Value Function

- Given a fixed policy  $\pi$ , its value function  $V^\pi$  satisfies the **Bellman equations**:

$$V^\pi(s) = R(s) + \gamma \sum_{s' \in S} P_{s\pi(s)}(s') V^\pi(s')$$

Immediate reward

expected sum of future discounted rewards

$s_1 \quad V(s) = R(s) + \gamma V^\pi$   
 $s_2 \quad \text{---}$   
 $\vdots \quad \text{---}$   
 $s_k \quad \text{---}$   
 $\vec{V}^\pi = \vec{R} + \gamma \vec{P} \vec{V}^\pi$

- Bellman's equations can be used to efficiently solve for  $V^\pi$  (see later)

$$V^\pi(s) \geq V^\pi(s) \quad \forall \pi.$$

Eric Xing

23

# The Grid world

M = 0.8 in direction you want to go  
 0.2 in perpendicular  $\begin{cases} 0.1 \text{ left} \\ 0.1 \text{ right} \end{cases}$

Policy: mapping from states to actions

An optimal policy for the stochastic environment:

|   |   |   |   |    |
|---|---|---|---|----|
| 3 | → | → | → | +1 |
| 2 | ↑ |   | ↑ | -1 |
| 1 | ↑ | ← | ← | ←  |
|   | 1 | 2 | 3 | 4  |

$$V_{3,3} = -0.04 + 1 \times 0.8 + 0.66 \times 0.1 + 0.592 \times 0.1 = 0.912$$

utilities of states:

|   |       |       |       |       |
|---|-------|-------|-------|-------|
| 3 | 0.812 | 0.868 | 0.912 | +1    |
| 2 | 0.762 |       | 0.660 | -1    |
| 1 | 0.705 | 0.655 | 0.611 | 0.388 |
|   | 1     | 2     | 3     | 4     |

Environment  $\begin{cases} \text{Observable (accessible): percept identifies the state} \\ \text{Partially observable} \end{cases}$

*Markov property*: Transition probabilities depend on state only, not on the path to the state.

Markov decision problem (MDP).

Partially observable MDP (POMDP): percepts does not have enough info to identify transition probabilities.

$$K = -0.04$$

Eric Xing

24

## Optimal value function



- We define the optimal value function according to

$$V^*(s) = \max_{\pi} V^{\pi}(s) \quad (1)$$

- In other words, this is the best possible expected sum of discounted rewards that can be attained using any policy
- There is a version of Bellman's equations for the optimal value function:

$$V^*(s) = R(s) + \max_{a \in A} \gamma \sum_{s' \in S} P_{sa}(s') V^*(s') \quad (2)$$

- Why?

## Optimal policy



- We also define a policy :  $\pi^* : S \mapsto A$  as follows:

$$\pi^*(s) = \arg \max_{a \in A} \sum_{s' \in S} P_{sa}(s') V^*(s') \quad (3)$$

- Fact:

- $V^*(s) = V^{\pi^*}(s) \geq V^{\pi}(s)$
- Policy  $\pi^*$  has the interesting property that it is the optimal policy for all states  $s$ .
  - It is not the case that if we were starting in some state  $s$  then there'd be some optimal policy for that state, and if we were starting in some other state  $s_0$  then there'd be some other policy that's optimal policy for  $s_0$ .
  - The same policy  $\pi^*$  attains the maximum above for all states  $s$ . This means that we can use the same policy no matter what the initial state of our MDP is.

## The Basic Setting for Learning



- **Training data:**  $n$  finite horizon trajectories, of the form  $\{s_0, a_0, r_0, \dots, s_T, a_T, r_T, s_{T+1}\}$ .
- **Deterministic or stochastic policy:** A sequence of decision rules  $\{\pi_0, \pi_1, \dots, \pi_T\}$ .
- Each  $\pi$  maps from the observable history (states and actions) to the action space at that time point.

Eric Xing

27

## Algorithm 1: Value iteration



- Consider only MDPs with finite state and action spaces ( $|S| < \infty, |A| < \infty$ )
- The value iteration algorithm:
  1. For each state  $s$ , initialize  $V(s) := 0$ .
  2. Repeat until convergence {
    - For every state, update
 
$$V(s) := R(s) + \max_{a \in A} \gamma \sum_{s' \in S} P_{sa}(s') V^*(s').$$

*(Handwritten note:  $V = R(s) + \gamma \sum P_{sa}(s') V^*(s')$   $\Rightarrow V^*(s)$ )*
- **synchronous update**
- **asynchronous updates**
- It can be shown that value iteration will cause  $V$  to converge to  $V^*$ . Having found  $V^*$ , we can then use Equation (3) to find the optimal policy.

Eric Xing

28

## Algorithm 2: Policy iteration


- The policy iteration algorithm:  $\pi^0 \rightarrow V^{\pi^0} \rightarrow \pi^1 \rightarrow V^{\pi^1} \rightarrow \pi^2 \dots$ 
  1. Initialize  $\pi$  randomly.
  2. Repeat until convergence {
    - Let  $V := V^\pi$
    - For each state  $s$ , let  $\pi(s) := \arg \max_{a \in A} \sum_{s' \in S} P_{sa}(s') V^*(s')$ .
- The inner-loop repeatedly computes the value function for the current policy, and then updates the policy using the current value function.
- Greedy update
- After at most a finite number of iterations of this algorithm,  $V$  will converge to  $V^*$ , and  $\pi$  will converge to  $\pi^*$ .

Eric Xing

29

## Convergence

- The utility values for selected states at each iteration step in the application of VALUE-ITERATION to the 4x3 world in our example




|   |       |   |   |    |
|---|-------|---|---|----|
| 3 |       |   |   | +1 |
| 2 |       |   |   | -1 |
| 1 | start |   |   |    |
|   | 1     | 2 | 3 | 4  |

Thrm: As  $t \rightarrow \infty$ , value iteration converges to exact  $U$  even if updates are done asynchronously &  $i$  is picked randomly at every step.

Eric Xing

30

# Convergence



**Figure 17.6** (a) The RMS (root mean square) error of the utility estimates compared to the correct values, as a function of iteration number during value iteration. (b) The expected policy loss compared to the optimal policy.

When to stop value iteration?



Eric Xing

31

## Summary

- Both value iteration and policy iteration are standard algorithms for solving MDPs, and there isn't currently universal agreement over which algorithm is better.
- For small MDPs, policy iteration is often very fast and converges with very few iterations. However, for MDPs with large state spaces, solving for  $V$  explicitly would involve solving a large system of linear equations, and could be difficult.
- In these problems, value iteration may be preferred. For this reason, in practice value iteration seems to be used more often than policy iteration.

Eric Xing

32