
Assembler Fundamentals

15-123


Systems Skills in C and Unix

Some background Stuff

Programs are Translated into binaries



Programs are Translated into byte code



Demo code

Byte code versus assembly code

```
#<main>
00 00
                  # number of arguments = 0
00 00
                  # number of local variables = 0
00 06
                  # code length = 6 bytes
10 19
         # bipush 25
                           # 25
                           # 36
10 24
         # bipush 36
         # iadd
                           \# (25 + 36)
60
         # return
B0
```

```
movl $25, -8(%rbp)
movl $36, -4(%rbp)
movl -4(%rbp), %edx
movl -8(%rbp), %eax
addl %edx, %eax
leave
ret
```

Register based vs stack based

Instructions are directly executed on registers


Instructions are "safely" executed on virtual machine

Functions as data

- Virtual machines (VM) treat programs as data
- Program is a file of bytes
- VM has a stack based model of implementation
- Each function call uses its own stack to execute the instructions
- The machine hardware only executes the VM instructions
- No program instructions get executed by hardware

Some other details

All programs get executed



Cost of computing is important

- Moving data is expensive
- Large storage devices are slower than smaller storage devices (hard drive vs RAM)
 - Capacity: RAM/hard drive = 1/100
 - Access : RAM/Hard drive = 1/10,000,000
- RAM versus Registers
 - Capacity: Register/RAM = 32 bits/2 GB
 - Access: Register:RAM access = 100:1


Speeding up with Cache can help

- Cache memories
 - Smaller faster storage devices
 - Stores data that the processor is likely to need in the near future
 - Cache memory is directly connected through bus interface
 - Goal is to make cache memory access as fast as register access

Understanding Instruction SetArchitecture

Instruction set architecture

 provides a perspective of the processor from assembly language or machine language programmer's point of view.



Instruction set architecture

- ISA describes the *instructions that processor understands*, including register set and how the memory is organized.
- A real world processor ISA would include few additional items such as data types; interrupt handlers, exception handling etc. *ISA* is part of the computer architecture specific to a particular hardware.

Registers

- Registers are special purpose memory locations
- Most assembly instructions directly operate on registers
 - loading data into registers from memory
 - performing operations on data and storing data back in memory
- The registers are named like
 - eax, ebx, ecx
 - ebp and esp for manipulating the base pointer and stack pointer
- The size of a register (say 32-bit) and number of registers (say 8) depends on particular computer architecture.
- A typical register instruction in assembly
 - movl \$10, %eax

A Hypothetical Machine

Register	Number	Notes
Z	000	Constant: Always zero (0)
A	001	
В	010	
C	011	
D	100	
E	101	
F	110	
G	111	
PC		Program Counter. 24 bits wide. Not addressable
IR		Instruction Register. 32 bits wide. Not addressable.

Question: How many addressable units are in our memory model? Answer based on PC

Basic Instructions

- The basic instructions for a computer are
 - branch instructions
 - jmp
 - I/O instructions
 - Load and save
 - Arithmetic instructions
 - add, mul
 - Device instructions
 - Read, write
 - comparison instructions
 - If(x > y)

Instructions

124

Function
Read Port into Reg0
Write Reg0 out to Port

CONTROL	INST	RUCTIONS				
Instruction		Rections		Address		Function
HLT		XXXX XXXX	XXXXXXX	XX XXXX X	XXX XXXX	Stop simulation
JMP	0001	0000 AAAA	AAAA AAA	A AAAA AA	AA AAAA	Jump (line number)
CJMP	0010	0000 AAAA	AAAA AAA	A AAAA AA	AÀ AAAA	Jump if true
OJMP	0011	0000 AAAA A	AAAA AAA	A AAAA AA	AA AAAA	Jump if overflow
		NSTRUCTION	NS			
Instruction	Op	Register		Value		Function
LOAD	0100	ORRR AAAA	AAAA AAA	AA AAAA AA	AAA AAAA	Load (hex address)
STORE	0101	ORRR AAAA	AAAA AAA	AA AAAA AA	AAA AAAA	Store (hex address)
LOADI	0110	ORRR 0000 00	000 1111 1111 1	III IIII		Load Immediate
NOP	0111	0000 0000 000	00 0000 0000	0000 0000		no operation
MATH INS	TRHC	TIONS				

MATH INSTRUCTIONS

Instruction	Op Reg0 Reg1 Reg2	Function
ADD	1000 ORRR ORRR ORRR 0000 0000 0000 0000	Reg0 = (Reg1 + Reg2)
SUB	1001 ORRR ORRR ORRR 0000 0000 0000 0000	Reg0 = (Reg1 - Reg2)


DEVICE I/O


Instruction	-Op- Reg0	0000 0000 0000 0000 0000	000	Port
IN	1010 ORRR	0000 0000 0000	0000	PPPP PPPP
OUT	1011 0RRR	0000 0000 0000	0000	PPPP PPPP

COMPARISON


	Instruction	-Op-Reg0	Keg1		Function
i	EQU	1100 ORRR	ORRR 0000	0 0000 0000 0000 0000	Cflg = (Reg0 == Reg1)
	LT	1101 ORRE	ORRK 0000	0000 0000 0000 0000	Cflg = (Reg0 < Reg1)
	LTE			0000 0000 0000 0000	$Cflg = (Reg0 \le Reg1)$
	NOT	1111 0000	0000 0000	0000 0000 0000 0000	Cflg = (!Cflg)

Sample program















From assembly to object code

0	LOADI	A	1		
1	LOADI	B	48		
2	IN		С	0	- 8
3	SUB		D	C	В
4	IN		C	0	
5	SUB		E	С	В
6	LTE	D	E		
7	NOT				
8	CJMP	{Line	13}		
9	ADD		C	D	В
10	TUO (С	15	
11	ADD		D	D	Α
13	HLT				

- 1. 0x61000001
- 2. 0x62000030
- 3. oxA3000000
- 4. 0X94320000
- 5. oxA3000000
- 6. 0x95320000
- 7. oxE4500000
- 8. oxFoooooo
- 9. 0X20000034
- 10. 0x83420000
- 11. oxB300000F
- 12. 0x84410000
- 13. 0X10000018
- 14. OXOOOOOOO

instructions gets loaded into registers



Exercises class activity

Exercise 1

• Write a program to add the numbers 2 and 5 and output to port #15 (output port). Then convert to machine code.

Write program that reads a single digit integer from keyboard and output.

Write a program that reads a single digit integer from keyboard and output the number if the number is greater or equal to 5.


Write a program that reads a single digit integer from keyboard and output all numbers between 1 and number

Simulation

How to think about a simulator

- 1. ox61000001
- **2.** 0x62000030
- 3. oxA3000000
- 4. 0X94320000
- 5. oxA3000000
- 6. 0x95320000
- 7. oxE4500000
- 8. oxFoooooo
- 9. 0X20000034
- 10. 0x83420000
- 11. oxB300000F
- 12. ox84410000
- 13. 0X10000018
- 14. 0X00000000

Instructions in RAM



Simulator hardware

Components

- An array of eight 32-bit registers
- A 32-bit register for IR and a 24-bit register for PC
- An array of bytes to simulate RAM. Each instruction takes 32-bytes
 - How much memory is needed based on PC?

Object Code Parser

- Load the instruction to IR
 - 0x61000001
- Parse the instruction using bit masks to extract the meaning ox61000001
- Execute the instruction LOADI A 1
 - Load 1 to register A

Code and Data

Code and Data are inseparable


• A 160 character C program that computes the first 800 digits of pi.

```
int a=10000,b,c=2800,d,e,f[2801],g;main(){for(;b-c;)f[b++]=a/5; for(;d=0,g=c*2;c-14,printf("%.4d",e+d/a),e=d%a)for(b=c;d+=f[b]*a, f[b]=d%-g,d/=g--,--b;d*=b);}
```

Loading code/data from memory

- 1. 0x61000001
- 2. ox62000030
- 3. oxA3000000
- 4. 0X94320000
- 5. oxA3000000
- 6. 0x95320000
- 7. oxE4500000
- 8. oxFoooooo
- 9. 0X20000034
- 10. 0x83420000
- 11. oxB300000F
- 12. 0x84410000
- 13. 0X10000018
- 14. 0X00000000
- 14. 0X00000001
- 15. 0X00010010
- 16. 0X00010011
- 17. 0X01001001
- 18. 0X10010010


LOAD Register hex-address



Storing data in memory


- 1. 0x61000001
- 2. ox62000030
- 3. oxA3000000
- 4. 0X94320000
- 5. oxA3000000
- 6. ox95320000
- 7. oxE4500000
- 8. oxFoooooo
- 9. 0X20000034
- 10. 0x83420000
- 11. oxB300000F
- 12. 0x84410000
- 13. 0X10000018
- 14. 0X00000000
- 14. 0X00000001
- 15. 0X00010010
- 16. 0X00010011
- 17. 0X01001001
- 18. 0X10010010

STORE Register hex-address



Code and Data

- 1. ox61000001
- 2. 0x62000030
- 3. oxA3000000
- 4. 0X94320000
- 5. oxA3000000
- 6. 0x95320000
- 7. oxE4500000
- 8. oxFoooooo
- 9. 0X20000034
- 10. 0x83420000
- 11. oxB300000F
- 12. 0x84410000
- 13. 0X10000018
- 14. 0X00000000
- 14. 0X00000001
- 15. 0X00010010
- 16. 0X00010011
- 17. 0X01001001
- 18. ox10010010



Coding Examples