

Latent Variable Models and Signal Separation


Class 13. 11 Oct 2012

11-755 MLSP: Bhaskara Raj


Template Sounds Combine to Form a Signal

- The individual component sounds “combine” to form the final complex sounds that we perceive
- Notes form music
- Phoneme-like structures combine in utterances
- Sound in general is composed of such “building blocks” or themes
- Which can be simple – e.g. notes, or complex, e.g. phonemes
- Our definition of a building block: the entire structure occurs repeatedly in the process of forming the signal
- Claim: Learning the building blocks enables us to manipulate sounds


3



- A piece of music from the same (and a few additional) notes



- Chords from the same notes



- A sequence of notes

Sounds – an example

11-755 MLSP: Bhaskara Raj


- A common problem: Separate or enhance sounds
- Speech from noise
- Suppress “bleed” in music recordings
- Separate music components..
- A popular approach: Can be done with pots, pans, marbles and expectation maximization
- Probabilistic latent component analysis
- Tools are applicable to other forms of data as well..

Sound separation and enhancement




- A person drawing balls from a pair of urns
- Each ball has a number marked on it
- You only hear the number drawn
- No idea of which urn it came from
- Estimate various facets of this process..

The Mixture Multinomial



- A proper speech utterance from the same sounds



- A sequence of sounds

Sounds – an example

11-755 MLSP: Bhaskara Raj

5

More complex: TWO pickers

- Two different pickers are drawing balls from the same pots
- After each draw they call out the number and replace the ball
- They select the pots with different probabilities
- From the numbers they call we must determine
- Probabilities with which each of them select pots
- The distribution of balls within the pots



Solution

- Analyze each of the callers separately
- Compute the probability of selecting pots separately for each caller
- But *combine* the counts of balls in the pots!!



Recap with only one picker and two pots

- Probability of Red urn:
 - $P(1 | \text{Red}) = 1.71/7.31 = 0.234$
 - $P(2 | \text{Red}) = 0.56/7.31 = 0.077$
 - $P(3 | \text{Red}) = 0.66/7.31 = 0.090$
 - $P(4 | \text{Red}) = 1.32/7.31 = 0.181$
 - $P(5 | \text{Red}) = 0.66/7.31 = 0.090$
 - $P(6 | \text{Red}) = 2.40/7.31 = 0.328$
- Probability of Blue urn:
 - $P(1 | \text{Blue}) = 1.29/11.69 = 0.122$
 - $P(2 | \text{Blue}) = 0.56/11.69 = 0.322$
 - $P(3 | \text{Blue}) = 0.66/11.69 = 0.125$
 - $P(4 | \text{Blue}) = 1.32/11.69 = 0.250$
 - $P(5 | \text{Blue}) = 0.66/11.69 = 0.125$
 - $P(6 | \text{Blue}) = 2.40/11.69 = 0.056$
- $P(Z=\text{Red}) = 7.31/18 = 0.41$
- $P(Z=\text{Blue}) = 10.69/18 = 0.59$

Called	P(red X)	P(blue X)
6	.8	.2
1	.57	.43
2	.14	.86
6	.8	.2
4	.33	.67
3	.33	.67
4	.33	.67
2	.14	.86
1	.57	.43
2	.14	.86
5	.33	.67
4	.33	.67
3	.33	.67
2	.14	.86
6	.8	.2
Called	P(red X)	P(blue X)

7.31

10.69

23

TWO pickers



- Probability of drawing a number X for the first picker:
 - $P_1(X) = P_1(\text{red}) * P(X | \text{red}) + P_1(\text{blue}) * P(X | \text{blue})$
 - Probability of drawing X for the second picker
 - $P_2(X) = P_2(\text{red}) * P(X | \text{red}) + P_2(\text{blue}) * P(X | \text{blue})$
- Problem: Given the set of numbers called out by both pickers estimate
- $P_1(\text{color})$ and $P_2(\text{color})$ for both colors of X
- $P(X | \text{red})$ and $P(X | \text{blue})$ for all values of X

With TWO pickers

Called	P(red X)	P(blue X)
6	.8	.2
1	.57	.43
2	.14	.86
6	.8	.2
4	.33	.67
3	.33	.67
4	.33	.67
2	.14	.86
1	.57	.43
2	.14	.86
5	.33	.67
4	.33	.67
3	.33	.67
2	.14	.86
6	.8	.2
Called	P(red X)	P(blue X)

PICKER 1

7.31

10.69

11-755 MUI.SP: Bhaskara Raj

- Two tables
- The probability of selecting pots is independently computed for the two pickers

Called	P(red X)	P(blue X)
5	.57	.43
6	.90	.10
1	.75	.25
2	.27	.73
3	.57	.43
4	.57	.43
4	.57	.43
Called	P(red X)	P(blue X)

PICKER 2


4.20

2.80

11-755 MUI.SP: Bhaskara Raj

■ We shall see..

- We represent signals spectrographically
- Sequence of magnitude spectral vectors estimated from (overlapping) segments of signal
- Computed using the short-time Fourier transform
- Note: Only retaining the magnitude of the STFT for operations
- We will, need the phase later for conversion to a signal



The representation

Signal Separation with the Urn model

- What does the probability of drawing balls from Urns have to do with sounds?
- Or Images?

Called	P(blue X)	6	.8	.2
4	.33	.67	.57	.43
3	.33	.67	.57	.43
2	.14	.86	.14	.86
1	.57	.43	.57	.43
4	.33	.67	.57	.43
5	.33	.67	.57	.43
6	.8	.2	.57	.43


Called	P(red X)	6	.8	.2
4	.33	.67	.57	.43
3	.33	.67	.57	.43
2	.14	.86	.14	.86
1	.57	.43	.57	.43
4	.33	.67	.57	.43
5	.33	.67	.57	.43
6	.8	.2	.57	.43

- Red:
 - Total count for "Red": 11.51
 - Total count for 1: 2.46
 - Total count for 2: 0.83
 - Total count for 3: 1.23
 - Total count for 4: 2.46
 - Total count for 5: 1.23
 - Total count for 6: 3.30
- P(6|RED) = 3.3 / 11.51 = 0.29

With TWO pickers: The SECOND picker

Called	P(blue X)	6	.8	.2
4	.33	.67	.57	.43
3	.33	.67	.57	.43
2	.14	.86	.14	.86
1	.57	.43	.57	.43
4	.33	.67	.57	.43
5	.33	.67	.57	.43
6	.8	.2	.57	.43

Called	P(blue X)	6	.8	.2
4	.33	.67	.57	.43
3	.33	.67	.57	.43
2	.14	.86	.14	.86
1	.57	.43	.57	.43
4	.33	.67	.57	.43
5	.33	.67	.57	.43
6	.8	.2	.57	.43



With TWO pickers

- Given a sequence of observations $O_{k1}, O_{k2}, \dots$ from the k^{th} picker
 - N_{kX} is the number of observations of color X drawn by the k^{th} picker
 - Initialize $P_k(Z), P(X|Z)$ for pots Z and colors X
 - Iterate:
 - For each Color X , for each pot Z and each observer k :

$$P_k(Z|X) = \frac{P(X|Z)P_k(Z)}{\sum_{Z'} P_k(Z')P_k(Z)}$$
 - Update probability of numbers for the pots:

$$P(X|Z) = \frac{\sum_{k=1}^K N_{kX} P_k(Z|X)}{\sum_{k=1}^K N_{kX} P_k(Z|X)}$$
 - Update the mixture weights: probability of urn selection for each picker

$$P_k(Z) = \frac{\sum_{X=1}^X N_{kX} P_k(Z|X)}{\sum_{X=1}^X N_{kX} P_k(Z|X)}$$

In Squigles

Called	P(blue X)	6	.8	.2
4	.33	.67	.57	.43
3	.33	.67	.57	.43
2	.14	.86	.14	.86
1	.57	.43	.57	.43
4	.33	.67	.57	.43
5	.33	.67	.57	.43
6	.8	.2	.57	.43

- To compute probabilities of numbers **combine** the tables
- Total count of Red: 11.51
- Total count of Blue: 13.49

Called	P(blue X)	6	.8	.2
4	.33	.67	.57	.43
3	.33	.67	.57	.43
2	.14	.86	.14	.86
1	.57	.43	.57	.43
4	.33	.67	.57	.43
5	.33	.67	.57	.43
6	.8	.2	.57	.43

With TWO pickers


A Multinomial Model for Spectra

- A generative model for one frame of a spectrogram
 - A magnitude spectral vector obtained from a DFT represents spectral magnitude against discrete frequencies
 - This may be viewed as a histogram of draws from a multinomial
 - The balls are marked with discrete frequency indices from the DFT
- Probability distribution underlying the t -th spectral vector
- Power spectrum of frame t
- FRAME
- FRAME
- HISTOGRAM
- HISTOGRAM

11-755 MLSP: Bhaskara Raj

The Picker Generates a Spectrogram



- The picker has a fixed set of Urns
- Each urn has a different probability distribution over f
- He draws the spectrum for the first frame
- In which he selects urns according to some probability $P_0(z)$
- Then draws the spectrum for the second frame
- In which he selects urns according to some probability $P_1(z)$
- And so on, until he has constructed the entire spectrogram





11-755 MLSP: Bhaskara Raj

The Picker Generates a Spectrogram

- The picker has a fixed set of Urns
- Each urn has a different probability distribution over f
- He draws the spectrum for the first frame
- In which he selects urns according to some probability $P_0(z)$
- Then draws the spectrum for the second frame
- In which he selects urns according to some probability $P_1(z)$
- And so on, until he has constructed the entire spectrogram





- The picker has a fixed set of Urns
- Each urn has a different probability distribution over f
- He draws the spectrum for the first frame
- In which he selects urns according to some probability $P_0(z)$
- Then draws the spectrum for the second frame
- In which he selects urns according to some probability $P_1(z)$
- And so on, until he has constructed the entire spectrogram



The Picker Generates a Spectrogram


- The picker has a fixed set of Urns
- Each urn has a different probability distribution over f
- He draws the spectrum for the first frame
- In which he selects urns according to some probability $P_0(z)$
- Then draws the spectrum for the second frame
- In which he selects urns according to some probability $P_1(z)$
- And so on, until he has constructed the entire spectrogram




11-755 MLSP: Bhaskara Raj

A more complex model

- A "picker" has multiple urns
- In each draw he first selects an urn, and then a ball from the urn
- Overall probability of drawing f is a *mixture multinomial*
 - Since several multinomials (urns) are combined
- The probability of frequencies with which he selects any urn, and multiple draws



- By “learning” the mixture multinomial model for any sound source we “discover” these latent spectral structures for the source
- The model can be learnt from spectrograms of a small amount of audio from the source using the EM algorithm



Spectral View of *Component Multinomials*


$$P_i(f) = \sum_z P_i(z) P(f|z)$$

Frame(time) specific mixture weight

Frame-specific spectral distribution

SOURCE specific bases


- The URNs are the same for every frame
- These are the *component multinomials* or *bases* for the source that generated the signal
- The only difference between frames is the probability with which he selects the urns



The Picker Generates a Spectrogram


- Component multinomials represent latent spectral structures (bases) for the given sound source
- The spectrum for every analysis frame is explained as an additive combination of these latent spectral structures

- Each component multinomial (urn) is actually a normalized histogram over frequencies $P(f|z)$ i.e. a spectrum




Spectral View of *Component Multinomials*

- The picker has a fixed set of Urns
- Each urn has a different probability distribution over f
- He draws the spectrum for the first frame
- In which he selects urns according to some probability $P_i(z)$
- Then draws the spectrum for the second frame
- In which he selects urns according to some probability $P_i(z)$
- And so on, until he has constructed the entire spectrogram



The Picker Generates a Spectrogram

- The picker has a fixed set of Urns
- Each urn has a different probability distribution over f
- He draws the spectrum for the first frame
- In which he selects urns according to some probability $P_i(z)$
- Then draws the spectrum for the second frame
- In which he selects urns according to some probability $P_i(z)$
- And so on, until he has constructed the entire spectrogram
- The number of draws in each frame represents the RMS energy in that frame



The Picker Generates a Spectrogram

- Initialize bases
- $P(f|z)$ for all z , for all f
- Must decide on the number of urns
- For each frame
- Initialize $P_i(z)$



EM learning of bases

EM Update Equations

- Iterative process:
 - Compute a posteriori probability of the z^{th} urn for the source for each f

$$P(z|f) = \frac{P(z)P(f|z)}{\sum_z P(z)P(f|z)}$$

- Compute mixture weight of z^{th} urn


$$P_z(z) = \frac{\sum_f P_z(z|f)S_f(f)}{\sum_f P_z(z|f)S_f(f)}$$

$$P(f|z) = \frac{\sum_f P_z(z|f)S_f(f)}{\sum_f P_z(z|f)S_f(f)}$$

- Compute the probabilities of the frequencies for the z^{th} urn

11-755 MLSP: Bhaskara Raj

How the bases compose the signal





- The overall signal is the sum of the contributions of individual urns
 - Each urn contributes a different amount to each frame
- The contribution of the z -th urn to the t -th frame is given by

$$P(f|z)P_z(z)S_t$$
 - $S_t = \sum_f S_t(f)$


11-755 MLSP: Bhaskara Raj

Learning Structures



11-755 MLSP: Bhaskara Raj


The bag of spectrograms



- Drawing procedure
 - Fundamentally equivalent to bag of frequencies model
 - With some minor differences in estimation

11-755 MLSP: Bhaskara Raj

Estimating the bag of spectrograms



- EM update rules
 - Can learn all parameters
 - Can learn $P(T|Z)$ and $P(Z)$ only given $P(f|Z)$
 - Can learn only $P(Z)$

11-755 MLSP: Bhaskara Raj


How meaningful are these structures

- Are these really the “notes” of sound
- **To investigate, lets go back in time..**

11-755 MUI.SP: Bhaskha Raj

The Engineer and the Musician

Once upon a time a rich potentate discovered a previously unknown recording of a beautiful piece of music. Unfortunately it was badly damaged.



He greatly wanted to find out what it would sound like if it were not.


So he hired an engineer and a musician to solve the problem..



11-755 MUI.SP: Bhaskha Raj

The Engineer and the Musician

The engineer worked for many years. He spent much money and published many papers.



Finally he had a somewhat scratchy restoration of the music..



The musician listened to the music carefully for a day, transcribed it, broke out his trusty keyboard and replicated the music.



11-755 MUI.SP: Bhaskha Raj

The Engineer and the Musician

Camogie Mellon

- The Engineer works on the signal
- **Restore** it

- The musician works on his familiarity with music
- He knows how music is composed
- He can identify notes and their cadence
- But took many years to learn these skills
- He uses these skills to **recompose** the music

11-755 MUI.SP: Bhaskha Raj

What the musician can do

- Notes are distinctive
- The musician knows notes (of all instruments)
- He can
 - *Detect notes in the recording*
 - Even if it is scratchy
 - Reconstruct damaged music
 - *Transcribe individual components*
 - Reconstruct separate portions of the music

11-755 MUI.SP: Bhaskha Raj

Who do you think won the princess?




Music over a telephone

- The King actually got music over a telephone
- The musician must restore it..
- **Bandwidth Expansion**
 - Problem: A given speech signal only has frequencies in the 300Hz-3.5kHz range
 - Telephone quality speech
 - Can we estimate the rest of the frequencies

Bandwidth Expansion


- The picker has drawn the histograms for every frame in the signal



11-755 MLSP: Bhaskar Raj

Bandwidth Expansion


- The picker has drawn the histograms for every frame in the signal



11-755 MLSP: Bhaskar Raj

Bandwidth Expansion


- The picker has drawn the histograms for every frame in the signal



11-755 MLSP: Bhaskar Raj

Bandwidth Expansion

- The picker has drawn the histograms for every frame in the signal




11-755 MLSP: Bhaskar Raj

- However, we are only able to observe the number of draws of some frequencies and not the others
- We must estimate the draws of the unseen frequencies

Bandwidth Expansion: Step 1 – Learning

- From a collection of **full-bandwidth** training data, that are similar to the bandwidth-reduced data, learn spectral bases




- Using the procedure described earlier
- Each magnitude spectral vector is a mixture of a common set of bases
- Use the EM to learn bases from them
- Basically learning the “notes”

11-755 MLSP: Bhaskar Rao

- Using *only the observed frequencies* in the bandwidth-reduced data, estimate mixture weights for the bases learned in step 1
- Find out which notes were active at what time

11-755 MLSP: Bhaskar Rao



Bandwidth Expansion: Step 2 – Estimation

Step 2

- Iterative process: “Transcribe”
- Compute a posteriori probability of the z^{th} urn for the speaker for each f

$$p_f(z|f) = \frac{p_f(z)p(f|z)}{\sum_{z'} p_f(z')p(f|z')}$$


- Compute mixture weight of z^{th} urn for each frame t

$$p_f(z) = \frac{\sum_{f \in (\text{observed frequencies})} p_f(z|f)p(f|z)}{\sum_{f \in (\text{observed frequencies})} p_f(z')p(f|z')}$$

- $p(f|z)$ was obtained from training data and will not be reestimated

11-755 MLSP: Bhaskar Rao

Predicting from $P_1(f)$: Simplified Example



- A single Urn with only red and blue balls
- Given that out an unknown number of draws, exactly m were red, how many were blue?

One Simple solution:

- Total number of draws $N = m / P(\text{red})$
- The number of tails drawn $= N * P(\text{blue})$
- Actual multinomial solution is only slightly more complex

11-755 MLSP: Bhaskar Rao

The negative multinomial

- Given $P(X)$ for all outcomes X
- Observed $n(X_1), n(X_2) \dots n(X_k)$
- What is $n(X_{k+1}), n(X_{k+2}) \dots$

$$P(n(X_{k+1}), n(X_{k+2}), \dots) = \frac{\Gamma(N_o) \Gamma(\sum_{i \geq k} n(X_i))}{\Gamma(N_o + \sum_{i \geq k} n(X_i))} \prod_{i \geq k} p_o^{n(X_i)}$$

- N_o is the total number of observed counts
- $n(X_1) + n(X_2) + \dots$
- P_o is the total probability of observed events
- $P(X_1) + P(X_2) + \dots$

11-755 MLSP: Bhaskar Rao

- Note that we are using mixture weights estimated from the reduced set of observed frequencies
- This also gives us estimates of the *unobserved* frequencies
- Use the complete probability distribution $P_1(f)$ to predict the unobserved frequencies!

11-755 MLSP: Bhaskar Rao

$$P_1(f) = \sum_z p_1(z)p(f|z)$$

- Compose the complete probability distribution for each frame, using the mixture weights estimated in Step 2

Step 3 and Step 4: Recompose

Estimating unobserved frequencies

- Expected value of the number of draws from a negative multinomial:


$$\hat{N}_r = \frac{\sum_{f \in (\text{observed frequencies})} s_r(f)}{\sum_{f \in (\text{observed frequencies})} p_r(f)}$$

- Estimated spectrum in unobserved frequencies

$$\hat{s}_r(f) = N_r p_r(f)$$

11-755 MLSP: Bhaskara Raj


Prediction of Audio



- An example with random spectral holes

11-755 MLSP: Bhaskara Raj

Resolving the components




- The musician wants to follow the individual tracks in the recording..
 - Effectively "separate" or "enhance" them against the background

11-755 MLSP: Bhaskara Raj

Overall Solution

- Learn the "urns" for the signal source from broadband training data
- For each frame of the reduced bandwidth test utterance, find mixture weights for the urns
 - Ignore (marginalize) the unseen frequencies
- Given the complete mixture multinomial distribution for each frame, estimate spectrum (histogram) at unseen frequencies



11-755 MLSP: Bhaskara Raj

Signal Separation from Monaural Recordings

- Multiple sources are producing sound simultaneously
- The combined signals are recorded over a single microphone
- The goal is to selectively separate out the signal for a target source in the mixture
 - Or at least to enhance the signals from a selected source

11-755 MLSP: Bhaskara Raj

Separating the Sources: Cleaner Solution

- For each frame:
 - Given
 - $S_i(f)$ – The spectrum at frequency f of the mixed signal
 - $S_{i,l}(f)$ – The spectrum of the separated signal for the i -th source at frequency f
- A simple maximum a posteriori estimator

$$\hat{S}_{i,l}(f) = S_i(f) \frac{\sum_{\text{all } z} P_i'(z) P(f|z)}{\sum_{\text{all } z} P_i'(z) P(f|z)}$$

11-755 MLSP: Bhaskara Raj

Supervised separation: Example with two sources

Find mixture weights for all bases for each frame

$$P_i'(f) = \sum_{\text{all } z} P_i'(z) P(f|z) + \sum_{\text{for source } 2} P_i'(z) P(f|z)$$

11-755 MLSP: Bhaskara Raj

Supervised separation: Example with two sources

- Each source has its own bases
- Can be learned from unmixed recordings of the source
- All bases combine to generate the mixed signal
- Goal: Estimate the contribution of individual sources

11-755 MLSP: Bhaskara Raj

Supervised separation: Example with two sources

KNOWN A PRIORI

$$P_i'(f) = \sum_{\text{all } z} P_i'(z) P(f|z) + \sum_{\text{for source } 2} P_i'(z) P(f|z)$$

Semi-supervised separation: Example

Supervised separation: Example with two sources

two sources

- Find mixture weights for all bases for each frame
- Segregate contribution of bases from each source

$$P_i'(f) = \sum_{\text{all } z} P_i'(z) P(f|z) + \sum_{\text{for source } 2} P_i'(z) P(f|z)$$

11-755 MLSP: Bhaskara Raj

Supervised separation: Example with two sources

KNOWN A PRIORI

UNKNOWN

$$P_i'(f) = \sum_{\text{all } z} P_i'(z) P(f|z) + \sum_{\text{for source } 2} P_i'(z) P(f|z)$$


- Estimate from mixed signal (in addition to all $P_i'(z)$)

$$P_{\text{source } 2}'(f) = \sum_{\text{for source } 2} P_i'(z) P(f|z)$$

$$P_{\text{source } 2}'(f) = \sum_{\text{for source } 2} P_i'(z) P(f|z)$$

11-755 MLSP: Bhaskara Raj

Separating Mixed Signals: Examples



- "Raise my rent" by David Gilmour
- Background music "bases" learnt from 5-seconds of music-only segments within the song
- Lead guitar "bases" learnt from the rest of the song
- A more difficult problem: Original audio clipped!
- Background music bases learnt from 5 seconds of music-only segments


11-755 MLSP: Bhaskara Raj

Where it works

- When the spectral structures of the two sound sources are distinct
 - Don't look much like one another
 - E.g. Vocals and music
 - E.g. Lead guitar and music
- Not as effective when the sources are similar
 - Voice on voice

11-755 MLSP: Bhaskara Raj

Separate overlapping speech




- Bases for both speakers learnt from 5 second recordings of individual speakers
- Shows improvement of about 5db in Speaker-to-Speaker ratio for both speakers
- Improvements are worse for same-gender mixtures

11-755 MLSP: Bhaskara Raj

More on the topic

- Shift-invariant representations



- Four bars from a music example
- The spectral patterns are actually patches
 - Not all frequencies fall off in time at the same rate
- The basic unit is a spectral patch, not a spectrum
- Extend model to consider this phenomenon


11-755 MLSP: Bhaskara Raj

Patterns extend beyond a single frame

- Yes
- Tweaking
 - More training data per source
 - More bases per source
 - Typically about 40, but going up helps.
- Adjusting FFT sizes and windows in the signal processing
- And / Or algorithmic improvements
 - Sparse overcomplete representations
 - Nearest-neighbor representations
 - Etc..

11-755 MLSP: Bhaskara Raj

Can it be improved?




- Two distinct sounds occurring with different repetition rates within a signal

An Example

- Maximum likelihood estimate follows fragmentation and counting strategy
- Two-step fragmentation
 - Each instance is fragmented into the super urns
 - The fragment in each super-urn is further fragmented into each time-shift
- Since one can arrive at a given (t, f) by selecting any T from $P(T|Z)$ and the appropriate shift $t-T$ from $P(t|Z)$


Estimating Parameters

- Employs bag of spectrograms model
- Each "super-urn" (z) has two sub urns
 - One suburn now stores a bi-variate distribution
 - Each ball has a (t, f) pair marked on it – the bases
- Balls in the **other** suburn merely have a time "T" marked on them – the "location"



Shift-Invariant Model

- Assume generation by a single latent variable
 - Super urn
- The t -f basis is the "clean" spectrogram



Another example: Dereverberation


$$P(t, f | Z) = \frac{\sum_T P(T | Z) \sum_{t'} P(t' | Z) P(t - t', f | Z)}{\sum_T P(T | Z) \sum_{t'} P(t' | Z) P(t - t', f | Z)}$$

$$P(t, f | Z) = \frac{\sum_T P(T | Z) \sum_{t'} P(t' | Z) P(t - t', f | Z)}{\sum_T P(T | Z) \sum_{t'} P(t' | Z) P(t - t', f | Z)}$$

$$P(t, f | Z) = \frac{\sum_T P(T | Z) \sum_{t'} P(t' | Z) P(t - t', f | Z)}{\sum_T P(T | Z) \sum_{t'} P(t' | Z) P(t - t', f | Z)}$$


- Given data (spectrogram) $S(t, f)$
- Initialize $P(Z)$, $P(T|Z)$, $P(t,f|Z)$
- Iterate

Shift invariant model: Update Rules



The shift-invariant model


Dereverberation: an example



- “Basis” spectrum must be made sparse for effectiveness
- Dereverberation of gamma-tone spectrograms is also particularly effective for speech recognition

11-755 MLSP: Bhaskara Raj

The two-D Shift-Invariant Model



- Both sub-spots are distributions over (T, F) pairs
- One subspot represents the basic pattern
- The other subspot represents the *location*

11-755 MLSP: Bhaskara Raj

Two-D Shift Invariance: Estimation

- Fragment and count strategy
- Fragment into superpots, but also into each T and F
- Since a given (t, f) can be obtained from any (T, F)

$$P(t, f, Z) = P(Z) \prod_{f'} P(t, f' | Z) P(t, f - f' | Z) \quad P(T, F, t, f | Z) = P(T, F | Z) P(t - T, f - F | Z)$$


$$P(t, f, Z) = \frac{P(Z)}{P(t, f, Z)} \quad P(T, F, t, f | Z) = \frac{P(T, F | Z) P(t - T, f - F | Z)}{P(T, F, t, f | Z)}$$

$$P(Z) = \frac{\sum_{t,f} P(t, f, Z)}{\sum_{t,f} P(t, f, Z)} \quad P(T, F, t, f | Z) = \frac{\sum_{t,f} P(t, f, Z)}{\sum_{t,f} P(t, f, Z)}$$

$$P(t, f, Z) = \frac{\sum_{t,f} P(t, f, Z)}{\sum_{t,f} P(t, f, Z)} \quad P(T, F, t, f | Z) = \frac{\sum_{t,f} P(t, f, Z)}{\sum_{t,f} P(t, f, Z)}$$

11-755 MLSP: Bhaskara Raj

The shift-invariant model



$$P(t, f) = \sum_Z P(Z) \sum_T \sum_F P(T, F | Z) P(t - T, f - F | Z)$$


11-755 MLSP: Bhaskara Raj

Shift-Invariance: Comments

- $P(T, F | Z)$ and $P(t, f | Z)$ are symmetric
- Cannot control which of them learns patterns and which the locations
- Answer: Constraints
- Constrain the size of $P(t, f | Z)$
- I.e., the size of the basic patch
- Other tricks – e.g., sparsity

11-755 MLSP: Bhaskara Raj

Shift-Invariance in Two dimensions



- Patterns may be substructures
- Repeating patterns that may occur anywhere
- Not just in the same frequency or time location
- More apparent in image data


11-755 MLSP: Bhaskara Raj

Shift-Invariance in Many Dimensions


- The generic notion of “shift-invariance” can be extended to multivariate data
 - Not just two-D data like images and spectrograms
- Shift invariance can be applied to any subset of variables

Example: 3-D shift invariance

- The original figure has multiple handwritten renderings of three characters
 - In different colours
- The algorithm learns the three characters and identifies their locations in the figure




Constant Q representation of Speech




- Energy at the output of a bank of filters with logarithmically spaced center frequencies
 - Like a spectrogram with non-linear frequency axis
- Changes in pitch become vertical translations of spectrogram
 - Different notes of an instrument will have the same patterns at different vertical locations

Pitch Tracking




- Changing pitch becomes a vertical shift in the location of a basis
 - The constant-Q spectrogram is modeled as a single pattern modulated by a vertical shift
 - $P(f)$ is the “kernel” shown to the left

The constant Q transform




- Spectrographic analysis with a bank of constant Q filters
 - The bandwidth of filters increases with center frequency.
 - The spacing between filter center frequencies increases with frequency
 - Logarithmic spacing

Example: 2-D shift invariance




Pitch Tracking



- Having more than one basis (z) allows simultaneous pitch tracking of multiple sources
- Example: A voice and an instrument overlaid
- The “impulse” distribution shows pitch of both separately

11-755 MLSP: Bhaskara Raj

Pitch Tracking



- Left: A vocalized “song”
- Right: Chord sequence
- “Impulse” distribution captures the “melody”!

11-755 MLSP: Bhaskara Raj

In Conclusion

- Surprising use of EM for audio analysis
- Various extensions
- Sparse estimation
- Exemplar based methods..
- Related deeply to non-negative matrix factorization
- TBD..

11-755 MLSP: Bhaskara Raj