

18-452/18-750
Wireless Networks and Applications
Lecture 14: Wireless and the Internet

Peter Steenkiste

Spring Semester 2018

<http://www.cs.cmu.edu/~prs/wirelessS18/>

Peter A. Steenkiste

1

Wireless and the Internet Challenges

- IP addresses are used both to forward packets to a host and to identify the host
 - » Active session break when a host moves
 - » Mobile hosts are hard to find
- TCP congestion control interprets packet losses as a sign of congestion
 - » Assumes links are reliable, so packet loss = full queue
 - » Not true for wireless links!
- Applications generally assume that they are continuously connected to the Internet
 - » Can access servers, social networks, ...
 - » Mobile apps must support “disconnected” operations

Peter A. Steenkiste

2

Outline

- The Internet 102
- Wireless and the Internet
- Mobility: Mobile IP
- TCP and wireless
- Disconnected operation
- Disruption tolerant networks

Peter A. Steenkiste

3

Mobile IP Goals


- Communicate with mobile hosts using their “home” IP address
 - » Target is “nomadic” devices: do not move while communicating, i.e., laptop, not cellphone
 - » Allows any host to contact mobile host using its “usual” IP address
- Mobility should be transparent to applications and higher level protocols
 - » No need to modify the software
- Minimize changes to host and router software
 - » No changes to communicating host
- Security should not get worse

Peter A. Steenkiste

4

Mobile IP Operation

- Agents advertise their presence.
 - Using ICMP or mobile IP control messages
 - Mobile host can solicit agent information
 - Mobile host can determine where it is
- Registration process: mobile host registers with home and foreign agent.
 - Set up binding valid for *registration lifetime*
- Tunneling
 - forward packets to foreign agent
 - foreign agent forwards packets to mobile host
- Supporting mobility
 - invalidating old caches in a lazy fashion



5

Peter A. Steenkiste


Mobile IP

- Home network has a **home agent** that is responsible for intercepting packets and forwarding them to the mobile host.
 - E.g. router at the edge of the home network
 - Forwarding is done using tunneling
- Remote network has a **foreign agent** that manages communication with mobile host.
 - Point of contact for the mobile host
- Binding ties IP address of mobile host to a “care of” address.
 - binding = (IP address, foreign agent address)
 - binding includes time stamp

Peter A. Steenkiste

6

Tunneling IP-in-IP Encapsulation



7

Peter A. Steenkiste


Optimizations

- Mobile host can be its own the foreign agent.
 - Mobile host acquires local IP address
 - performs tasks of the mobile agent
- Short circuit the home location by going directly to the foreign agent.
 - Routers in the network store cache bindings and intercept and tunnel packets before they the mobile host's home network
 - Need a protocol to update/invalidate caches
 - Raises many security questions and is not in the standard

Peter A. Steenkiste

8

Registration via Foreign Agent




1. FA advertises service
2. MH requests service
3. FA relays request to HA
4. HA accepts (or denies) request and replies
5. FA relays reply to MH

Peter A. Steenkiste

9

Authentication



Dr. Evil will receive all the traffic destined to the mobile host

Peter A. Steenkiste

10

Mobile IP Authentication

- Without security, a “bad guy” on any network with a FA could issue a registration request for a host on any network (with a HA)
 - » HA would begin to forward datagrams to the bad guy
- Registration messages between a mobile host and its home agent must be authenticated
 - » Uses mobile-home authentication extension
- Mobile hosts, home agents, and foreign agents must maintain a mobility security association for mobile hosts, indexed by...
 - » Security Parameter Index (SPI)
 - » IP address (home address for mobile host)

Peter A. Steenkiste

11

Discussion

- Mobile IP not used in practice
- Not designed for truly mobile users
 - » Designed for nomadic users, e.g. visitors to a remote site
 - » Only solves the initial contact problem, but ...
- Mobile devices are typically clients, not servers, i.e., they initiate connections
 - » Problem Mobile IP solves is rare in practice
- IETF defined solutions that are more efficient
 - » But they are more heavy weight: effectively creates overlay with tunnels and special “routers”
- Ultimately all solutions are similar: need a “relay” that knows location of the device

Peter A. Steenkiste

12


Outline

- The Internet 102
- Wireless and the Internet
- Mobility: Mobile IP
- TCP and wireless
- Disconnected operation
- Disruption tolerant networks

Peter A. Steenkiste

13

Solution Ideas?



Peter A. Steenkiste

14


Solution Space

- **Modify TCP for wireless paths**
 - » Would maintain status quo for wired paths
 - » What would wireless TCP look like?
 - » Difficult to do: there are many Internet hosts
 - » Traditionally, hosts have no information about path properties
- **Modify TCP for all paths**
 - » Not clear what that modification would be!
 - » Similar problems: need to modify many hosts
- **Modify TCP only on the mobile host**
 - » A more practical idea – but what would the change be?
- **Keep end hosts the same but tweak things at the wireless gateway**
 - » Keep end-end TCP happy despite wireless links

Peter A. Steenkiste

15


Possible Classification of Solutions



Peter A. Steenkiste

16

I-TCP



Peter A. Steenkiste

17

Connection Split: Indirect TCP or I-TCP

- Do not change TCP on the wire-line part
- Split the TCP connection at the wireless gateway into two parts
 - » One optimized for the wireless link
 - » The second for the wire-line communication (TCP)
- No real transport-layer end-to-end connection
 - » Although host on wired network does not know this
- Wired host should not notice the characteristics of the wireless part
 - » This is a challenge since wireless gateway is limited in what it can send and when, e.g. cannot prematurely acknowledge data
 - » Certain things cannot be hidden: delay, dramatic throughput variations

Peter A. Steenkiste

18

I-TCP Discussion

I-TCP Advantages

- » No changes in the fixed network or hosts (TCP protocol), so all current TCP optimizations still work
- » Wireless transmission errors do not “propagate” to the wire-line network
- » Simple, effective (in the best case)


I-TCP Disadvantages

- » End-to-end semantics become less clear, e.g. what happens if the wireless gateway crashes?
- » Higher end-to-end delays due to buffering and forwarding to the gateway

Peter A. Steenkiste

19

Snooping TCP



Peter A. Steenkiste

20

Snooping TCP

- “Transparent” extension of TCP within the wireless gateway
 - » End hosts are not modified
- Hides wireless losses from wired host
 - » Buffer packets sent to the mobile host
 - » Local retransmission: Lost packets on the wireless link, for both directions, are retransmitted immediately by the mobile host or foreign agent
- Wireless gateway “snoops” the packet flow so it can cover up signs of packet loss
 - » E.g. recognizes acknowledgements in both directions and suppresses duplicate ACKs

Peter A. Steenkiste

21

Snooping TCP Discussion

- Data transfer to the mobile host
 - » FA buffers data until it receives ACK from the MH
 - » FA detects packet loss via duplicated ACKs or time-out
- Data transfer from the mobile host
 - » FA detects packet loss on the wireless link via sequence numbers
 - » FA answers directly with a NACK to the MH
 - » MH can now retransmit data with only a very short delay
- Integration of the MAC layer
 - » MAC layer often has similar mechanisms to those of TCP
- Problems
 - » Snooping TCP does not isolate the wireless (as I-TCP)
 - » Snooping might be useless if encryption is used

Peter A. Steenkiste

22

An Internet Style Approach

- Use aggressive retransmission in the wireless network to hide retransmission losses
 - » Most deployed wireless network in fact do that already
 - » Would sell few products if they did not
- Wireless losses translate into increased delay
 - » But TCP roundtrip time estimation is very conservative, e.g. increases if variance is high
- Also: persistent high loss rate results in reduced available bandwidth → congestion response is appropriate and needed
- Works remarkably well!
- Other solutions only needed for “challenged” networks

Peter A. Steenkiste

23

Outline

- The Internet 102
- Wireless and the Internet
- Mobility: Mobile IP
- TCP and wireless
- Disconnected operation
- Disruption tolerant networks

Peter A. Steenkiste

24

Disconnected Operation

- Mobility means that devices will occasionally be disconnected from the network
 - » Seconds ... Minutes ... Hours .. Days
 - » Mostly an issue for clients
- This can confuse systems and applications that assume a wired/stationary model
 - » Clients cannot access servers, e.g., mail, calendar applications, ...
 - » Distributed file systems
 - » Systems for back up or systems management
- Must adapt the applications and systems to make them “disconnection aware”

Peter A. Steenkiste

25

Two Examples

- E-mail: users must be able to “work on” e-mail offline and operations are performed when the mobile client is redirected
 - » Compose, read and delete e-mail
 - » Possibly others: manage folders, etc.
- Calendars and tasks are similar: operations performed offline must be executed later
 - » Adding or removing appointment and tasks, ...
- Must sometimes resolve conflicts when multiple clients are used offline
 - » E.g., mail is deleted on one client and moved to another folder on another – delete or keep?
 - » Tend to be minor – ask user for help if needed

Peter A. Steenkiste

26

More Complex Case: File System

- A distributed file system can be accessed from many computers
 - » Files tend to be cached in the computers
- Creates opportunities for inconsistencies
 - » E.g., a file is modified on two different computers – how do you merge the changes? Who is responsible?
- The consistency model depends on the file system
 - » Stronger consistency requires that the system can keep track of all copies and remove/lock them if needed
- Disconnected operation makes the consistency problem harder!
 - » Some file copies may be inaccessible for long periods!

Peter A. Steenkiste

27

Mobility is Common Today

- Many applications are designed to work on mobile clients so they deal properly with disconnections
 - » Many apps on mobile devices are designed for mobility
 - » Most clients server applications can work offline with at least partial functionality
- Does not work for interactive applications
 - » Games, etc.
- Disconnection can still be very inconvenient
 - » Need state that is not cached on your client device
 - » Things like back ups cannot be performed
 - » Unpredictable delays in communication

Peter A. Steenkiste

28

Outline

- The Internet 102
- Wireless and the Internet
- Mobility: Mobile IP
- TCP and wireless
- Disconnected operation
- Disruption tolerant networks

Peter A. Steenkiste

Based on slides by Kevin Fall

29


Challenged Networks

- **Violate one or more of Internet's assumptions**
 - » End-points may rarely/never be online at the same time
 - » Very long delay path, frequent disconnections, ...
 - » Have naming semantics for their particular application domain
 - » Not be well served by the current end-to-end TCP/IP
- **Examples**
 - » Terrestrial mobile networks
 - » Some ad-hoc networks
 - » Sensor/actuator networks
- **Goals for “disruption tolerant” networks**
 - » Achieve **interoperability** between very diverse types networks
 - » Sometimes also called disruption tolerant

Peter A. Steenkiste

30

Background



Peter A. Steenkiste

31

High-level Architecture

- **Characteristics:**
 - » Operate as an **overlay** above the existing transport layers
 - » Based on an abstraction of **message switching**
 - Bundle
 - Bundle forwarder (DTN gateway)
 - **Store-and-forward** gateway function between different networks




- **Constituent of DTN architecture**
 - » Region: internally homogenous, i.e. same network stack, addressing, ...
 - » DTN gateway: Interconnection point between region boundaries
 - » Name Tuple: {Region name, Entity name}

Peter A. Steenkiste

32

Example DTN



Peter A. Steenkiste

33